HISTORY

Model Name : KDF-E42A10/E50A10
SERVICE MANUAL
Part No. : 9-872-749-03

When clicking an item, it's detail is displayed.

Date	SUPP./CORR.	Description of SUP/COR	Change of main text
2005.6	–	NEW	–
2005.8	CORR.-1	Addition of LAMP XL-2400 (Page 72)	Yes
2005.10	CORR.-2	Deleted of LAMP BLOCK ASSY (Page 62)	Yes

Self Diagnosis Supported model

SERVICE MANUAL MIX5 CHASSIS

MODEL	COMMANDER	DEST.	CHASSIS NO.
KDF-E42A10	RM-YD003	USA	
KDF-E42A10	RM-YD003	CANADA	
KDF-E42A10	RM-YD003	MEXICO	
KDF-E50A10	RM-YD003	USA	
KDF-E50A10	RM-YD003	CANADA	
KDF-E50A10	RM-YD003	MEXICO	

MODEL	COMMANDER	DEST.	CHASSIS NO.



KDF-E42A10/E50A10

RM-YD003

LCD PROJECTION TV

SONY®

Specifications

Projection System	3 LCD Panels, 1 lens projection system	
LCD Panel	0.73 inch TFT LCD panel (1,280 · 720 pixels)	
Projection Lens	High Performance, large diameter hybrid lens F2.4	
Antenna	75-ohm external terminal for VHF/UHF	
Lamp	100W, XL-2400	
Television System	NTSC	American TV Standard
	ATSC (8VSB terrestrial)	ATSC compliant 8VSB
	QAM on cable	ANSI/SCTE 07 2000
Visible Screen Size (Picture measured diagonally)	KDF-E42A10: 42 inches KDF-E50A10: 50 inches	
Channel Coverage	Terrestrial (analog)	2-69
	Cable TV (analog)	1-125
	Terrestrial (digital)	2-69
	Cable TV (digital)	1-135
Number of Inputs/Outputs		
HDMI IN	Video	1080i, 720p, 480p, 480i
	Audio	Two channel linear PCM 32, 44.1 and 48 kHz, 16, 20 and 24 bit
Video (IN)	3 total (1 on side panel)	1 Vp-p, 75 ohms unbalanced, sync negative
S Video (IN)	1	Y: 1 Vp-p, 75 ohms unbalanced, sync negative C: 0.286 Vp-p (Burst signal), 75 ohms
Audio (IN)	5 total (1 on side panel)	500 mVrms (100% modulation) Impedance: 47 kilohms
Component Video Input	2 (Y P_B/C_B P_R/C_R)	Y: 1 Vp-p, 75 ohms unbalanced, sync negative P_B/C_B: 0.7 Vp-p, 75 ohms P_R/C_R: 0.7 Vp-p, 75 ohms
AUDIO (VAR/FIX) OUT	1	500 mVrms at the maximum volume setting (Variable) 500 mVrms (Fixed) Impedance (output): 2 kilohms ✍ AUDIO OUT jacks are operable only when the TV's Speaker is set to Off.
RF Inputs	2	
PC Input	1	
Digital Audio Optical Output (PCM/Dolby Digital)	1	Optical Rectangular (1)
CableCARD Slot	PCMCIA Type I/II	
Speaker output	12 W + 12 W	
Power requirement	120 V, 60 Hz	
Power consumption	In use: 210 W In standby: Less than 17 W	

Dimensions (W/H/D)	KDF-E42A10: 999 · 722 · 357 mm (39 3/8 · 28 1/2 · 14 1/8 inches) KDF-E50A10: 118 4· 827 · 408 mm (46 5/8 · 32 5/8 · 16 1/8 inches)
Mass	KDF-E42A10: 28 kg (61 lb. 12 oz.) KDF-E50A10: 33 kg (72 lb. 13 oz.)
Supplied Accessories	
Remote Control	RM-YD003
AA (R6) Batteries	2 supplied for remote control
Operating Instructions	1
Quick Setup Guide	1
Warranty Card	1
Product Registration Card	1

Optional accessories:

- ❑ HDMI cable
- ❑ HDMI-to-DVI cable
- ❑ Component video cable
- ❑ S VIDEO cable
- ❑ A/V cable
- ❑ Audio cable
- ❑ Optical cable
- ❑ TV Stand : (SU-RG11S for KDF-E42A10, SU-RG11M for KDF-E50A10)
- ❑ Theatre Stand System: RHT-G2000
- ❑ Lamp : XL-2400

✍ **The availability of optional accessories depends on stock.**

Design and specifications are subject to change without notice.
Non-metric weights and measures are approximate.

Indicators



The indicators show the current status of your TV. If there is a change in the condition or a problem with the TV, the indicators will flash or light up in the manner described below to let you know that it requires your attention.

Indicator	Flashing because...
POWER/ STANDBY flashing	green : The lamp for the light source is preparing to turn on. When it is ready, it turns on. red : The lamp door or the lamp is not securely attached. The red indicator will continue to flash in intervals of three blinks at a time until the lamp door or the lamp is placed correctly. When the lamp door or the lamp is securely attached, the TV will turn on with green indicator.
LAMP indicator flashes	The projection lamp has burned out. Replace it with new one (see page 86).
TIMER indicator is lit	When one of the timers is set, the indicator will remain lit (will not flash) even when the TV is turned off.

Projection Lamp

Your TV uses a projection lamp as its light source. As with any lamp, it has lifespan and needs to be replaced when the Lamp indicator flashes or the screen becomes darker. Note the following:

- ❏ After turning on your TV, it may take a while (1 minute or less) before the picture appears.
- ❏ When the projection lamp wears out, the screen goes dark. Replace the lamp with a new Sony XL-2400 replacement lamp (not supplied).

✍ **The light emitted from the lamp is quite bright when your TV is in use. To avoid eye discomfort or injury, do not look into the light housing when the power is on.**

Replacing the Lamp

The projection lamp, which illuminates the picture, has a limited life.

If the screen becomes dark, the color looks unusual, or the LAMP indicator on the front of the TV flashes, it is time to replace the lamp with a new one (not supplied).

> ⚠ **WARNING**
>
> **Electric appliances can cause fire or high temperature, resulting in injury or death. Be sure to follow the instructions below.**

- ❑ Use a Sony XL-2400 replacement lamp (not supplied) for replacement. Use of any other lamp may damage the TV.
- ❑ Do not remove the lamp for any purpose other than replacement. Doing so may cause injury or fire.
- ❑ Do not put flammable materials and metal objects inside the lamp receptacle of the TV after removing the lamp. Doing so may cause fire or electrical shock. Do not touch the lamp receptable once the lamp has been removed.
- ❑ When the lamp eventually burns out, you may hear a noticeable pop sound. This is normal and it is inherent to this type of lamp.
- ❑ In rare instances, the bulb may pop inside the lamp unit, but the lamp unit is designed to contain all of the broken glass pieces inside the lamp unit.
- ❑ The lamps contain mercury. For proper disposal of the used lamps, follow and observe the local ordinances. See page 89.

How to Replace the Lamp

1 Turn off the power on the main unit. Wait several minutes, then unplug the power cord.
(The cooling fan will continue to operate for about two minutes after turning the power off.)

2 Wait at least 30 minutes after unplugging the power cord to allow the lamp to cool down before replacing it. To avoid being burned, do not touch the lamp receptable once the lamp has been removed.

3 Take the new lamp out of the box.
Do not touch the glass portion of the new lamp.

> ✍ **Do not shake the lamp. Vibration can damage the lamp or shorten its life.**
>
> ✍ **Avoid touching the front glass of a new lamp or the glass of the lamp receptacle. This may reduce picture quality or lamp life.**

4 Remove the outside lamp cover.



5 Remove the lamp door.

Turn the knob counterclockwise to OPEN and pull out the cover.



6 Pull out the lamp.

Hook a finger through the loop of the lamp handle and pull the handle upwards. Then pull the lamp straight out.



✍ **The lamp is very hot immediately after use. Never touch the glass portion of the lamp or the surrounding parts.**

✍ **After the used lamp has cooled, place it into the empty box of the replacement lamp. Never put the used lamp into a plastic bag.**

7 Put the new lamp into its place.

Mount the new lamp securely. Failure to do so may cause a fire or the screen to go dark.



✍ **If the lamp is not securely reattached, the self-diagnostic function may be triggered and the POWER/STANDBY indicator flashes three times (see page 12).**

8 Reattach the lamp door.

Turn the knob back to CLOSE and secure the cover.



9 Put the outside lamp cover back in its place.



✍ **Consult your Sony dealer for a Sony XL-2400 replacement lamp.**

✍ **Take great care when replacing the lamp or plugging in/unplugging the connecting cords. Rough handling may cause the TV to fall, damaging the TV, the TV stand and the floor.**

The used lamp

This product contains mercury. Disposal of this product may be regulated if sold in the United States. For disposal or recycling information, please contact your local authorities or the Electronics Industries Alliance (http://www.eiae.org).

❑ Do not leave the used lamp near flammable materials or within the reach of children.

❑ Do not pour water onto the used lamp or put any object inside the lamp. Doing so may cause the lamp to burst.

For replacement lamp information visit:
U. S. residents: http://www.sonystyle.com/tv/
Canadian residents: http://www.sonystyle.ca/tv/

SAFETY CHECK-OUT

(US model only)

After correcting the original service problem, perfom the following safety checks before releasing the set to the customer:

1. Check the area of your repair for unsoldered or poorly-soldered connections. Check the entire board surface for solder splashes and bridges.
2. Check the interboard wiring to ensure that no wires are "pinched" or contact high-wattage resistors.
3. Check that all control knobs, shields, covers, ground straps, and mounting hardware have been replaced. Be absolutely certain that you have replaced all the insulators.
4. Look for unauthorized replacement parts, particularly transistors, that were installed during a previous repair. Point them out to the customer and recommend their replacement.
5. Look for parts which, through functioning, show obvious signs of deterioration. Point them out to the customer and recom mend their replacement.
6. Check the line cords for cracks and abrasion. Recommend the replacement of any such line cord to the customer.
7. Check the condition of the monopole antenna (if any). Make sure the end is not broken off, and has the plastic cap on it. Point out the danger of impalement on a broken antenna to the customer, and recommend the antenna's replacement.
8. Check the B+ and HV to see they are at the values specified. Make sure your instruments are accurate;be suspicious of your HV meter if sets always have low HV.
9. Check the antenna temminals, metal trim, "metallized" knobs, screws, and all other exposed metal parts for AC leakage. Check leakage as described below.

LEAKAGE TEST

The AC leakage from any exposed metal part to earth ground and from all exposed metal parts to any exposed metal part having a return to chassis, must not exceed 0.5mA (500 microampers) . Leakage current can be measured by any one of three methods.

1. A commercial leakage tester, such as the Simpson 229 or RCA WT-540A. Follow the manufacturers' instructions to usc these instruments.
2. A battery-operated AC milliammeter. The Data Precision 245 digital multimeter is suitable for this job.
3. Measuring the voltage drop across a resistor by means of a VOM or battery-operated AC voltmeter. The "limit" indication is 0.75V, so analog meters must have an accurate low-voltage scale. The Simpson 250 and Sanwa SH-63Trd are examples of a passive VOM that is suitable. NearIy all battery operated digital multimeters that have a 2V AC range are suitable. (See Fig. A)

HOW TO FIND A GOOD EARTH GROUND

A cold-water pipe is guaranteed earth ground;the cover-plate retaining screw on most AC outlet boxes is also at earth ground. If the retaining screw is to be used as your earth-ground, verify that it is at ground by measuring the resistance between it and a cold-water pipe with an ohmmeter. The reading should be zero ohms. If a cold-water pipe is not accessible, connect a 60-l00 watts trouble light (not a neon lamp) between the hot side of the receptacle and the retaining screw. Try both slots, if necessary, to locate the hot side of the line, the lamp should light at normal brilliance if the screw is at ground potential. (See Fig. B)



Fig. A. Using an AC voltmeter to check AC leakage.



Fig. B. Checking for earth ground.

CAUTION

These servicing instructions are for use by qualified service personnel only.
To reduce the risk of electric shock, do not perform any servicing other than that contained in the operating instructions unless you are qualified to do so.

WARNING!!
AN ISOLATION TRANSFORMER SHOULD BE USED DURING ANY SERVICE TO AVOID POSSIBLE SHOCK HAZARD, BECAUSE OF LIVE CHASSIS.
THE CHASSIS OF THIS RECEIVER IS DIRECTLY CONNECTED TO THE AC POWER LINE.

SAFETY-RELATED COMPONENT WARNING!!
COMPONENTS IDENTIFIED BY SHADING AND MARK ⚠ ON THE SCHEMATIC DIAGRAMS, EXPLODED VIEWS AND IN THE PARTS LIST ARE CRITICAL TO SAFE OPERATION. REPLACE THESE COMPONENTS WITH SONY PARTS WHOSE PART NUMBERS APPEAR AS SHOWN IN THIS MANUAL OR IN SUPPLEMENTS PUBLISHED BY SONY. CIRCUIT ADJUSTMENTS THAT ARE CRITICAL TO SAFE OPERATION ARE IDENTIFIED IN THIS MANUAL. FOLLOW THESE PROCEDURES WHENEVER CRITICAL COMPONENTS ARE REPLACED OR IMPROPER OPERATION IS SUSPECTED.

ATTENTION!!
AFIN D'EVITER TOUT RISQUE DELECTROCUTION PROVENANT D'UN CHÁSSIS SOUS TENSION, UN TRANSFORMATEUR D'ISOLEMENT DOIT ETRE UTILISÉ LORS DE TOUT DEPANNAGE.
LE CHÁSSIS DE CE RECEPTEUR EST DIRECTEMENT RACCORDÉ Á L'ALIMENTATION SECTEUR.

ATTENTION AUX COMPOSANTS RELATIFS ÁLA SÉCURITÉ!!
LES COMPOSANTS IDENTIFIÉS PAR UNE FRAME ET PAR UNE MAPQUE ⚠ SUR LES SCHÉMAS DE PRINCIPE, LES VUES EXPLOSÉES ET LES LISTES DE PIECES SONT D'UNE IMPORTANCE CRITIQUE POUR LA SÉCURITÉ DU FONCTIONNEMENT. NE LES REMPLACER QUE PAR DES COMPOSANTS SONY DONT LE NUMÉRO DE PIÉCE EST INDIQUÉ DANS LE PRÉSENT MANUEL OU DANS DES SUPPLÉMENTS PUBLIÉS PAR SONY. LES RÉGLAGES DE CIRCUIT DONT L'IMPORTANCE EST CRITIQUE POUR LA SÉCURITÉ DU FONCTIONNEMENT SONT IDENTIFIES DANS LE PRÉSENT MANUEL. SUIVRE CES PROCÉDURES LORS DE CHAQUE REMPLACEMENT DE COMPOSANTS CRITIQUES, OU LORSQU'UN MAUVAIS FONCTIONNEMENT SUSPECTÉ.

TABLE OF CONTENTS

Section	Title	Page
1.	**SELF DIAGNOSIS FUNCTION**	11
2.	**DISASSEMBLY**	
2-1.	Rear Cover	16
2-2.	Service Position	17
2-3.	Antenna Switch, QU Block Assembly	18
2-4.	K Board	19
2-5.	Terminal Bracket	19
2-6.	HPC Board	19
2-7.	B Block	20
2-8.	OU Bracket	20
2-9.	B Board	20
2-10.	B, QM and QT Boards	21
2-11.	QT Board	21
2-12.	QM Board	21
2-13.	P Board	21
2-14.	AGU Board	22
2-15.	DC Fan	22
2-16.	Main Duct (R)	23
2-17.	Duch Block Assembly (Without Main Duct (R))	23
2-18.	D.C. Fan (Sirocco)	23
2-19.	Speaker Grill Block Assembly	23
2-20.	HA and HB Boards	24
2-21.	Screen Frame Block Assembly	24
2-22.	Speakers	24
2-23.	Rear Cover (With Mirror)	24
2-24.	How to Replace Optics Unit	25
2-24-1.	Remove Lamp Bloxk (1)	25
2-24-2.	Remove Lamp Bloxk (2)	25
2-24-3.	Remove Lamp Bloxk (3)	25
2-24-4.	Remove Cover, Rear (1)	25
2-24-5.	Remove Cover, Rear (1-2)	25
2-24-6.	Remove Cover, Rear (2)	25
2-24-7.	Remove Stay (L), Side	26
2-24-8.	Pull Out Some Blocks (1)	26
2-24-9.	Pull Out Some Blocks (2)	26
2-24-10.	Pull Out Some Blocks (3)	26
2-24-11.	Pull Out Some Blocks (4)	26
2-24-12.	Pull Out Some Blocks (5)	27
2-24-13.	Pull Out Some Blocks (6)	27
2-24-14.	Pull Out Some Blocks (7)	27
2-24-15.	Pull Out Some Blocks (8)	28
2-24-16.	Pull Out Some Blocks (9)	28
2-24-17.	Pull Out Some Blocks (10)	28
2-24-18.	Remove Optics Unit	28
3.	**ELECTRICAL ADJUSTMENTS**	
3-1.	Electrical Adjustment by Remote Commander	29
3-1-1.	Method of Setting the Service Adjustment Mode	29
3-1-2.	Service Mode Adjustment	29
3-1-3.	Memory Write Confirmation Method	29
3-1-4.	Adjusting Buttons and Indicator	29
3-2.	To read Lamp and Panel time	30
3-3.	Test Reset	30
4.	**DIAGRAMS**	
4-1.	Block Diagram (1)	31
	Block Diagram (2)	32
	Block Diagram (3)	33
	Block Diagram (4)	34
	Block Diagram (5)	35
	Block Diagram (6)	36
	Block Diagram (7)	37
4-2.	Frame Schematic Diagram	38
4-3.	Circuit Boards Location	39
4-4.	Schematic Diagrams	39
(1)	Schematic Diagram of GT Board	40
(2)	Schematic Diagram of HA Board	41
(3)	Schematic Diagram of HB Board	42
(4)	Schematic Diagram of HC Board	43
(5)	Schematic Diagram of K Board	44
(6)	Schematic Diagram of QT (1/3) Board	45
(7)	Schematic Diagram of QT (2/3) Board	46
(8)	Schematic Diagram of QT (3/3) Board	47
(9)	Schematic Diagram of QU Board	48
(10)	Schematic Diagram of S2 Board	49
(11)	Schematic Diagram of T1 Board	50
(12)	Schematic Diagram of T2 Board	51

Section	Title	Page
4-5.	Printed Wiring Boards	52
(1)	GT Board	52
(2)	HA, HB Boards	53
(3)	HC, K Boards	54
(4)	QT Board	55
(5)	QU Board	56
(6)	S2 Board	57
(7)	T1, T2 Boards	58
4-6.	Semiconductors	59

5. EXPLODED VIEWS

5-1.	Screen Mirror Block, Cover	60
5-2.	B Block, Chassis Assembly	61
5-3.	Lamp Duct Assembly, Optics Unit Block	62

6. ELECTRICAL PARTS LIST

- GT Board 63
- HA Board 65
- HB Board 65
- HC Board 66
- HPC Board 66
- K Board 67
- QT Board 69
- QU Board 71
- S2 Board 71
- T1 Board 71
- T2 Board 71

SECTION 1
SELF DIAGNOSIS FUNCTION

1. Summary of Self-Diagnosis Function

- This device includes a self-diagnosis function.
- In case of abnormalities, the POWER/STANDBY indicator automatically blinks. It is possible to predict the abnormality location by the number of blinks. The Instruction Manual describes blinking of the POWER/STANDBY indicator.
- If the symptom is not reproduced sometimes in case of a malfunction, there is recording of whether a malfunction was generated or not. Operate the remote command to confirm the matter on the screen and to predict the location of the abnormality.

2. Diagnosis Items and Prediction of Malfunction Location

- When a malfunction occurs the POWER/STANDBY indicator only blinks for one of the following diagnosis items. In case of two or more malfunctions, the item which first occurred blinks. If the malfunctions occurred simultaneously, the item with the lower blink count blinks first.
- The screen display displays the results regarding all the diagnosis items listed below. The display "0" means that no malfunctions occurred.

Diagnosis Item	Number of times POWER/STANDBY indicator blinks	Probable Cause Location	Defected symptoms
Temp error	2 times	- Set temperture is high. - Temp sensor connector is not attached securely. (CN7020 on HB board, CN7180 on S2 board)	- No picture/No sound
Lamp cover error	3 times	- Lamp cover is not attached securely. -Lamp is not set securely.	- No picture/No sound
Fan stopped	4 times	- Fan 1-4 power is not supplied. (AGU board) - Fan connector is not attached securely. -Fan caught wires or harnesses.	- No picture/No sound
Lamp driver error	5 times	- Lamp driver is faulty.	- No picture/No sound
Low B error	6 times	- B_12V is not supplied. (GT board)	- No picture/No sound
Audio error	7 times	- Short-circuit of Audio power supply line. -Blow out of fuse. (PS3001 on K board) -IC failure. (IC3005 on K board)	- No picture/No sound
D-OVP error	8 times	-B -12V is over voltage. (B board)	- No picture/No sound
ATSC OVP	10 times	-Q_10.5V is over voltage. (GT board)	- No picture/No sound
Lamp error	LAMP-LED flashes	- Lamp for the light source burns out.	- No picture/No sound

3. Blinking count display of POWER/STANDBY indicator

- One blink is not used for self-diagnosis.



- Example

Diagnosis item	LED blinks
Lamp cover	3 times
Fan	4 times



- Release of POWER/STANDBY indicator blinking

The POWER/STANDBY indicator blinking display is released by removing the plug from the power or leaving for 2 minutes.

4. Self-diagnosis screen displays

- In cases of malfunctions where it is not possible to determine the symptom such as when the power goes off occasionally or when the screen disappears occasionally, there is a screen display on whether the malfunction occurred or not in the past (and whether the detection circuit operated or not) in order to allow confirmation.

<Screen Display Method>

- Quickly press the remote command button in the following order from the standby state.

DISPLAY → Channel 5 → Vol - → POWER

Be aware that this differs from the method of entering the service mode (Vol +).

SELF CHECK

1	: LAMP_ERROR	0
2	: TEMP_ERROR	0
2	: LAMP_TEMP	0
3	: LAMP_COVER	0
4	: FAN_ERROR	0
5	: LAMP_DRIVER	1
6	: LOWB_ERROR	0
7	: AUDIO_PROT	0
8	: D_OVP	0
10	: ATSC_OVP	0

- Numeral "1" means a fault was detected one time
- Numeral "0" means that no fault was detected

- The results display is not automatically cleared. In case of repairs and after repairs, check the self-diagnosis screen and be sure to return the results display to "0".
- If the results display is not returned to "0" it will not be possible to judge a new malfunction after completing repairs.

<Method of Clearing Results Display>

1. Power off (Set to the standby mode)
2. DISPLAY → Channel 5 → Vol - → POWER
3. Channel 8 → ENTER

<Method of Ending Self-Diagnosis Screen>

- When ending the self-diagnosis screen completely, turn the power switch OFF on the remote commander or the main unit.

5. Self-Diagnosis function operation

2	:	Temp	When the temperature sensor on the S2 board detects high temperature, or IIC line connector (CN8410:AGU board, CN7180:S2 board) is not seated securely, the TV-micro tums off the lamp. When the temperature sensor on the HB board detects high temperature, or IIC line connector (CN8004:AGU board, CN7020:HB board) is not seated securely, the TV-micro tums off the lamp.
3	:	Lamp cover	The rib at the back of the lamp cover closes the SW on the T1 board. The lamp closes the SW on the T2 board. It is monitored by the BE micro (pin133 of IC4100) and tums off the lamp when it is opened.
4	:	Fan	Fan rotation is detected by ‘‘FAN-PROT” and the TV-micro (pin 38 of IC8002) tums off the lamp when it is ‘‘high”.
5	:	Lamp Driver	When the ‘‘LAMP-PROT” (pin132 of IC4100) is high, the lamp is not tumed on. If the ‘‘LAMP-HV-DET” (pin134 of IC4100) is low at the same time, it is classified as no high voltage of the lamp driver.
6	:	Low B error	When no ‘‘B_12V” is detected, pin 128 of TV-micro is low and it tums off the main power.
7	:	Audio	When DC voltage is detected at the speaker output, pin 149 of TV-micro is low and it tums off the main power.
8	:	D-OVP	When overvoltage of ‘‘B_12V” is detected, pin 127 of TV-micro is low and it tums off the main power.
10	:	ATSC-OVP	When overvoltage of ‘‘Q_10.5 V” is detected, pin 126 of TV-micro is low and it tums off the main power.
LAMP	:	Lamp	When the ‘‘LAMP-PROT” (pin132 of IC4100) is high, the lamp is not tumed on. If the ‘‘LAMP-HV-DET” (pin134 of IC4100) is high at the same time, it is classified as no lamp or a dead lamp.

BLOCK DIAGRAM



Reading Lamp and Panel time

Use the following to determine the lamp and panel time of a set.

Screen Display Method

In standby mode, press the buttons on the Remote Commander sequentially, in rapid succession, as shown below:

1. Press [Display] ➡ Channel [5] ➡ Sound Volume [+] ➡ Power ON

2. To enter BE-micro service menu, press JUMP 2 times.

CONFIGRATION	00		SERVICE
CP18_COLOR_SYS	00	00A0	BE Micro

⬇ Press Channel-4

3. To display the lamp time, press Channel-4.

   The screen displays:
   " Total lamp time is 14 hours"

GW_SPECIAL	34		SERVICE
LAMP_TIME	02	00000014	BE Micro

⬇ Press Channel-4

4. To display the panel time, press Channel-4.

   The screen displays:
   " Total panel time is 14 hours"

GW_SPECIAL	34		SERVICE
PANEL_TIME	01	00000014	BE Micro

⬇ Press Channel-5 7 times, Channel-1

5. To display the lamp time clear, press Channel-5 7 times and Channel-1.

OPTION_E	20		SERVICE
LAMP	01	0000	BE Micro

To reset the lamp time press Channel-3 > MUTING > ENT.
WRITE (Character color is red) is momentarily displayed and the lamp time is reset to "0".

Exiting Service Mode

After completing the changes exit service mode by turning off the set using the Remote Commander or the power switch.

SECTION 2
DISASSEMBLY

2-1. REAR COVER

E42A10





E50A10



2-2. SERVICE POSITION



Ⓐ



Ⓑ



Ⓒ









2-3. ANTENNA SWITCH, QU BLOCK ASSEMBLY









2-4. K BOARD







2-5. TERMINAL BRACKET



2-6. HPC BOARD



2-7. B BLOCK





2-8. OU BRACKET





2-9. B BOARD





2-10. B, QM AND QT BOARDS



2-11. QT BOARD





2-12. QM BOARD



2-13. P BOARD



2-14. AGU BOARD



2-15. DC FAN







2-16. MAIN DUCT (R)



2-17. DUCT BLOCK ASSEMBLY (WITHOUT MAIN DUCT (R))



2-18. D.C. FAN (SIROCCO)



2-19. SPEAKER GRILL BLOCK ASSEMBLY





2-20. HA AND HB BOARDS



2-21. SCREEN FRAME BLOCK ASSEMBLY





2-22. SPEAKERS



2-23. REAR COVER (WITH MIRROR)



2-24. HOW TO REPLACE OPTICS UNIT

2-24-1. Remove Lamp Block (1)

Remove " Door, Lamp ".



2-24-2. Remove Lamp Block (2)

Turn left "Lever, Lock" below, and then remove "Door, Lamp".



2-24-3. Remove Lamp Block (3)

Pull the "Lever, Lock" below to remove "Lamp block".



2-24-4. Remove Cover, Rear (1)

Take off 11 screws (42"), and then pull out "Cover, Rear".



2-24-5. Remove Cover, Rear (1-2)

Take off 13 screws (50").



2-24-6. Remove Cover, Rear (2)

It is removed "Cover, Rear".

2-24-7. Remove Stay (L), Side

Take off 4 screws, and then remove 2 "Stay (L), Side".



2-24-8. Pull Out Some Blocks (1)

Take off 4 screws.



2-24-9. Pull Out Some Blocks (2)

Take off 5 screws.



2-24-10. Pull Out Some Blocks (3)

Pull out "B block", "Chassis block", and "Duct (R), Main" a little bit.



2-24-11. Pull Out Some Blocks (4)

Unlock "Holder, Wire" as shown below.



2-24-12. Pull Out Some Blocks (5)

Take off 1 screw.



< F >



2-24-13. Pull Out Some Blocks (6)

Loose 1 special screw. (This screw can not be taken off.)



< G >

2-24-14. Pull Out Some Blocks (7)

Take off 1 screw.



< H >

2-24-15. Pull Out Some Blocks (8)

Remove 2 connecters to pull out some blocks as shown below.

< I >



2-24-16. Pull Out Some Blocks (9)

Unlock "Purse Lock" to pull out some blocks as shown below.



< J >



2-24-17. Pull Out Some Blocks (10)

Pull out "B block", "Chassis block", "Duct block", and "Optics Unit block".



2-24-18. Remove Optics Unit

Remove all connecters to remove "Optics Unit block" and then it.



SECTION 3
ELECTRICAL ADJUSTMENTS

3-1. ELECTRICAL ADJUSTMENT BY REMOTE COMMANDER

By using remote commander (RM-YD003), all circuit adjustments can be made.

NOTE : Test Equipment Required.

1. Pattern Generator (with component outputs)
2. Oscilloscope
3. Digital multimeter

3-1-1. Method of Setting the Service Adjustment Mode

1. Standby mode. (Power off)
2. DISPLAY → 5 → VOL (+) → TV POWER
   on the remote commander.
   (Press each button within a second.)
   The following service screen will appear.

<TV micro>

```
STATUS              0              SERVICE
SHUTDOWN_LOG1       0           TV MICRO

ATI                              : H05-01.xx
SAIPH     PROGRAM                : 1.xxx
          BOOT                   : x.xxx
CHIMERA   PROGRAM                : 1.xxx
          PACK                   : 1.xxx
          OSD                    : x.xxx
          NVM A0                 : x.xxx
          NVM AC                 : x.xxx
          NVM AE                 : ----
HDMI                             : 1.xxx
```

Press “JUMP” key.

<Digiotal Module micro>

```
QM                  0       0       SERVICE
INFO                                    DTV
```

Press “JUMP” key.

<BE micro>

```
CONFIGRATION  00        0           SERVICE
CP18_COLOR_SYS  00  00A0            BE Micro
```

Press “JUMP” key.

3-1-2. Service Mode Adjustment

1. The SCREEN displays the item being adjusted.
2. Press “①” or “④” on the remote commander to select the adjustment item.
3. Press “③” or “⑥” on the remote commander to change the data.
4. Press “②” or “⑤” on the remote commander to select the category. Every time you press “②” (Category up).
5. If you want to recover the latest values press “⓪” then “ENTER” to read the memory.
6. Press “MUTING” then “ENTER” to write into memory.
7. Turn power off.

<Method of setting the shipping condition>

1. Service Adjustment mode.
2. Press “⑧” then “ENTER”
3. Wait until appearing “ Initial Setup” display.
4. Disconnect AC plug and connect again to change factory reset condition completely.

3-1-3. Memory Write Confirmation Method

1. After adjustment, turn power off with the remote commander.
2. Turn power on and set to service mode.
3. Call the adjusted items again and confirm they were adjusted.

3-1-4. Adjusting Buttons and Indicator



RM-YD003

FUNCTION OF KEYS ON COMMANDER

- ① : Changes adjustment item. (item No. moves up)
- ④ : Changes adjustment item. (item No. moves down)
- ② : Changes adjustment category. (category moves up)
- ⑤ : Changes adjustment category. (category moves down)
- ③ : Changes data value. (up)
- ⑥ : Changes data value. (down)

Commander Function

Button	Mode	Description
MUTING + ENTER	WRITE	Writes data to NVM.
⓪ + ENTER	READ	Reads data from NVM.
⑧ + ENTER	RESET	Set the shipping condition.

3-2. H/V Center Confirmation and Adjustment

Please check the picture horizontal/vertical center after the replacement of the following parts .

- Optical block
- Top assembly

1, Check H/V center with 480i monoscope signal in “Full “ mode .

2, If the center is shifted , adjust it with the following service items .



3-3. IRIS Adjustment

Please check it after the replacement of the following parts.

- IRIS unit+Optics unit block+C board
- B board

Check values of the service data in NVM on C board

DBL_CTRL_AC	#0	BL_U_TOP
	#1	BL_U_BOTTOM
	#2	BL_MAX
	#3	BL_MIN
	#4	IRIS_GAIN
	#5	HALL_GAIN

and write the same values on C board to the service data in NVM on B board.

DBL_CTRL	#0	BL_U_TOP
	#1	BL_U_BOTTOM
	#2	BL_MAX
	#3	BL_MIN
	#4	IRIS_GAIN
	#5	HALL_GAIN

SECTION 4
DIAGRAMS

4-1. BLOCK DIAGRAM (1)

Note:
AGU, B, HPC, P and QM boards are supplied as the block for service.
C board is included in the Optics Unit Block.
(The parts on each boards are not supplied individually.)



BLOCK DIAGRAM (2)



BLOCK DIAGRAM (3)



BLOCK DIAGRAM (4)



BLOCK DIAGRAM (5)







BLOCK DIAGRAM (6)



BLOCK DIAGRAM (7)



4-2. FRAME SCHEMATIC DIAGRAM



4-3. CIRCUIT BOARDS LOCATION



4-4. SCHEMATIC DIAGRAMS

Note:

- The parts marked "#" on schematic diagrams are not mounted.
- All capacitors are in µF unless otherwise noted. (pF: µµF) Capacitors without voltage indication are all 50 V.
- Indication of resistance, which does not have one for rating electrical power, is as follows.

  Pitch: 5 mm
  Rating electrical power 1/4 W (CHIP : 1/10 W)

- All resistors are in ohms.
- : nonflammable resistor.
- : fusible resistor.
- △ : internal component.
- : panel designation, and adjustment for repair.
- All variable and adjustable resistors have characteristic curve B, unless otherwise noted.
- : earth-ground.
- : earth-chassis.
- All voltages are in V.
- Readings are taken with a 10 MΩ digital multimeter.
- Readings are taken with a color-bar signal input.
- Voltage variations may be noted due to normal production tolerances.
- ✻ : Can not be measured.
- Circled numbers are waveform references.
- : B + bus.
- : B – bus.
- : Signal path.

Reference information

RESISTOR	: RN	METAL FILM
	: RC	SOLID
	: FPRD	NONFLAMMABLE CARBON
	: FUSE	NONFLAMMABLE FUSIBLE
	: RW	NONFLAMMABLE WIREWOUND
	: RS	NONFLAMMABLE METAL OXIDE
	: RB	NONFLAMMABLE CEMENT
COIL	: LF-8L	MICRO INDUCTOR
CAPACITOR	: TA	TANTALUM
	: PS	STYROL
	: PP	POLYPROPYLENE
	: PT	MYLAR
	: MPS	METALIZED POLYESTER
	: MPP	METALIZED POLYPROPYLENE
	: ALB	BIPOLAR
	: ALT	HIGH TEMPERATURE
	: ALR	HIGH RIPPLE

Note: The components identified by shading and mark ⚠ are critical for safety. Replace only with part number specified.

Terminal name of semiconductors in silk screen printed circuit (✻)

	Device	Printed symbol	Terminal name	Circuit
①	Transistor	T	Collector / Base / Emitter	
②	Transistor	—	Collector / Base / Emitter	
③	Diode		Cathode / Anode	
④	Diode	T	Cathode / Anode / (NC)	
⑤	Diode	—	Cathode / Anode (NC)	
⑥	Diode	T	Common / Anode / Cathode	
⑦	Diode	—	Common / Anode Cathode	
⑧	Diode	T	Common / Anode / Anode	
⑨	Diode	—	Common / Anode Anode	
⑩	Diode	T	Common / Cathode / Cathode	
⑪	Diode	—	Common / Cathode Cathode	
⑫	Diode	▌	Anode Cathode / Anode Anode / Cathode Anode	
⑬	Transistor (FET)	▌	Drain Source Gate	
⑭	Transistor (FET)	▌	Drain Source Gate	
⑮	Transistor (FET)	▌	Source Drain Gate	
⑯	Transistor	▌	Emitter Collector Base	
⑰	Transistor	⫴	C2 B1 E1 / E2 B2 C1	
⑱	Transistor	⫴	C1 B2 E2 / E1 B1 C2	
⑲	Transistor	▬	C1 B2 E2 / E1 B1 C2	
⑳	Transistor	▬	C1 B2 E2 / E1 B1 C2	
㉑	Transistor	▬	E2 B1 E1 / C2 C1(B2)	
㉒	Transistor	▬	(B2) / B1 E1 E2 / C1 C2	
㉓	Transistor	▬	(B2) / E2 E1 B1 / C2 C1	
—	Discrete semiconductot			

(Chip semiconductors that are not actually used are included.)

Ver.1.5

(1) Schematic Diagram of GT Board



(2) Schematic Diagram of HA Board



(3) Schematic Diagram of HB Board



(4) Schematic Diagram of HC Board



(5) Schematic Diagram of K Board



(6) Schematic Diagram of QT (1/3) Board



(7) Schematic Diagram of QT (2/3) Board



(8) Schematic Diagram of QT (3/3) Board



(9) Schematic Diagram of QU Board



(10) Schematic Diagram of S2 Board



(11) Schematic Diagram of T1 Board



(12) Schematic Diagram of T2 Board



4-5. PRINTED WIRING BOARDS

(1) GT Board



• GT BOARD SEMICONDUCTOR LOCATION

IC		
	Side A	Side B ✻
IC6000	C-7	
IC6002	G-8	
IC6003	G-7	
IC6004	G-6	
IC6005	G-4	
IC6007	F-8	
IC6008	F-5	
IC6009	B-8	
IC6010	F-4	
IC6011	C-8	

TRANSISTOR		
	Side A	Side B ✻
Q6000	G-4	
Q6001	B-6	
Q6003	B-3	
Q6004	B-4	
Q6007	B-3	
Q6008	D-6	
Q6009	H-4	
Q6010	F-4	
Q6011	F-5	

DIODE		
	Side A	Side B ✻
D6000	B-4	
D6001	C-8	
D6002	B-8	
D6011	C-6	
D6014	B-2	
D6015	D-7	
D6018	F-6	
D6019	F-8	
D6020	F-6	
D6022	G-4	
D6027	G-7	
D6028	G-7	
D6029	D-8	
D6032	B-5	
D6033	C-5	
D6034	E-8	
D6039	B-3	
D6280	D-4	
D6281	E-4	
D6282	E-4	
D6289	D-3	
D6296	E-5	
D6297	B-2	
D6298	E-4	
D6300	D-2	
D6301	F-5	
D6302	B-3	
D6306	G-5	
D6307	G-8	

(2) HA, HB Boards



(3) HC, K Boards


1 2 3 4 5 6 7 8 9 10 11 12 13 14
A B C D E F G H I
CN7104
CN7100
C7109
C7100
J7100
J7102
JL7102
JL7101
C7104
C7103
J7101
1-867-961-11 (172648411)
SONY
HC
B
CN7100
CN7104
CN7103
VD7112
L7101
VD7111
C7109
C7108
VD7113
FB7100
D7108 R7123
CN7102
VD7109 VD7101
VD7110 VD7100
A-1103-764-A
R7124
R7125
D7101
C7104
R7104
C7102
R7103
VD7104
CN7101
D7111
C7114 C7111 R7128
C7113
R7129
C7112
R7126
D7100
C7101
R7109
VD7103
VD7105
R7105
J7100
J7101
J7102
A
1
CN3001
GND
GND
PVDD
PVDD
C3038
C3039
C3036
C3035
C3055
C3054
C3058
C3057
SONY
EB3003
K
L+
L-
R+
R-
CN3003
EB3001
PS3001
5A
A-1111-304-A
C3003
C3027
C3060
IC3001
JL3003
C3004
C3030
C3043
C3065
C3071
C3019
L3001
L3002
C3008
1-866-539-11 (172588811)
C3028
C3033
C3061
C3068
C3026
C3042
C3059
C3070
IC3003
IC3005
JL3004
C3009
FL3002
C3085
C3072
JL3005
FL3001
C3080
C3075
IC3007
IC3008
GND
1.8V
3.3V
12V
JL3011
JL3002
IC3006
JL3009
X3001
CN3004
IC3002
JL3007
JL3008
EB3002
IC3004
IC3009
JL3010
EB3004
3.3V SW
A MUTE
SP PROT
AMP RST
SCSHIFT
GND
SCDT
OF FRAG
SCLATCH1
M RST
LR DATA
LRCK
BCLK
GND
MCLK
CN3002
EB3003
CN3003
CN3001
EB3001
C3096
Q3002
Q3003
C3012
Q3005
Q3006
C3011
Q3004
C3060
C3027
C3071
C3065
C3043
C3030
SONY
K
1-866-539-11
(172588811)
B
C3074
C3047
C3024
C3049
D3004
D3001
D3003
D3002
L3006
R3150
Q3001
EB3002
EB3004
D3005
A
EP-(GW+GN)

(4) QT Board



• QT BOARD SEMICONDUCTOR LOCATION

IC		
	Side A	Side B
IC7800	H-8	
IC7801	F-4	
IC7802	F-6	
IC7803	H-7	
IC7804	I-8	
IC7806	G-9	
IC7807	H-4	
IC7808	F-5	
IC7900	G-3	
IC7904	G-3	
IC7906	B-8	
IC7907	A-8	

TRANSISTOR		
	Side A	Side B
Q7802	G-7	
Q7803	H-9	
Q7804	E-7	
Q7805	F-8	
Q7806	E-4	
Q7807	E-4	

DIODE		
	Side A	Side B
D7801	A-6	
D7802	A-6	
D7803	A-6	

(5) QU Board


1
2
3
4
5
6
A
B
C
D
E
F
G
CN7951
C7952
C7954
C7951
C7953
A34
B34
MASS PRO
1-867-305-12
(1-726-172-12)
SONY
615-A
A-1112-
CN7952
CN7953
TP7950
>EP-(GW+GN)<
80
1
A1
B1
A

(6) S2 Board


1
2
3
4
5
6
A
B
C
D
E
F
C7180
C7181
IC7180
R7186
R7183
C7182
R7181
C7183
R7182
R7184
R7187
R7188
R7180
R7185
SONY
S 2
(172603011)
1-866-914-11
CN7180
A-1103-
(172603011)
1-866-914-11
SONY
S 2

(7) T1, T2 Boards



4-6. SEMICONDUCTORS

LM75BIM-5/NOPB
M24C02-WMN6T(B)



8 PINS

MCZ3001DB

18 PINS

MM1431ATT
NJM2870F18 (TE2)
XXC6219B182MR



5 PINS

NJM2387DL2-TE1



PQ1CG2032FZ



PQ30RV11



RPM7240-H8



2SC1623-L5L6
UPA1716G



10ERB20-TB3
UF4005/23



1SS184



D10SC4M-F
D10SC6M-4012



D2L20U-TA
RD8.2ES-B2



D2SB60A-F04
D2SB60L
D4SBL40
D4SBS6-F



D5LC20U-4012



DTZ10B
HZU5.6GTRF
MA111-TX
UDZS-TE17-5.6B



ERA22-08TP3



P6SMB39AT3
S3G



SML-020MVT-T86



SML-210MT-T86
SML-210VTT86
SML-310LTT86



SECTION 5
EXPLODED VIEWS

NOTE:

- Items with no part number and no description are not stocked because they are seldom required for routine service
- The construction parts of an assembled part are indicated with a collation number in the remark column.
- Items marked " * " are not stocked since they are seldom required for routine service. Some delay should be anticipated when ordering these items.

The components identified by shading and mark ⚠ are critical for safety.
Replace only with part number specified.

Les composants identifies par une trame et une marque ⚠ sont critiques pour la securite.
Ne les remplacer que par une piece portant le numero specifie.

5-1. SCREEN MIRROR BLOCK, COVERS



REF. NO.	PART NO.	DESCRIPTION	REMARK
1	2-590-903-01	GRILL, SPEAKER (42)	(E42A10)
1	2-590-908-01	GRILL, SPEAKER (50)	(E50A10)
2	2-590-913-01	BUTTON, POWER	
3	2-590-914-01	BUTTON, MULTI	
4	1-826-219-11	LOUD SPEAKER (5X15cm)	
5	2-580-654-01	SCREW, +PWTP2 4X16	
6	A-1127-073-A	SCREEN FRAME ASSY	(E50A10)
6	A-1127-076-A	SCREEN FRAME ASSY	(E42A10)
7	2-590-449-11	PLATE(42L),DIFFUSION	(E42A10)
7	2-590-451-11	PLATE(50L),DIFFUSION	(E50A10)
8	2-590-450-11	PLATE(42F),DIFFUSION	(E42A10)
8	2-590-452-11	PLATE(50F),DIFFUSION	(E50A10)
9	A-1127-074-A	MIRROR ASSY	(E50A10)

REF. NO.	PART NO.	DESCRIPTION	REMARK
9	A-1127-077-A	MIRROR ASSY	(E42A10)
10	2-590-909-01	BRACKET, HC (50)	(E50A10)
11	A-1127-075-A	MIRROR COVER ASSY	(E50A10)
11	A-1127-078-A	MIRROR COVER ASSY	(E42A10)
12	2-591-155-01	COVER,REAR	(E50A10)
12	2-591-155-11	COVER,REAR	(E42A10)
13	2-591-156-01	DOOR,LAMP	
14	4-097-548-01	CUSHION, FOOT	
15	2-590-915-01	TRAY, CONTROL	
16	2-593-048-01	DAMPER	
17	2-580-640-01	SCREW, +BVTP2 4X16	
#1	7-685-648-79	SCREW +BVTP 3X12 TYPE2 IT-3	

5-2. B BLOCK, CHASSIS ASSEMBLY

The components identified by shading and mark ⚠ are critical for safety.
Replace only with part number specified.

Les composants identifies par une trame et une marque ⚠ sont critiques pour la securite.
Ne les remplacer que par une piece portant le numero specifie.



REF. NO.		PART NO.	DESCRIPTION	REMARK
51	*	A-1073-391-A	QU BOARD, COMPLETE	
52		A-1129-347-A	QM BOARD, COMPLETE	
53		A-1103-580-A	QT BOARD, COMPLETE	
54		A-1129-348-A	B BOARD, COMPLETE	
55		3-682-691-00	NUT, WASHER HEXAGON	
56		8-597-504-00	ANTENNA SWITCHE RFD-SA811	
57		A-1113-732-A	GT BOARD, COMPLETE	
58		A-1129-346-A	AGU BOARD, COMPLETE	
59		A-1129-345-A	P BOARD, COMPLETE	
60		A-1138-521-A	HPC BOARD, COMPLETE	
61	⚠	1-791-192-21	CORD, NOISE FILTER WITH POWER	
62	⚠	1-787-333-11	D.C. FAN	
63		3-701-810-72	SCREW, TERMINAL	
64		2-580-640-01	SCREW, +BVTP2 4X16	
65		2-580-593-01	SCREW, +PSW M3X8	
#1		7-685-648-79	SCREW +BVTP 3X12 TYPE2 IT-3	

5-3. LAMP DUCT ASSEMBLY, OPTICS UNIT BLOCK

The components identified by shading and mark ⚠ are critical for safety.
Replace only with part number specified.

Les composants identifies par une trame et une marque ⚠ sont critiques pour la securite.
Ne les remplacer que par une piece portant le numero specifie.



REF. NO.	PART NO.	DESCRIPTION	REMARK
101	X-2055-656-1	CABINET ASSY, BOTTOM(42) (E42A10)	
101	X-2055-653-1	CABINET ASSY, BOTTOM(50) (E50A10)	
102	A-1115-002-A	K BOARD, COMPLETE	
103	A-1123-069-A	OPTICS UNIT BLOCK ASSY (E50A10)	
103	A-1123-071-A	OPTICS UNIT BLOCK ASSY (E42A10)	
104	⚠ 1-787-373-11	FAN,DC	

REF. NO.	PART NO.	DESCRIPTION	REMARK
105	1-576-912-11	THERMOSTAT	
106	⚠ 1-468-936-11	POWER SUPPLY BLOCK	
107	⚠ 1-787-231-11	D.C. FAN (SIROCCO)	
108	2-580-640-01	SCREW, +BVTP2 4X16	
#1	7-685-648-79	SCREW +BVTP 3X12 TYPE2 IT-3	

SECTION 6
ELECTRICAL PARTS LIST

The components identified by shading and mark ⚠ are critial for safety.
Replace only with part number specified.

Les composants identifies par une trame et une marque ⚠ sont critiques pour la securite.
Ne les remplacer que par une piece portant le numero specifie.

When indicating parts by reference number, please include the board name.

- Items marked " * " are not stocked since they are seldom required for routine service. Some delay should be anticipated when ordering these items.
- All variable and adjustable resistors have characteristic curve B, unless otherwise noted.
- RESISTORS
  All resistors are in ohms
  F : nonflammable
- CAPACITORS
  PF : μμF
- There are some cases the reference number on one board overlaps on the other board. Therefore, when ordering parts by the reference number, please include the board name.

REF. NO.	PART NO.	DESCRIPTION			REMARK
	A-1113-732-A	GT BOARD, COMPLETE			
		**********			
	4-382-854-01	SCREW (M3X8), P, SW (+)			
		< CAPACITOR >			
C6006	1-128-953-31	ELECT	470UF	20%	25V
C6007	1-128-953-31	ELECT	470UF	20%	25V
C6008	1-162-966-11	CERAMIC CHIP	0.0022UF	10%	50V
C6020	1-162-970-11	CERAMIC CHIP	0.01UF	10%	25V
C6021	1-126-967-11	ELECT	47UF	20%	50V
C6022	1-126-962-11	ELECT	3.3UF	20%	50V
C6023	1-162-970-11	CERAMIC CHIP	0.01UF	10%	25V
C6024	1-100-831-91	CERAMIC CHIP	0.001UF	2%	50V
C6026	1-126-964-11	ELECT	10UF	20%	50V
C6028	1-162-970-11	CERAMIC CHIP	0.01UF	10%	25V
C6029	1-136-497-81	FILM	0.1UF	5%	50V
C6030	1-126-947-11	ELECT	47UF	20%	35V
C6032	1-107-824-11	CERAMIC	220PF	5%	1KV
C6033	1-107-824-11	CERAMIC	220PF	5%	1KV
C6034	1-165-954-11	FILM	56000PF	3%	800V
C6035	1-126-969-11	ELECT	220UF	20%	50V
C6036	1-126-963-11	ELECT	4.7UF	20%	50V
C6039	1-126-963-11	ELECT	4.7UF	20%	50V
C6040	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C6041	1-162-970-11	CERAMIC CHIP	0.01UF	10%	25V
C6044	1-126-940-11	ELECT	330UF	20%	25V
C6045 ⚠	1-165-530-31	MYLAR	0.47UF	10	0V
C6048	1-128-951-31	ELECT	2200UF	20%	16V
C6049	1-128-951-31	ELECT	2200UF	20%	16V
C6051	1-126-933-11	ELECT	100UF	20%	16V
C6052	1-137-190-91	FILM	0.22UF	5%	50V
C6053	1-126-947-11	ELECT	47UF	20%	35V
C6054	1-126-935-11	ELECT	470UF	20%	16V
C6055	1-126-947-11	ELECT	47UF	20%	35V
C6065	1-128-548-11	ELECT	4700UF	20%	25V
C6077 ⚠	1-131-940-11	ELECT	1200UF	20%	250V
C6078 ⚠	1-131-940-11	ELECT	1200UF	20%	250V
C6083	1-100-714-11	ELECT	100UF	20%	400V
C6084	1-100-714-11	ELECT	100UF	20%	400V
C6085	1-161-830-00	CERAMIC	0.0047UF	500V	
C6272 ⚠	1-161-964-91	CERAMIC	0.0047UF	250V	
C6273 ⚠	1-161-964-91	CERAMIC	0.0047UF	250V	
C6274 ⚠	1-165-530-31	MYLAR	0.47UF	10	0V
C6275 ⚠	1-161-964-91	CERAMIC	0.0047UF	250V	
C6276	1-161-964-91	CERAMIC	0.0047UF	250V	
C6277	1-113-610-11	ELECT(BLOCK)	220UF	20%	250V
C6279 ⚠	1-119-888-51	CERAMIC	2200PF	20%	250V
C6280 ⚠	1-119-888-51	CERAMIC	2200PF	20%	250V
C6283	1-162-116-00	CERAMIC	680PF	10%	2KV
C6284	1-126-950-11	ELECT	330UF	20%	35V
C6285	1-164-217-11	CERAMIC CHIP	150PF	5%	50V
C6286 ⚠	1-165-530-31	MYLAR	0.47UF	10	0V
C6289	1-137-353-11	MYLAR	0.047UF	5%	100V
C6290	1-137-365-11	MYLAR	0.0015UF	5%	50V
C6291	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C6292	1-126-934-11	ELECT	220UF	20%	16V
C6297	1-137-852-31	ELECT	3300UF	20%	16V
C6298	1-126-935-11	ELECT	470UF	20%	16V
C6299	1-164-227-11	CERAMIC CHIP	0.022UF	10%	25V
C6300	1-110-563-11	CERAMIC CHIP	0.068UF	10%	16V
C6304	1-126-947-11	ELECT	47UF	20%	35V
C6305	1-126-947-11	ELECT	47UF	20%	35V
C6323	1-126-935-11	ELECT	470UF	20%	16V
		< CONNECTOR >			
CN6002	1-794-502-11	PIN, CONNECTOR (B04B-PASK) 4P			
CN6009	1-785-706-11	PIN, CONNECTOR (PC BOARD) 10P			
CN6010 ⚠	1-580-843-11	PIN, CONNECTOR (POWER)			
CN6011	1-695-915-11	TAB (CONTACT)			
CN6012	1-695-915-11	TAB (CONTACT)			
CN6013	1-695-915-11	TAB (CONTACT)			
CN6014	1-695-915-11	TAB (CONTACT)			
CN6015	1-695-915-11	TAB (CONTACT)			
CN6018	1-691-960-21	PIN, CONNECTOR (PC BOARD) 3P			
CN6019	1-815-789-11	CONNECTOR, BOARD TO BOARD 50P			
		< DIODE >			
D6000 ⚠	8-719-510-53	DIODE	D4SB60L		
D6001	6-500-335-01	DIODE	MC2838-T112-1		
D6002	8-719-510-12	DIODE	D10SC4M-F		
D6011	8-719-979-64	DIODE	UF4005/23		
D6014	6-500-335-01	DIODE	MC2838-T112-1		
D6015	6-500-567-31	DIODE	10ERB20-TB3		
D6018	8-719-028-45	DIODE	D2L20U-TA		
D6019	8-719-057-96	DIODE	D10SC6M-4012		
D6020	8-719-075-66	DIODE	D5LC20U-4012		
D6022	6-500-335-01	DIODE	MC2838-T112-1		
D6027	6-500-335-01	DIODE	MC2838-T112-1		
D6028	6-500-335-01	DIODE	MC2838-T112-1		
D6029	8-719-060-89	DIODE	D4SBS6-F		
D6032	6-501-223-01	DIODE	S3G		
D6033	6-501-223-01	DIODE	S3G		

Les composants identifies par une trame et une marque ⚠ sont critiques pour la securite. Ne les remplacer que par une piece portant le numero specifie.

The components identified by shading and mark ⚠ are critical for safety.
Replace only with part number specified.

REF. NO.	PART NO.	DESCRIPTION	REMARK
D6034	8-719-064-49	DIODE D4SBL40	
D6039	6-500-335-01	DIODE MC2838-T112-1	
D6280	8-719-160-65	DIODE RD16FB2	
D6281	8-719-110-08	DIODE RD8.2ESB2	
D6282	6-500-567-31	DIODE 10ERB20-TB3	
D6289 ⚠	8-719-077-76	DIODE D2SB60A-F04	
D6296	8-719-055-45	DIODE ERA22-08TP3	
D6297	6-500-335-01	DIODE MC2838-T112-1	
D6298	6-500-567-31	DIODE 10ERB20-TB3	
D6300	8-719-948-45	DIODE ERA22-08	
D6301	8-719-057-96	DIODE D10SC6M-4012	
D6302	6-500-335-01	DIODE MC2838-T112-1	
D6306	6-500-335-01	DIODE MC2838-T112-1	
D6307	6-500-335-01	DIODE MC2838-T112-1	
		< FUSE >	
F6000 ⚠	1-532-506-51	FUSE 6.3A 250V	
		< FERRITE BEAD >	
FB6000	1-410-396-41	FERRITE 0.45UH	
FB6001	1-410-396-41	FERRITE 0.45UH	
FB6002	1-410-396-41	FERRITE 0.45UH	
FB6003	1-412-911-11	FERRITE 0UH	
FB6004	1-412-911-11	FERRITE 0UH	
		< FUSE HOLDER >	
FH6000⚠	1-533-223-11	FUSE HOLDER	
FH6001⚠	1-533-223-11	FUSE HOLDER	
		< IC >	
IC6000	6-705-810-01	IC MCZ3001DB	
IC6002	6-705-464-01	IC BA50BC0T	
IC6003	6-705-466-01	IC BA90BC0T	
IC6004	6-705-464-01	IC BA50BC0T	
IC6005	6-705-464-01	IC BA50BC0T	
IC6007	8-759-098-24	IC PQ30RV11J00H	
IC6008	6-708-175-01	IC MR4010-7103	
IC6009	8-759-640-19	IC PQ1CG2032FZ	
IC6010	8-759-682-42	IC MM1431ATT	
IC6011	8-759-682-42	IC MM1431ATT	
		< COIL >	
L6000	1-406-659-11	INDUCTOR 10UH	
L6002	1-419-742-12	INDUCTOR 33UH	
L6003	1-406-659-11	INDUCTOR 10UH	
L6004	1-412-525-31	INDUCTOR 10UH	
L6009	1-406-983-11	INDUCTOR 1MH	
L6010	1-406-661-21	INDUCTOR 22UH	
L6011 ⚠	1-456-859-11	LINE FILTER COIL	
L6012 ⚠	1-456-859-11	LINE FILTER COIL	
		< PHOTOCOUPLER >	
PH6001⚠	6-600-187-01	PHOTOCOUPLER PC123Y22JOOF	
PH6002⚠	6-600-187-01	PHOTOCOUPLER PC123Y22JOOF	
PH6003⚠	6-600-187-01	PHOTOCOUPLER PC123Y22JOOF	
PH6004⚠	6-600-187-01	PHOTOCOUPLER PC123Y22JOOF	

REF. NO.	PART NO.	DESCRIPTION	REMARK
		< TRANSISTOR >	
Q6000	8-729-054-36	TRANSISTOR UPA1716G-E2	
Q6001	6-550-882-01	TRANSISTOR 2SK3568(LBS2SONY,Q	
Q6003	8-729-600-22	TRANSISTOR 2SA1235-F	
Q6004	8-729-120-28	TRANSISTOR 2SC1623-L5L6	
Q6007	8-729-120-28	TRANSISTOR 2SC1623-L5L6	
Q6008	6-550-882-01	TRANSISTOR 2SK3568(LBS2SONY,Q	
Q6009	8-729-120-28	TRANSISTOR 2SC1623-L5L6	
Q6010	8-729-120-28	TRANSISTOR 2SC1623-L5L6	
Q6011	8-729-120-28	TRANSISTOR 2SC1623-L5L6	
		< RESISTOR >	
R6002	1-215-904-11	METAL OXIDE 100K 5% 2W	
R6003	1-215-904-11	METAL OXIDE 100K 5% 2W	
R6005	1-216-864-11	SHORT CHIP 0	
R6006	1-218-726-11	METAL CHIP 27K 0.5% 1/10W	
R6007	1-218-698-11	METAL CHIP 1.8K 0.5% 1/10W	
R6009	1-216-821-11	METAL CHIP 1K 5% 1/10W	
R6011	1-218-724-11	METAL CHIP 22K 0.5% 1/10W	
R6012	1-218-724-11	METAL CHIP 22K 0.5% 1/10W	
R6013	1-218-692-11	METAL CHIP 1K 0.5% 1/10W	
R6016	1-202-933-61	FUSIBLE 0.1 10% 1/2W	
R6017	1-249-377-11	CARBON 0.47 5% 1/4W	
R6018	1-249-377-11	CARBON 0.47 5% 1/4W	
R6019	1-218-823-11	METAL CHIP 100 0.5% 1/10W	
R6020	1-218-870-11	METAL CHIP 9.1K 0.5% 1/10W	
R6029	1-245-472-21	METAL 270K 1% 1/4W	
R6030	1-245-471-21	METAL 240K 1% 1/4W	
R6031	1-245-471-21	METAL 240K 1% 1/4W	
R6032	1-245-471-21	METAL 240K 1% 1/4W	
R6035	1-218-877-11	METAL CHIP 18K 0.5% 1/10W	
R6042	1-211-991-11	METAL CHIP 82 0.5% 1/10W	
R6043	1-212-897-00	FUSIBLE 470 5% 1/4W	
R6045	1-202-933-61	FUSIBLE 0.1 10% 1/2W	
R6047	1-249-393-11	CARBON 10 5% 1/4W	
R6048	1-249-393-11	CARBON 10 5% 1/4W	
R6050	1-218-871-11	METAL CHIP 10K 0.5% 1/10W	
R6051	1-218-871-11	METAL CHIP 10K 0.5% 1/10W	
R6054	1-245-494-31	METAL 2.2M 2% 1/4W	
R6055	1-245-494-31	METAL 2.2M 2% 1/4W	
R6056	1-216-817-11	METAL CHIP 470 5% 1/10W	
R6057	1-243-979-71	METAL OXIDE 0.1 5% 2W	
R6058	1-249-385-11	CARBON 2.2 5% 1/4W	
R6059	1-216-864-11	SHORT CHIP 0	
R6060	1-216-829-11	METAL CHIP 4.7K 5% 1/10W	
R6061	1-216-833-11	METAL CHIP 10K 5% 1/10W	
R6062	1-216-833-11	METAL CHIP 10K 5% 1/10W	
R6063	1-216-821-11	METAL CHIP 1K 5% 1/10W	
R6064	1-216-821-11	METAL CHIP 1K 5% 1/10W	
R6065	1-216-821-11	METAL CHIP 1K 5% 1/10W	
R6068	1-216-864-11	SHORT CHIP 0	
R6070	1-216-833-11	METAL CHIP 10K 5% 1/10W	
R6072	1-218-722-11	METAL CHIP 18K 0.5% 1/10W	
R6074	1-218-708-11	METAL CHIP 4.7K 0.5% 1/10W	
R6086	1-216-350-11	METAL OXIDE 1.2 5% 1W	
R6089	1-216-864-11	SHORT CHIP 0	
R6098	1-220-340-11	METAL CHIP 470K 5% 1/2W	
R6099	1-220-340-11	METAL CHIP 470K 5% 1/2W	
R6100	1-202-933-61	FUSIBLE 0.1 10% 1/2W	
R6243	1-216-835-11	METAL CHIP 15K 5% 1/10W	
R6244	1-218-720-11	METAL CHIP 15K 0.5% 1/10W	
R6245	1-215-865-11	METAL OXIDE 220 5% 1W	

Les composants identifies par une trame et une marque ⚠ sont critiques pour la securite. Ne les remplacer que par une piece portant le numero specifie.

The components identified by shading and mark ⚠ are critical for safety. Replace only with part number specified.

REF. NO.	PART NO.	DESCRIPTION			REMARK
R6246 ⚠	1-219-568-91	METAL	8.2M	5%	1/2W
R6248	1-216-828-11	METAL CHIP	3.9K	5%	1/10W
R6249	1-219-759-11	METAL	1M	5%	1/2W
R6250	1-216-829-11	METAL CHIP	4.7K	5%	1/10W
R6251	1-216-828-11	METAL CHIP	3.9K	5%	1/10W
R6252	1-216-837-11	METAL CHIP	22K	5%	1/10W
R6253	1-216-833-11	METAL CHIP	10K	5%	1/10W
R6254	1-216-833-11	METAL CHIP	10K	5%	1/10W
R6255	1-216-344-00	METAL OXIDE	0.39	5%	1W
R6257	1-216-349-00	METAL OXIDE	1	5%	1W
R6259	1-244-207-11	WIREWOUND	3.3	5%	10W
R6261	1-260-328-11	CARBON	1K	5%	1/2W
R6262	1-216-829-11	METAL CHIP	4.7K	5%	1/10W
R6263	1-249-389-11	CARBON	4.7	5%	1/4W
R6267	1-216-829-11	METAL CHIP	4.7K	5%	1/10W
R6268	1-216-821-11	METAL CHIP	1K	5%	1/10W
R6273	1-249-389-11	CARBON	4.7	5%	1/4W
R6277	1-216-821-11	METAL CHIP	1K	5%	1/10W
R6278	1-216-827-11	METAL CHIP	3.3K	5%	1/10W
R6279	1-216-845-11	METAL CHIP	100K	5%	1/10W
R6280	1-216-833-11	METAL CHIP	10K	5%	1/10W
R6281	1-216-833-11	METAL CHIP	10K	5%	1/10W
R6283	1-243-979-71	METAL OXIDE	0.1	5%	2W
R6284	1-216-864-11	SHORT CHIP	0		
R6285	1-216-832-11	METAL CHIP	8.2K	5%	1/10W
R6286	1-216-834-11	METAL CHIP	12K	5%	1/10W
R6287	1-218-720-11	METAL CHIP	15K	0.5%	1/10W
R6288	1-218-708-11	METAL CHIP	4.7K	0.5%	1/10W
R6291	1-216-864-11	SHORT CHIP	0		
R6296	1-216-821-11	METAL CHIP	1K	5%	1/10W
R6297	1-216-801-11	METAL CHIP	22	5%	1/10W
R6300	1-216-821-11	METAL CHIP	1K	5%	1/10W
R6301	1-216-864-11	SHORT CHIP	0		
R6302	1-216-845-11	METAL CHIP	100K	5%	1/10W
R6339	1-216-864-11	SHORT CHIP	0		
		< RELAY >			
RY6001 ⚠	1-755-388-11	RELAY (AC POWER)			
RY6002 ⚠	1-755-388-11	RELAY (AC POWER)			
		< SPARK GAP >			
SG6000	1-576-487-11	ELEMENT, SPARK			
		< TRANSFORMER >			
T6000 ⚠	1-443-747-11	TRANSFORMER (PIT)			
T6004 ⚠	1-443-748-11	TRANSFORMER (SRT)			
		< VARISTOR >			
VD6000 ⚠	1-804-992-21	VARISTOR			
VD6001 ⚠	1-804-991-21	VARISTOR			
VD6003 ⚠	1-804-991-21	VARISTOR			
**********					
		HA MOUNT			
		**********			
		< CAPACITOR >			
C7000	1-100-597-91	CERAMIC CHIP	0.1UF	10%	25V
		< CONNECTOR >			
CN7000	1-819-445-11	HEADER ASSEMBLY FOR PWB 3P			
		< RESISTOR >			
R7001	1-218-676-11	METAL CHIP	220	0.5%	1/10W
R7002	1-218-684-11	METAL CHIP	470	0.5%	1/10W
R7003	1-218-691-11	METAL CHIP	910	0.5%	1/10W
R7004	1-218-698-11	METAL CHIP	1.8K	0.5%	1/10W
R7005	1-218-706-11	METAL CHIP	3.9K	0.5%	1/10W
		< SWITCH >			
S7000	1-692-431-21	SWITCH, TACTILE			
S7001	1-692-431-21	SWITCH, TACTILE			
S7002	1-692-431-21	SWITCH, TACTILE			
S7003	1-692-431-21	SWITCH, TACTILE			
S7004	1-692-431-21	SWITCH, TACTILE			
S7005	1-692-431-21	SWITCH, TACTILE			
**********					
		HB MOUNT			
		**********			
		< CAPACITOR >			
C7020	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7021	1-126-964-11	ELECT	10UF	20%	50V
C7022	1-162-974-11	CERAMIC CHIP	0.01UF		50V
C7023	1-162-974-11	CERAMIC CHIP	0.01UF		50V
C7024	1-162-974-11	CERAMIC CHIP	0.01UF		50V
C7025	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7026	1-162-974-11	CERAMIC CHIP	0.01UF		50V
C7027	1-162-974-11	CERAMIC CHIP	0.01UF		50V
C7028	1-162-974-11	CERAMIC CHIP	0.01UF		50V
C7029	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7030	1-162-915-11	CERAMIC CHIP	10PF	0.50PF	50V
C7031	1-165-908-11	CERAMIC CHIP	1UF	10%	10V
C7032	1-162-915-11	CERAMIC CHIP	10PF	0.50PF	50V
		< DIODE >			
D7022	6-500-861-01	DIODE SML-020MVT-T86			
D7023	8-719-064-07	DIODE SML-310LTT86			
D7024	6-500-861-01	DIODE SML-020MVT-T86			
		< IC >			
IC7020	6-600-210-01	IC RPM7240-H8			
IC7021	6-707-223-01	IC LM75BIM-5/NOPB			
		< TRANSISTOR >			
Q7020	8-729-120-28	TRANSISTOR 2SC1623-L5L6			
Q7021	8-729-120-28	TRANSISTOR 2SC1623-L5L6			
Q7022	8-729-120-28	TRANSISTOR 2SC1623-L5L6			
Q7023	8-729-120-28	TRANSISTOR 2SC1623-L5L6			
Q7024	8-729-120-28	TRANSISTOR 2SC1623-L5L6			
		< RESISTOR >			
R7020	1-216-823-11	METAL CHIP	1.5K	5%	1/10W
R7021	1-216-805-11	METAL CHIP	47	5%	1/10W

REF. NO.	PART NO.	DESCRIPTION			REMARK
R7022	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7023	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7024	1-216-813-11	METAL CHIP	220	5%	1/10W
R7025	1-216-813-11	METAL CHIP	220	5%	1/10W
R7026	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7027	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7028	1-216-813-11	METAL CHIP	220	5%	1/10W
R7029	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7030	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7031	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7032	1-216-813-11	METAL CHIP	220	5%	1/10W
R7033	1-216-813-11	METAL CHIP	220	5%	1/10W
R7034	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7035	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7039	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7046	1-216-801-11	METAL CHIP	22	5%	1/10W
R7047	1-216-801-11	METAL CHIP	22	5%	1/10W

< SWITCH >

S7020	1-692-431-21	SWITCH, TACTILE			

****

HC MOUNT
****

< CAPACITOR >

C7101	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C7102	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C7103	1-126-964-11	ELECT	10UF	20%	50V
C7104	1-126-964-11	ELECT	10UF	20%	50V
C7111	1-162-927-11	CERAMIC CHIP	100PF	5%	50V
C7112	1-162-927-11	CERAMIC CHIP	100PF	5%	50V
C7113	1-164-227-11	CERAMIC CHIP	0.022UF	10%	25V
C7114	1-164-227-11	CERAMIC CHIP	0.022UF	10%	25V

< DIODE >

D7100	8-719-977-28	DIODE	DTZ10B
D7101	8-719-977-28	DIODE	DTZ10B
D7102	8-719-069-55	DIODE	UDZSTE-175.6B
D7108	8-719-083-58	DIODE	UDZSTE-173.9B
D7109	8-719-062-19	DIODE	MA3200WA-TX
D7110	8-719-062-19	DIODE	MA3200WA-TX
D7111	8-719-062-19	DIODE	MA3200WA-TX

< JACK >

J7100	1-819-355-11	PHONO JACK 3P
J7101	1-819-356-11	PHONO JACK 3P
J7102	1-568-267-11	JACK

< RESISTOR >

R7103	1-216-849-11	METAL CHIP	220K	5%	1/10W
R7104	1-216-849-11	METAL CHIP	220K	5%	1/10W
R7105	1-218-676-11	METAL CHIP	220	0.5%	1/10W
R7106	1-218-668-11	METAL CHIP	100	0.5%	1/10W
R7109	1-216-821-11	METAL CHIP	1K	5%	1/10W
R7110	1-216-821-11	METAL CHIP	1K	5%	1/10W
R7111	1-216-864-11	SHORT CHIP	0		
R7123	1-216-864-11	SHORT CHIP	0		
R7124	1-218-676-11	METAL CHIP	220	0.5%	1/10W
R7125	1-218-676-11	METAL CHIP	220	0.5%	1/10W
R7126	1-216-864-11	SHORT CHIP	0		
R7128	1-216-797-11	METAL CHIP	10	5%	1/10W
R7129	1-216-797-11	METAL CHIP	10	5%	1/10W

< VARISTOR >

VD7100	1-803-974-21	VARISTOR, CHIP	(1608)		
VD7101	1-803-974-21	VARISTOR, CHIP	(1608)		
VD7102	1-803-974-21	VARISTOR, CHIP	(1608)		
VD7108	1-803-974-21	VARISTOR, CHIP	(1608)		
VD7109	1-803-974-21	VARISTOR, CHIP	(1608)		
VD7110	1-803-974-21	VARISTOR, CHIP	(1608)		

****

HPC MOUNT
****

< CAPACITOR >

C7200	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7201	1-127-573-11	CERAMIC CHIP	1UF	10%	16V
C7202	1-127-573-11	CERAMIC CHIP	1UF	10%	16V
C7205	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7206	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7207	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V

< CONNECTOR >

CN7200	1-794-930-21	CONNECTOR, D SUB

< DIODE >

D7203	8-719-073-39	DIODE	HZU5.6GTRF
D7204	8-719-073-39	DIODE	HZU5.6GTRF
D7205	8-719-073-39	DIODE	HZU5.6GTRF
D7208	8-719-977-28	DIODE	DTZ10B
D7209	8-719-977-28	DIODE	DTZ10B
D7210	8-719-404-50	DIODE	MA111-TX
D7212	8-719-977-28	DIODE	DTZ10B
D7213	8-719-801-78	DIODE	1SS184

< FERRITE BEAD >

FB7200	1-469-100-21	FERRITE	0UH
FB7201	1-469-100-21	FERRITE	0UH
FB7202	1-469-100-21	FERRITE	0UH
FB7204	1-400-141-22	FERRITE	0UH

< IC >

IC7200	6-704-600-01	IC M24C02-WMN6T(B)

< JACK >

J7200	1-573-798-11	JACK, MINIATURE (DIA. 3.5)

< IC LINK >

PS7200	1-576-122-21	IC LINK	0.4A	72V

REF. NO.	PART NO.	DESCRIPTION			REMARK
		< TRANSISTOR >			
Q7200	6-550-014-01	TRANSISTOR SSM6N15FU(TE85R)			
		< RESISTOR >			
R7200	1-216-853-11	METAL CHIP	470K	5%	1/10W
R7202	1-216-845-11	METAL CHIP	100K	5%	1/10W
R7205	1-216-805-11	METAL CHIP	47	5%	1/10W
R7206	1-216-864-11	SHORT CHIP	0		
R7207	1-216-864-11	SHORT CHIP	0		
R7208	1-216-864-11	SHORT CHIP	0		
R7209	1-216-805-11	METAL CHIP	47	5%	1/10W
R7210	1-216-851-11	METAL CHIP	330K	5%	1/10W
R7211	1-216-851-11	METAL CHIP	330K	5%	1/10W
R7216	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7217	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7218	1-216-805-11	METAL CHIP	47	5%	1/10W
R7219	1-216-805-11	METAL CHIP	47	5%	1/10W
R7222	1-216-864-11	SHORT CHIP	0		
R7223	1-216-864-11	SHORT CHIP	0		
R7227	1-216-821-11	METAL CHIP	1K	5%	1/10W
R7229	1-216-845-11	METAL CHIP	100K	5%	1/10W
R7231	1-216-864-11	SHORT CHIP	0		
R7232	1-216-864-11	SHORT CHIP	0		
R7233	1-216-864-11	SHORT CHIP	0		
R7234	1-216-864-11	SHORT CHIP	0		
R7235	1-216-864-11	SHORT CHIP	0		

****

A-1115-002-A K BOARD, COMPLETE
****

< CAPACITOR >

C3001	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3002	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C3003	1-128-404-11	ELECT CHIP	100UF	20%	35V
C3004	1-117-681-11	ELECT CHIP	100UF	20%	16V
C3005	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3006	1-164-506-11	CERAMIC CHIP	4.7UF		16V
C3007	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3008	1-117-681-11	ELECT CHIP	100UF	20%	16V
C3009	1-126-206-11	ELECT CHIP	100UF	20%	6.3V
C3010	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3011	1-164-506-11	CERAMIC CHIP	4.7UF		16V
C3012	1-164-506-11	CERAMIC CHIP	4.7UF		16V
C3013	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3019	1-117-681-11	ELECT CHIP	100UF	20%	16V
C3020	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3021	1-165-128-11	CERAMIC CHIP	0.22UF		16V
C3022	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3023	1-165-128-11	CERAMIC CHIP	0.22UF		16V
C3024	1-163-989-11	CERAMIC CHIP	0.033UF	10%	25V
C3025	1-164-936-11	CERAMIC CHIP	680PF	10%	50V
C3026	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3027	1-112-030-31	ELECT	1500UF	20%	35V
C3028	1-128-992-21	ELECT CHIP	47UF	20%	25V
C3030	1-136-177-00	FILM	1UF	5%	50V
C3032	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3033	1-128-992-21	ELECT CHIP	47UF	20%	25V
C3034	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3035	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3036	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3037	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3038	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3039	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3041	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3042	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3043	1-136-177-00	FILM	1UF	5%	50V
C3044	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3045	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3046	1-164-936-11	CERAMIC CHIP	680PF	10%	50V
C3047	1-163-989-11	CERAMIC CHIP	0.033UF	10%	25V
C3048	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3049	1-163-989-11	CERAMIC CHIP	0.033UF	10%	25V
C3050	1-164-936-11	CERAMIC CHIP	680PF	10%	50V
C3051	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3052	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3053	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3054	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3055	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3056	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3057	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3058	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3059	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3060	1-112-030-31	ELECT	1500UF	20%	35V
C3061	1-128-992-21	ELECT CHIP	47UF	20%	25V
C3062	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3063	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3065	1-136-177-00	FILM	1UF	5%	50V
C3067	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3068	1-128-992-21	ELECT CHIP	47UF	20%	25V
C3070	1-115-339-11	CERAMIC CHIP	0.1UF	10%	50V
C3071	1-136-177-00	FILM	1UF	5%	50V
C3072	1-128-995-21	ELECT CHIP	100UF	20%	10V
C3073	1-164-936-11	CERAMIC CHIP	680PF	10%	50V
C3074	1-163-989-11	CERAMIC CHIP	0.033UF	10%	25V
C3075	1-126-395-11	ELECT CHIP	22UF	20%	16V
C3076	1-164-360-11	CERAMIC CHIP	0.1UF		16V
C3077	1-165-128-11	CERAMIC CHIP	0.22UF		16V
C3078	1-165-128-11	CERAMIC CHIP	0.22UF		16V
C3079	1-100-567-81	CERAMIC CHIP	10000PF	10%	25V
C3080	1-128-993-21	ELECT CHIP	22UF	20%	10V
C3081	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3082	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3083	1-107-820-11	CERAMIC CHIP	0.1UF		16V
C3084	1-100-567-81	CERAMIC CHIP	10000PF	10%	25V
C3085	1-128-995-21	ELECT CHIP	100UF	20%	10V
C3086	1-164-850-11	CERAMIC CHIP	10PF	0.50PF	50V
C3088	1-100-567-81	CERAMIC CHIP	10000PF	10%	25V
C3090	1-164-937-11	CERAMIC CHIP	0.001UF	10%	50V
C3091	1-164-850-11	CERAMIC CHIP	10PF	0.50PF	50V
C3094	1-164-936-11	CERAMIC CHIP	680PF	10%	50V
C3095	1-164-936-11	CERAMIC CHIP	680PF	10%	50V
C3096	1-164-936-11	CERAMIC CHIP	680PF	10%	50V
C3097	1-164-936-11	CERAMIC CHIP	680PF	10%	50V
C3099	1-165-128-11	CERAMIC CHIP	0.22UF		16V
C3100	1-165-128-11	CERAMIC CHIP	0.22UF		16V
C3101	1-165-128-11	CERAMIC CHIP	0.22UF		16V
C3102	1-165-128-11	CERAMIC CHIP	0.22UF		16V
		< CONNECTOR >			
CN3001	1-794-502-11	PIN, CONNECTOR (B04B-PASK) 4P			

REF. NO.	PART NO.	DESCRIPTION			REMARK
CN3002	1-819-443-11	HEADER ASEEMBLY FOR PWB 15P			
CN3003	1-580-838-11	PIN, CONNECTOR (PC BOARD) 4P			
		< DIODE >			
D3001	6-500-260-01	DIODE P6SMB39AT3			
D3002	6-500-260-01	DIODE P6SMB39AT3			
D3003	6-500-260-01	DIODE P6SMB39AT3			
D3004	6-500-260-01	DIODE P6SMB39AT3			
		< TERMINAL BOARD >			
EB3001	1-537-771-21	TERMINAL BOARD, GROUND			
EB3002	1-537-771-21	TERMINAL BOARD, GROUND			
		< FILTER >			
FL3001	1-234-177-21	FERRITE	0UH		
FL3002	1-234-177-21	FERRITE	0UH		
		< IC >			
IC3001	6-706-862-01	IC NJM2387DL2-TE1			
IC3002	8-759-548-99	IC SN74LV08APWR			
IC3003	6-706-862-01	IC NJM2387DL2-TE1			
IC3004	8-759-573-97	IC SN74LVC541APWR			
IC3005	6-707-629-01	IC CXD9845M			
IC3006	6-705-979-01	IC CXD9788AR			
IC3007	6-701-189-01	IC MC74VHC1GU04DFT1			
IC3008	6-700-263-01	IC NJM2870F18(TE2)			
		< COIL >			
L3001	1-457-106-11	COIL,CHOKE 10UH			
L3002	1-457-106-11	COIL,CHOKE 10UH			
L3006	1-412-939-11	INDUCTOR	1UH		
		< IC LINK >			
PS3001	1-576-788-21	FUSE	5A	72V	
		< TRANSISTOR >			
Q3002	8-729-602-36	TRANSISTOR 2SA1602-F			
Q3003	8-729-602-36	TRANSISTOR 2SA1602-F			
Q3004	8-729-120-28	TRANSISTOR 2SC1623-L5L6			
Q3005	8-729-602-36	TRANSISTOR 2SA1602-F			
Q3006	8-729-602-36	TRANSISTOR 2SA1602-F			
		< RESISTOR >			
R3001	1-218-990-81	SHORT CHIP	0		
R3002	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3003	1-218-990-81	SHORT CHIP	0		
R3004	1-218-990-81	SHORT CHIP	0		
R3005	1-218-990-81	SHORT CHIP	0		
R3006	1-208-927-11	METAL CHIP	47K	0.5%	1/16W
R3007	1-208-929-11	METAL CHIP	56K	0.5%	1/16W
R3008	1-208-931-11	METAL CHIP	68K	0.5%	1/16W
R3009	1-208-699-11	METAL CHIP	4.7K	0.5%	1/16W
R3010	1-208-699-11	METAL CHIP	4.7K	0.5%	1/16W
R3011	1-218-990-81	SHORT CHIP	0		
R3012	1-218-941-81	RES-CHIP	100	5%	1/16W
R3013	1-218-941-81	RES-CHIP	100	5%	1/16W
R3014	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3015	1-218-941-81	RES-CHIP	100	5%	1/16W
R3016	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3017	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3019	1-218-977-11	RES-CHIP	100K	5%	1/16W
R3020	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3021	1-218-978-11	RES-CHIP	120K	5%	1/16W
R3022	1-218-977-11	RES-CHIP	100K	5%	1/16W
R3023	1-218-990-81	SHORT CHIP	0		
R3024	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3025	1-208-695-11	METAL CHIP	3.3K	0.5%	1/16W
R3026	1-208-695-11	METAL CHIP	3.3K	0.5%	1/16W
R3027	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3029	1-218-977-11	RES-CHIP	100K	5%	1/16W
R3030	1-208-683-11	METAL CHIP	1K	0.5%	1/16W
R3032	1-218-933-11	RES-CHIP	22	5%	1/16W
R3033	1-218-990-81	SHORT CHIP	0		
R3034	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3035	1-218-977-11	RES-CHIP	100K	5%	1/16W
R3036	1-218-990-81	SHORT CHIP	0		
R3037	1-218-990-81	SHORT CHIP	0		
R3038	1-218-978-11	RES-CHIP	120K	5%	1/16W
R3039	1-218-977-11	RES-CHIP	100K	5%	1/16W
R3040	1-218-990-81	SHORT CHIP	0		
R3041	1-218-990-81	SHORT CHIP	0		
R3042	1-218-990-81	SHORT CHIP	0		
R3043	1-218-990-81	SHORT CHIP	0		
R3044	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3045	1-218-990-81	SHORT CHIP	0		
R3046	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3047	1-218-990-81	SHORT CHIP	0		
R3048	1-218-990-81	SHORT CHIP	0		
R3049	1-218-990-81	SHORT CHIP	0		
R3050	1-216-791-11	METAL CHIP	3.3	5%	1/10W
R3051	1-218-941-81	RES-CHIP	100	5%	1/16W
R3052	1-218-941-81	RES-CHIP	100	5%	1/16W
R3053	1-216-791-11	METAL CHIP	3.3	5%	1/10W
R3054	1-218-941-81	RES-CHIP	100	5%	1/16W
R3055	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3056	1-216-800-11	METAL CHIP	18	5%	1/10W
R3057	1-218-941-81	RES-CHIP	100	5%	1/16W
R3059	1-218-941-81	RES-CHIP	100	5%	1/16W
R3060	1-218-990-81	SHORT CHIP	0		
R3062	1-216-790-11	METAL CHIP	2.7	5%	1/10W
R3063	1-216-790-11	METAL CHIP	2.7	5%	1/10W
R3064	1-218-941-81	RES-CHIP	100	5%	1/16W
R3065	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3066	1-218-990-81	SHORT CHIP	0		
R3067	1-218-990-81	SHORT CHIP	0		
R3070	1-218-945-11	RES-CHIP	220	5%	1/16W
R3071	1-218-941-81	RES-CHIP	100	5%	1/16W
R3072	1-218-990-81	SHORT CHIP	0		
R3073	1-218-990-81	SHORT CHIP	0		
R3075	1-218-945-11	RES-CHIP	220	5%	1/16W
R3076	1-218-972-11	RES-CHIP	39K	5%	1/16W
R3077	1-216-800-11	METAL CHIP	18	5%	1/10W
R3078	1-218-941-81	RES-CHIP	100	5%	1/16W
R3079	1-218-945-11	RES-CHIP	220	5%	1/16W
R3082	1-218-990-81	SHORT CHIP	0		
R3084	1-218-965-11	RES-CHIP	10K	5%	1/16W
R3085	1-216-800-11	METAL CHIP	18	5%	1/10W
R3086	1-218-933-11	RES-CHIP	22	5%	1/16W
R3088	1-218-933-11	RES-CHIP	22	5%	1/16W

REF. NO.	PART NO.	DESCRIPTION			REMARK
R3089	1-218-990-81	SHORT CHIP	0		
R3092	1-218-990-81	SHORT CHIP	0		
R3096	1-216-790-11	METAL CHIP	2.7	5%	1/10W
R3097	1-216-790-11	METAL CHIP	2.7	5%	1/10W
R3098	1-218-990-81	SHORT CHIP	0		
R3100	1-216-800-11	METAL CHIP	18	5%	1/10W
R3101	1-216-791-11	METAL CHIP	3.3	5%	1/10W
R3102	1-216-791-11	METAL CHIP	3.3	5%	1/10W
R3103	1-216-791-11	METAL CHIP	3.3	5%	1/10W
R3104	1-218-945-11	RES-CHIP	220	5%	1/16W
R3105	1-218-977-11	RES-CHIP	100K	5%	1/16W
R3106	1-218-990-81	SHORT CHIP	0		
R3107	1-218-989-11	RES-CHIP	1M	5%	1/16W
R3108	1-218-941-81	RES-CHIP	100	5%	1/16W
R3111	1-218-945-11	RES-CHIP	220	5%	1/16W
R3112	1-218-945-11	RES-CHIP	220	5%	1/16W
R3113	1-218-990-81	SHORT CHIP	0		
R3114	1-218-990-81	SHORT CHIP	0		
R3150	1-216-295-91	SHORT CHIP	0		
R3151	1-216-813-11	METAL CHIP	220	5%	1/10W
R3152	1-216-864-11	SHORT CHIP	0		
R3153	1-216-864-11	SHORT CHIP	0		
R3154	1-216-864-11	SHORT CHIP	0		
R3155	1-216-864-11	SHORT CHIP	0		
R3156	1-216-864-11	SHORT CHIP	0		
R3157	1-216-864-11	SHORT CHIP	0		
R3158	1-216-864-11	SHORT CHIP	0		
R3159	1-216-864-11	SHORT CHIP	0		
R3164	1-218-990-81	SHORT CHIP	0		

< VIBRATOR >

X3001	1-795-660-21	QUARTZ CRYSTAL UNIT			

****

A-1103-580-A QT BOARD, COMPLETE
****

< CAPACITOR >

C7800	1-137-765-21	ELECT CHIP	47UF	20%	16V
C7801	1-165-492-21	ELECT CHIP	100UF	20%	10V
C7802	1-165-492-21	ELECT CHIP	100UF	20%	10V
C7803	1-165-492-21	ELECT CHIP	100UF	20%	10V
C7804	1-100-159-91	CERAMIC CHIP	22UF	10%	6.3V
C7805	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7806	1-115-156-11	CERAMIC CHIP	1UF		10V
C7807	1-127-820-11	CERAMIC CHIP	4.7UF	10%	16V
C7808	1-127-820-11	CERAMIC CHIP	4.7UF	10%	16V
C7809	1-137-765-21	ELECT CHIP	47UF	20%	16V
C7810	1-127-820-11	CERAMIC CHIP	4.7UF	10%	16V
C7811	1-162-995-11	CERAMIC CHIP	0.022UF		50V
C7812	1-162-970-11	CERAMIC CHIP	0.01UF	10%	25V
C7813	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7814	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7815	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7816	1-162-995-11	CERAMIC CHIP	0.022UF		50V
C7817	1-115-566-11	CERAMIC CHIP	4.7UF	10%	10V
C7818	1-127-820-11	CERAMIC CHIP	4.7UF	10%	16V
C7819	1-100-159-91	CERAMIC CHIP	22UF	10%	6.3V
C7820	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7821	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7823	1-100-159-91	CERAMIC CHIP	22UF	10%	6.3V
C7824	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7825	1-128-996-11	ELECT CHIP	4.7UF	20%	50V
C7826	1-165-319-11	CERAMIC CHIP	0.1UF		50V
C7827	1-128-996-11	ELECT CHIP	4.7UF	20%	50V
C7828	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C7829	1-162-970-11	CERAMIC CHIP	0.01UF	10%	25V
C7830	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7831	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C7832	1-162-970-11	CERAMIC CHIP	0.01UF	10%	25V
C7834	1-137-765-21	ELECT CHIP	47UF	20%	16V
C7835	1-128-996-11	ELECT CHIP	4.7UF	20%	50V
C7836	1-128-396-11	ELECT CHIP	470UF	20%	10V
C7837	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7838	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7840	1-165-989-11	CERAMIC CHIP	10UF	10%	6.3V
C7841	1-165-989-11	CERAMIC CHIP	10UF	10%	6.3V
C7842	1-162-970-11	CERAMIC CHIP	0.01UF	10%	25V
C7843	1-162-970-11	CERAMIC CHIP	0.01UF	10%	25V
C7845	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7846	1-165-492-21	ELECT CHIP	100UF	20%	10V
C7847	1-128-396-11	ELECT CHIP	470UF	20%	10V
C7849	1-165-492-21	ELECT CHIP	100UF	20%	10V
C7850	1-165-492-21	ELECT CHIP	100UF	20%	10V
C7851	1-165-989-11	CERAMIC CHIP	10UF	10%	6.3V
C7852	1-125-889-91	CERAMIC CHIP	2.2UF	10%	10V
C7853	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7855	1-165-492-21	ELECT CHIP	100UF	20%	10V
C7858	1-127-820-11	CERAMIC CHIP	4.7UF	10%	16V
C7859	1-115-566-11	CERAMIC CHIP	4.7UF	10%	10V
C7860	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7865	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7867	1-165-989-11	CERAMIC CHIP	10UF	10%	6.3V
C7868	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7872	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7873	1-165-989-11	CERAMIC CHIP	10UF	10%	6.3V
C7874	1-107-826-11	CERAMIC CHIP	0.1UF	10%	16V
C7875	1-127-820-11	CERAMIC CHIP	4.7UF	10%	16V
C7905	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7906	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7907	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7908	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7912	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7929	1-115-156-11	CERAMIC CHIP	1UF		10V
C7931	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7932	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7933	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7934	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7935	1-115-156-11	CERAMIC CHIP	1UF		10V
C7943	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7944	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7945	1-162-917-11	CERAMIC CHIP	15PF	5%	50V
C7946	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C7947	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C7948	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C7949	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V
C7950	1-162-964-11	CERAMIC CHIP	0.001UF	10%	50V

< CONNECTOR >

CN7802	1-819-390-21	FFC/FPC CONNECTOR (ZIF) 49P
CN7903	1-818-484-11	FFC/FPC CONNECTOR (ZIF) 80P

REF. NO.	PART NO.	DESCRIPTION	REMARK
		< DIODE >	
D7801	8-719-066-99	DIODE SML-210VTT86	
D7802	8-719-060-99	DIODE SML-210MT-T86	
D7803	8-719-066-99	DIODE SML-210VTT86	
		< FERRITE BEAD >	
FB7800	1-400-180-21	INDUCTOR 0UH	
FB7801	1-400-089-21	FERRITE 0UH	
FB7802	1-400-089-21	FERRITE 0UH	
FB7803	1-400-180-21	INDUCTOR 0UH	
FB7808	1-400-180-21	INDUCTOR 0UH	
FB7809	1-414-226-21	FERRITE 0UH	
FB7810	1-414-226-21	FERRITE 0UH	
FB7811	1-414-760-21	FERRITE 0UH	
FB7901	1-414-229-11	FERRITE 0UH	
FB7902	1-414-760-21	FERRITE 0UH	
FB7903	1-414-760-21	FERRITE 0UH	
FB7904	1-414-229-11	FERRITE 0UH	
FB7905	1-414-229-11	FERRITE 0UH	
FB7906	1-414-229-11	FERRITE 0UH	
		< IC >	
IC7800	6-708-112-01	IC MIC49300WR-TR	
IC7801	6-705-839-01	IC XC6219B182MR	
IC7802	6-708-082-01	IC NJM2846DL2-05(TE2)	
IC7803	6-708-171-01	IC MIC5235YM5TR	
IC7804	8-749-925-00	IC TK11819MTL	
IC7806	8-759-646-63	IC CD74HC4053M-96	
IC7807	8-759-549-01	IC SN74LV125APWR	
IC7808	6-708-082-01	IC NJM2846DL2-05(TE2)	
IC7900	8-753-238-09	IC CXD1969R-T6	
IC7904	8-759-649-45	IC SN74AHC1G04DCKR	
IC7906	6-706-811-01	IC TPS2091DR	
IC7907	6-706-812-01	IC TPS2012ADR	
		< COIL >	
L7800	1-414-755-11	INDUCTOR 22UH	
L7801	1-412-642-61	INDUCTOR 1.2MH	
L7802	1-414-755-11	INDUCTOR 22UH	
L7804	1-414-754-11	INDUCTOR 10UH	
L7805	1-414-752-11	INDUCTOR 2.2UH	
L7806	1-414-754-11	INDUCTOR 10UH	
L7808	1-414-754-11	INDUCTOR 10UH	
L7809	1-414-754-11	INDUCTOR 10UH	
L7810	1-414-754-11	INDUCTOR 10UH	
L7811	1-414-754-11	INDUCTOR 10UH	
L7812	1-414-754-11	INDUCTOR 10UH	
		< TRANSISTOR >	
Q7802	8-729-047-14	TRANSISTOR 2SC3775	
Q7803	8-729-120-28	TRANSISTOR 2SC1623-L5L6	
Q7804	8-729-120-28	TRANSISTOR 2SC1623-L5L6	
Q7805	8-729-120-28	TRANSISTOR 2SC1623-L5L6	
Q7806	8-729-600-22	TRANSISTOR 2SA1235-F	
Q7807	8-729-120-28	TRANSISTOR 2SC1623-L5L6	
		< RESISTOR >	
R7800	1-216-864-11	SHORT CHIP 0	

REF. NO.	PART NO.	DESCRIPTION			REMARK
R7803	1-216-809-11	METAL CHIP	100	5%	1/10W
R7804	1-216-821-11	METAL CHIP	1K	5%	1/10W
R7805	1-218-847-11	METAL CHIP	1K	0.5%	1/10W
R7806	1-211-977-11	METAL CHIP	22	0.5%	1/10W
R7807	1-218-830-11	METAL CHIP	200	0.5%	1/10W
R7808	1-216-845-11	METAL CHIP	100K	5%	1/10W
R7809	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7810	1-216-864-11	SHORT CHIP	0		
R7815	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7816	1-216-864-11	SHORT CHIP	0		
R7817	1-216-864-11	SHORT CHIP	0		
R7818	1-216-864-11	SHORT CHIP	0		
R7819	1-216-837-11	METAL CHIP	22K	5%	1/10W
R7820	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7821	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7822	1-216-837-11	METAL CHIP	22K	5%	1/10W
R7825	1-216-864-11	SHORT CHIP	0		
R7831	1-218-889-11	METAL CHIP	56K	0.5%	1/10W
R7832	1-218-881-11	METAL CHIP	27K	0.5%	1/10W
R7833	1-216-864-11	SHORT CHIP	0		
R7835	1-216-864-11	SHORT CHIP	0		
R7839	1-216-864-11	SHORT CHIP	0		
R7841	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7842	1-216-864-11	SHORT CHIP	0		
R7844	1-216-809-11	METAL CHIP	100	5%	1/10W
R7845	1-216-821-11	METAL CHIP	1K	5%	1/10W
R7850	1-216-817-11	METAL CHIP	470	5%	1/10W
R7851	1-216-835-11	METAL CHIP	15K	5%	1/10W
R7852	1-216-817-11	METAL CHIP	470	5%	1/10W
R7853	1-216-837-11	METAL CHIP	22K	5%	1/10W
R7854	1-216-864-11	SHORT CHIP	0		
R7858	1-216-809-11	METAL CHIP	100	5%	1/10W
R7859	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7860	1-216-837-11	METAL CHIP	22K	5%	1/10W
R7861	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7863	1-216-837-11	METAL CHIP	22K	5%	1/10W
R7864	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7865	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7866	1-216-827-11	METAL CHIP	3.3K	5%	1/10W
R7867	1-216-817-11	METAL CHIP	470	5%	1/10W
R7877	1-216-864-11	SHORT CHIP	0		
R7878	1-216-864-11	SHORT CHIP	0		
R7883	1-216-864-11	SHORT CHIP	0		
R7885	1-216-864-11	SHORT CHIP	0		
R7886	1-216-864-11	SHORT CHIP	0		
R7888	1-216-803-11	METAL CHIP	33	5%	1/10W
R7890	1-216-295-91	SHORT CHIP	0		
R7891	1-218-867-11	METAL CHIP	6.8K	0.5%	1/10W
R7892	1-218-891-11	METAL CHIP	68K	0.5%	1/10W
R7893	1-218-911-11	METAL CHIP	470K	0.5%	1/10W
R7894	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7896	1-216-295-91	SHORT CHIP	0		
R7897	1-216-295-91	SHORT CHIP	0		
R7909	1-216-864-11	SHORT CHIP	0		
R7910	1-216-797-11	METAL CHIP	10	5%	1/10W
R7911	1-216-797-11	METAL CHIP	10	5%	1/10W
R7912	1-216-803-11	METAL CHIP	33	5%	1/10W
R7913	1-216-797-11	METAL CHIP	10	5%	1/10W
R7914	1-216-797-11	METAL CHIP	10	5%	1/10W
R7915	1-216-797-11	METAL CHIP	10	5%	1/10W
R7919	1-216-821-11	METAL CHIP	1K	5%	1/10W
R7940	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7941	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7952	1-216-833-11	METAL CHIP	10K	5%	1/10W

Les composants identifies par une trame et une marque ⚠ sont critiques pour la securite. Ne les remplacer que par une piece portant le numero specifie.

The components identified by shading and mark ⚠ are critical for safety. Replace only with part number specified.

REF. NO.	PART NO.	DESCRIPTION			REMARK
R7954	1-216-845-11	METAL CHIP	100K	5%	1/10W
R7987	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7989	1-216-845-11	METAL CHIP	100K	5%	1/10W
R7991	1-216-864-11	SHORT CHIP	0		
R7992	1-216-864-11	SHORT CHIP	0		
R7994	1-216-864-11	SHORT CHIP	0		
R7997	1-216-833-11	METAL CHIP	10K	5%	1/10W
R7998	1-216-833-11	METAL CHIP	10K	5%	1/10W
R8000	1-216-829-11	METAL CHIP	4.7K	5%	1/10W
R8002	1-216-864-11	SHORT CHIP	0		
		< NETWORK RESISTOR >			
RB7900	1-234-371-21	RES, NETWORK 47		(1005X4)	
RB7901	1-234-371-21	RES, NETWORK 47		(1005X4)	
RB7902	1-242-963-21	RES, NETWORK 33		(1005X4)	
RB7903	1-234-369-21	RES, NETWORK 10		(1005X4)	
RB7904	1-234-369-21	RES, NETWORK 10		(1005X4)	
RB7905	1-234-369-21	RES, NETWORK 10		(1005X4)	
RB7906	1-234-369-21	RES, NETWORK 10		(1005X4)	
RB7907	1-234-369-21	RES, NETWORK 10		(1005X4)	
RB7908	1-234-369-21	RES, NETWORK 10		(1005X4)	
RB7909	1-234-369-21	RES, NETWORK 10		(1005X4)	
RB7910	1-234-369-21	RES, NETWORK 10		(1005X4)	
RB7911	1-234-369-21	RES, NETWORK 10		(1005X4)	
RB7913	1-234-400-21	CONDUCTOR, NETWORK		(2010X4)	
RB7914	1-242-963-21	RES, NETWORK 33		(1005X4)	
RB7916	1-234-400-21	CONDUCTOR, NETWORK		(2010X4)	
RB7917	1-234-400-21	CONDUCTOR, NETWORK		(2010X4)	
		< TUNER >			
TU7800	8-597-505-00	TUNER UNIT, DIGITAL BTD-CA811Z			

****

* A-1073-391-A QU BOARD, COMPLETE
****

		< CAPACITOR >			
C7951	1-115-156-11	CERAMIC CHIP	1UF		10V
C7952	1-115-156-11	CERAMIC CHIP	1UF		10V
C7953	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7954	1-164-156-11	CERAMIC CHIP	0.1UF		25V
		< CONNECTOR >			
CN7951	1-573-768-21	PIN, CONNECTOR (1.5MM) (SMD)5P			
CN7952	1-818-486-11	PCMCIA CONNECTOR (SMD)			
CN7953	1-818-483-11	FFC/FPC CONNECTOR (ZIF) 80P			
		< TEST POINT >			
TP7950	1-694-766-21	TERMINAL (ONBOARD CONTACT)			

****

S2 MOUNT
****

		< CAPACITOR >			
C7180	1-164-156-11	CERAMIC CHIP	0.1UF		25V
C7181	1-165-908-11	CERAMIC CHIP	1UF	10%	10V
C7182	1-162-915-11	CERAMIC CHIP	10PF	0.50PF	50V
C7183	1-162-915-11	CERAMIC CHIP	10PF	0.50PF	50V
		< CONNECTOR >			
CN7180	1-819-333-11	HEADER ASSEMBLY FOR PWB 5P			
		< IC >			
IC7180	6-707-223-01	IC LM75BIM-5/NOPB			
		< RESISTOR >			
R7181	1-216-801-11	METAL CHIP	22	5%	1/10W
R7182	1-216-801-11	METAL CHIP	22	5%	1/10W
R7185	1-216-864-11	SHORT CHIP	0		
R7186	1-216-864-11	SHORT CHIP	0		
R7187	1-216-864-11	SHORT CHIP	0		

****

T1 MOUNT
****

		< CONNECTOR >	
CN7150	1-819-336-11	HEADER ASSEMBLY FOR PWB 3P	
		< SWITCH >	
S7150	1-786-591-11	SWITCH, MICRO	

****

T2 MOUNT
****

		< SWITCH >	
S7155	1-786-591-11	SWITCH, MICRO	

****

MISCELLANEOUS
****

	A-1054-757-A	CONVERTER, PS
	A-1123-069-A	OPTICS UNIT BLOCK ASSY (E50A10)
	A-1123-071-A	OPTICS UNIT BLOCK ASSY (E42A10)
	A-1124-850-A	LAMP BLOCK ASSY
⚠	1-468-936-11	POWER SUPPLY BLOCK
	1-576-912-11	THERMOSTAT
⚠	1-787-231-11	D.C. FAN (SIROCCO)
⚠	1-787-333-11	D.C. FAN
⚠	1-787-373-11	FAN,DC
⚠	1-791-192-21	CORD, NOISE FILTER WITH POWER
	1-826-219-11	LOUDSPEAKER (5X15cm)
	1-830-099-21	LEAD WIRE WITH CONNECTOR(LVDS)

****

ACCESSORIES & PACKING MATERIALS
****

	2-597-544-11	MANUAL, INSTRUCTION

REF. NO.	PART NO.	DESCRIPTION	REMARK
	2-597-544-21	MANUAL, INSTRUCTION	
	2-597-544-31	MANUAL, INSTRUCTION	
	2-597-545-11	QUICK SETUP GUIDE	
	2-597-545-21	QUICK SETUP GUIDE	
	2-597-545-31	QUICK SETUP GUIDE	
		< REMOTE COMMANDER >	
	1-479-327-11	REMOTE COMANDER RM-YD003	
	9-885-083-75	COVER, BATTERY	
	9-885-089-78	COVER, SLIDE	
		< OPTIONAL ACCESSORIES >	
	93-0875-00	LAMP XL-2400	

©2005.10

SONY

2-597-544-**11**(1)

GRAND WEGA™

LCD Projection TV
HD-TV
Operating Instructions

KDF-E42A10
KDF-E50A10

© 2005 Sony Corporation

Owner's Record

The model and serial numbers are located at the rear of the TV. Record these numbers in the spaces provided below. Refer to them whenever you call upon your Sony dealer regarding this product.

Model No. _____

Serial No. _____

Contacting Sony

If, after reading the following instructions, you have additional questions related to the use of your Sony® TV, please call one of the following numbers.

Customers in the continental United States contact the Direct Response Center at:

1-800-222-SONY (7669)

or visit http://www.sonystyle.com/tv/

Customers in Canada contact the Customer Relations Center at:

1-877-899-SONY (7669)

or visit http://www.sonystyle.ca/tv/

WARNING

To reduce the risk of fire or electric shock, do not expose this apparatus to rain or moisture.

This symbol is intended to alert the user to the presence of uninsulated “dangerous voltage” within the product’s enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.

This symbol is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

The apparatus shall not be exposed to dripping or splashing and no objects filled with liquids, such as vases, shall be placed on the apparatus.

CAUTION

To prevent electric shock, do not use this polarized AC plug with an extension cord, receptacle or other outlet unless the blades can be fully inserted to prevent blade exposure.

CAUTION

When using TV games, computers, and similar products with your projection TV, keep the brightness and contrast functions at low settings. If a fixed (non-moving) pattern is left on the screen for long periods of time at a high brightness or contrast setting, the image can be permanently imprinted onto the screen. Continuously watching the same program can cause the imprint of station logos onto the TV screen. These types of imprints are not covered by your warranty because they are the result of misuse.

Note on Caption Vision

This TV provides display of TV closed captioning in accordance with §15.119 of the FCC rules.

For Customers in the United States

If you have any questions about this product, you may call; Sony Customer Information Services Center 1-800-222-7669 or http://www.sony.com/

Declaration of Conformity

Trade Name: SONY
Model: KDF-E42A10/KDF-E50A10
Responsible Party: Sony Electronics Inc.
Address: 16450 W. Bernardo Dr,
San Diego, CA 92127 U.S.A.
Telephone Number: 858-942-2230

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTIFICATION

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- ☐ Reorient or relocate the receiving antenna.
- ☐ Increase the separation between the equipment and receiver.
- ☐ Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- ☐ Consult the dealer or an experienced radio/TV technician for help.

You are cautioned that any changes or modifications not expressly approved in this manual could void your authority to operate this equipment.

For Customers in Canada

This Class B digital apparatus complies with Canadian ICES-003.

Safety

- ☐ Operate the TV only on 120 V AC.
- ☐ Use the AC power cord specified by Sony and suitable for the voltage where you use it.
- ☐ The plug is designed, for safety purposes, to fit into the wall outlet only one way. If you are unable to insert the plug fully into the outlet, contact your dealer.
- ☐ If any liquid or solid object should fall inside the cabinet, unplug the TV immediately and have it checked by qualified service personnel before operating it further.
- ☐ If you will not be using the TV for several days, disconnect the power by pulling the plug itself. Never pull on the cord.
- ☐ For details concerning safety precautions, see “Important Safety Instructions” on page 5.

Installing

- ☐ The TV should be installed near an easily accessible power outlet.
- ☐ To prevent internal heat buildup, do not block the ventilation openings.
- ☐ Do not install the TV in a hot or humid place, or in a place subject to excessive dust or mechanical vibration.
- ☐ Avoid operating the TV at temperatures below 41°F (5°C).
- ☐ If the TV is transported directly from a cold to a warm location, or if the room temperature changes suddenly, the picture may be blurred or show poor color due to moisture condensation. In this case, please wait a few hours to let the moisture evaporate before turning on the TV.

(Continued)

- ☐ To obtain the best picture, do not expose the screen to direct illumination or direct sunlight. It is recommended to use spot lighting directed down from the ceiling or to cover the windows that face the screen with opaque drapery. It is desirable to install the TV in a room where the floor and walls are not of a reflective material.
- ☐ See pages 13 and 14 for more information on the installation.

CAUTION

Use the following Sony appliance(s) only with the following TV STAND.

Use with other TV STAND may cause instability and possibly result in injury.

SONY APPLIANCE MODEL NO.

KDF-E42A10

KDF-E50A10

SONY TV STAND MODEL NO.

SU-RG11S (KDF-E42A10)

SU-RG11M (KDF-E50A10)

To Customers

Sufficient expertise is required for installing the specified product. Be sure to subcontract the installation to Sony dealers or licensed contractors and pay adequate attention to safety during the installation.

For Customers in the United States

This product contains mercury. Disposal of this product may be regulated if sold in the United States. For disposal or recycling information, please contact your local authorities or the Electronics Industries Alliance (http://www.eiae.org).

Note

This digital television is capable of receiving analog basic, digital basic and digital premium cable television programming by direct connection to a cable system providing such programming. A security card provided by your cable operator is required to view encrypted digital programming. Certain advanced and interactive digital cable services such as video-on-demand, a cable operator's enhanced program guide and data-enhanced television services may require the use of a set-top box. For more information call your local cable operator.

This television also includes a QAM demodulator which should allow you to receive unscrambled digital cable television programming via subscription service to a cable service provider. Availability of digital cable television programming in your area depends on the type of programming and signal provided by your cable service provider.

Trademark Information

CableCARD™ is a trademark of Cable Television Laboratories, Inc.

TruSurround XT, SRS and the (●)* symbol are trademarks of SRS Labs, Inc. TruSurround XT technology is incorporated under license from SRS Labs, Inc.

Licensed by BBE Sound, Inc. under USP4638258, 4482866. "BBE" and BBE symbol are trademarks of BBE Sound, Inc.

Macintosh is a trademark licensed to Apple Computer, Inc., registered in the U.S.A and other countries.

WEGA, Grand WEGA, WEGA GATE, Steady Sound, Digital Reality Creation and CineMotion are registered trademarks of Sony Corporation.

"PlayStation" is a trademark of Sony Computer Entertainment, Inc.

DOLBY DIGITAL

This TV is manufactured under license from Dolby Laboratories. "Dolby" and the double-D symbol are trademarks of Dolby Laboratories.

HDMI

This TV incorporates High-Definition Multimedia Interface (HDMI™) technology. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

Important Safety Instructions

1) Read these instructions.
2) Keep these instructions.
3) Heed all warnings.
4) Follow all instructions.
5) Do not use this apparatus near water.

6) Clean only with dry cloth.

7) Do not block any ventilation openings. Install in accordance with the manufacturer's instructions.

8) Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.

9) Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.



10) Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.

11) Only use attachments/accessories specified by the manufacturer.

12) Use only with the cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.

13) Unplug this apparatus during lightning storms or when unused for long periods of time.

14) Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.

☐ Be sure to observe the TV's "For Safety" section on page 6.

Antennas

Outdoor Antenna Grounding

If an outdoor antenna is installed, follow the precautions below. An outdoor antenna system should not be located in the vicinity of overhead power lines or other electric light or power circuits, or where it can come in contact with such power lines or circuits.

WHEN INSTALLING AN OUTDOOR ANTENNA SYSTEM, EXTREME CARE SHOULD BE TAKEN TO KEEP FROM CONTACTING SUCH POWER LINES OR CIRCUITS AS CONTACT WITH THEM IS ALMOST INVARIABLY FATAL.

Be sure the antenna system is grounded so as to provide some protection against voltage surges and built-up static charges.

Section 810 of the National Electrical Code (NEC) in USA and Section 54 of the Canadian Electrical Code in Canada provides information with respect to proper grounding of the mast and supporting structure, grounding of the lead-in wire to an antenna discharge unit, size of grounding conductors, location of antenna discharge unit, connection to grounding electrodes, and requirements for the grounding electrode.

(Continued)

Antenna Grounding According to the NEC

Refer to section 54-300 of Canadian Electrical Code for Antenna Grounding.


Antenna lead-in wire
Ground clamp
Antenna lead-in wire (NEC Section 810-20)
Electrical service equipment
Grounding conductors (NEC section 810-21)
Ground clamps
Power service grounding electrode system (NEC Art 250 Part H)
NEC: National Electrical Code

Cleaning

- ☐ Clean the rear cover area of the TV regularly. Dust in the rear cover area may cause a problem with the cooling system of the TV set.
- ☐ Clean the cabinet of the TV with a dry soft cloth. To remove dust from the screen, wipe it gently with a soft cloth. Stubborn stains may be removed with a cloth slightly dampened with solution of mild soap and warm water. Never use strong solvents such as thinner or benzine for cleaning. If the picture becomes dark after using the TV for a long period of time, it may be necessary to clean the inside of the TV. Consult qualified service personnel.

- ☐ Unplug the AC power cord when cleaning this unit. Cleaning this unit with a plugged AC power cord may result in electric shock.

On Contamination on the Screen Surface

The screen surface has a special coating to reduce reflections. To prevent screen damage, clean the screen as follows:

- ☐ Clean the screen with a soft cloth.
- ☐ To remove hard contamination, use a cloth moistened with a solution of mild detergent and water. Do not spray cleaning solution directly onto the TV. It should only be sprayed to moisten the cleaning cloth.
- ☐ Do not use any type of abrasive pad, alkaline cleaner, acid cleaner, scouring powder, chemical cloth, or solvent such as alcohol, benzene or thinner, as these may scratch the screen's coating.

Service

Damage Requiring Service

Do not attempt to service the set by yourself since opening the cabinet may expose you to dangerous voltage or other hazards.

Unplug the set from the wall outlet and refer servicing to qualified service personnel.

Replacement Parts

When replacement parts are required, be sure the service technician certifies in writing that he has used replacement parts specified by the manufacturer that have the same characteristics as the original parts.

Unauthorized substitutions may result in fire, electric shock or other hazards.

See “Replacing the Lamp” on page 86.

For Safety

Be Careful When Moving the TV



When you place the TV in position, be careful not to drop it on your foot or fingers.

Watch your footing while installing the TV.

Carry the TV in the Specified Manner



If you carry the TV in a manner other than the specified manner and without the specified number of persons, it may drop and a serious injury may be caused. Be sure to follow the instructions mentioned below.

- ☐ Carry the TV with the specified number of persons (see page 13).
- ☐ Hold the TV tightly when carrying it.
- ☐ Before carrying the TV, disconnect any accessories or cables.

About the TV

Although the TV is made with high-precision technology, black dots may appear or bright points of light (red, blue, or green) may appear constantly on the screen. This is a structural property of the panel and is not a defect.

Installation

- ☐ If direct sunlight or other strong illumination shines on the screen, part of the screen may appear white due to reflections from behind the screen. This is a structural property of the TV.
  Do not expose the screen to direct illumination or direct sunlight.
- ☐ The picture quality may be affected by your viewing position. For the best picture quality, install your TV according to “Recommended Viewing Area” on page 14.
- ☐ When installing your TV against a wall, keep it at least 4 inches (10 cm) away from the wall.

Projection Lamp

- ☐ Your TV uses a projection lamp as its light source. It is time to replace the lamp with a new one (not supplied) when:
  - the lamp replacement indicator on the front panel blinks in red,
  - screen images become dark,
  - no image appears on the display after prolonged use.
- ☐ In rare instances, the bulb may pop inside the lamp unit, but the lamp unit is designed to contain all of broken glass pieces inside the lamp unit. (See “Replacing the Lamp” on page 86.)
- ☐ When the lamp eventually burns out, you may hear a noticeable pop sound. This is normal and is inherent in this type of lamp.

Disposal of Used Batteries

To preserve our environment, dispose of used batteries according to your local laws or regulations.

Cooling Fan

This TV uses a cooling fan. You may hear the noise of fan running, depending on the placement of your TV. The noise may be more noticeable during the night or when the background noise level is low.

Contents

Introducing the TV

Welcome 9
- Package Contents 9
- Features 9

Enjoying Your TV 11
- Notes on the TV 11
- Screen 11
- Indicators 12
- Projection Lamp 12

Installing the TV 13
- Carrying Your TV 13
- Take Precaution during Installation 13
- Preventing the TV from Toppling Over 14
- When Installing Your TV against a Wall 14
- Recommended Viewing Area 14

TV Controls and Connectors 15
- Front Panel 15
- Side Panel 16
- Rear Panel 17

Connecting the TV

Overview 19
- Making Video and Audio Connections 19
- About Using S VIDEO 20
- About Using HDMI to DVI Adapter 20

Basic Connections 21
- Cable System or VHF/UHF 22
- Cable Box and Antenna 23
- Cable Box 24
- Satellite Receiver 25
- Digital Cable Box or Digital Satellite Receiver 26
- Equipment with HDMI Connection 27
- Equipment with DVI Connection 28
- Equipment with Digital Audio (Optical) 29

Using CableCARD Device 30
- About Using CableCARD Device 30
- Activating CableCARD Service 30
- Removing the CableCARD Device 31

Setting Up the Channel List 32
- Using Initial Setup 32

Connecting Optional Equipment 33
- VCR and Cable 34
- VCR and Cable Box 35
- Two VCRs for Tape Editing 37
- DVD Player with Component Video Connectors 38
- DVD Player with S VIDEO and Audio Connectors 39
- Personal Computer 40
- Camcorder or “PlayStation” 41
- Audio Receiver 42

Watching the TV

Overview 43

Inserting Batteries into the Remote Control 43

Button Descriptions 44

Programming the Remote Control 47

Using Other Equipment with Your Remote Control 49

Special Buttons on the Remote Control 51
- Using the GUIDE Button 51
- Using the WIDE Button 53
- Using the JUMP Button 54
- Using the FREEZE Button 54

Introducing WEGA GATE

Overview of WEGA GATE 55

Navigating and Selecting Items 57

Using Favorites in WEGA GATE 57

Using Cable in WEGA GATE 58

Using Antenna in WEGA GATE 58

Using External Inputs in WEGA GATE 59

Using Settings in WEGA GATE 59

Using the Settings

Overview 61

Accessing the Video Settings 63
- Selecting Video Options 63
- Selecting PC Video Options 65

Accessing the Audio Settings 66
- Selecting Audio Options 66
- Selecting PC Audio Options 68

Accessing the Screen Settings 69
Selecting Screen Options 69
Selecting PC Screen Options 71
Accessing the Channel Settings 72
Selecting Channel Options 72
Accessing the Parental Lock Settings..... 74
Selecting Parental Lock Options..... 74
Viewing Blocked Programs..... 75
Selecting Custom Rating Options..... 76
Accessing the Setup Settings 78
Selecting Setup Options 78
Programming Caption Vision 80
Selecting PC Setup Options 81
Accessing the Applications Settings..... 83
Selecting Applications Options 83

Other Information

Overview..... 85
Contacting Sony 85
Replacing the Lamp..... 86
How to Replace the Lamp..... 86
Troubleshooting 90
Remote Control..... 90
CableCARD Device 90
Video..... 91
Audio..... 92
Channels..... 92
General 93
Specifications 94

Index

Index 96

Introducing the TV

Welcome

Thank you for purchasing this Sony's *HD* LCD projection TV. This manual is for models KDF-E42A10 and KDF-E50A10.

Package Contents

Along with your new TV, the packing box contains a remote control and two AA (R6) batteries. See page 95 for the complete list of packaging contents.

Features

Some of the features that you will enjoy with your new TV include:

- **WEGA GATE™:** WEGA GATE is a new feature that allows you to easily navigate to the most convenient TV functions: favorite channels, cable channels, antenna channels, external input list or settings.
- **WEGA Engine:** Delivers superb picture quality from any video source by minimizing the signal deterioration caused by digital-to-analog conversion and stabilizing the signal processing. This engine features unique Sony technology, including:
  - **DRC® (Digital Reality Creation)-MF V1:** Unlike conventional line doublers, the DRC Multifunction feature replaces the signal's NTSC waveform with the near-HD equivalent by digital mapping processing. The DRC Palette option lets you customize the level of detail (Reality) and smoothness (Clarity) to create up to three custom palettes.
- **Integrated HDTV:** You can watch digital television programs and enjoy the improved audio/video quality offered by these programs.
- **Wide Screen Mode:** Allows you to watch 4:3 normal broadcasts in wide screen mode (16:9 aspect ratio).
- **Advanced Iris:** This advanced iris shutter works automatically open and close according to the incoming signal level to create brighter whites and better contrast in dark scenes.
- **CineMotion®:** Using the reverse 3-2 pull down technology, the CineMotion feature provides smoother picture movement when playing back movies or other video sources on film.
- **Parental Control:** V-Chip technology allows parents to block unsuitable programming from younger viewers.
- **CableCARD™ slot:** Provides cable subscribers with access to digitally encrypted cable channels — without the need for a set-top box — that will enable you to receive not only standard definition but also high definition television. The CableCARD device, which is provided by your cable TV company, is inserted into the TV's rear panel

(Continued)

CableCARD slot. After the service is activated with your cable TV company, the card replaces the need for a separate set-top box. (Check with your cable TV company about CableCARD service details, limitations, pricing, and availability. For more information about the CableCARD device in this manual, see page 30.)

- **Component Video Inputs:** Offers the best video quality for DVD (480p, 480i) and digital set-top box (1080i, 720p, 480p, 480i) connections.
- **S VIDEO Inputs:** Provides a high-quality image from connected equipment.
- **Favorite Channels:** With the WEGA GATE function, it allows you to navigate a list of up to 16 favorite channels without leaving the current channel.
- **Steady Sound®:** Equalizes volume levels so there is consistent output between programs and commercials.
- **HDMI (High-Definition Multimedia Interface):** Provides an uncompressed, all-digital audio/video interface between this TV and any HDMI-equipped audio/video component, such as a set-top box, DVD player, and A/V receiver. HDMI supports enhanced, or high-definition video, plus two-channel digital audio.

Enjoying Your TV

To enjoy your TV for years to come and maintain its original picture quality, you should perform periodic maintenance.

Notes on the TV

To enjoy clear picture

- ❑ Prevent sunlight or other light sources from shining directly on to the screen.
- ❑ The screen surface is easily scratched. Do not rub, touch, or tap it with sharp or abrasive objects (see "On Contamination on the Screen Surface" on page 6).

When not using the TV for a long period of time

- ❑ Unplug the AC power cord from the outlet if you anticipate not using the TV for more than a week.

When turning off the power

- ❑ The cooling fan will continue to operate for about two minutes. Allow several minutes before unplugging from the outlet or switching the breaker off.

On moisture condensation

- ❑ If your TV is moved directly from a cold to a warm location or is placed in a humid room, or if the room temperature changes suddenly, the picture may blur or show poor color. This is caused by moisture condensation on the lenses inside. Wait a few hours to let the moisture evaporate before turning on the TV. When the condensation has evaporated, the picture will return to normal.

Screen

To minimize reflection, the screen surface has a special coating. Inappropriate cleaning methods could damage the screen surface. Special care is required.

Cleaning the Screen Surface

Dust and dirt on the screen can affect the picture quality. To dust off the screen use a soft cloth. Be sure to follow the cleaning instruction on page 6 for stubborn stains and dirt.

Indicators



The indicators show the current status of your TV. If there is a change in the condition or a problem with the TV, the indicators will flash or light up in the manner described below to let you know that it requires your attention.

Indicator	*Flashing because...*
POWER/ STANDBY flashing	green : The lamp for the light source is preparing to turn on. When it is ready, it turns on. red : The lamp door or the lamp is not securely attached. The red indicator will continue to flash in intervals of three blinks at a time until the lamp door or the lamp is placed correctly. When the lamp door or the lamp is securely attached, the TV will turn on with green indicator.
LAMP indicator flashes	The projection lamp has burned out. Replace it with new one (see page 86).
TIMER indicator is lit	When one of the timers is set, the indicator will remain lit (will not flash) even when the TV is turned off.

Projection Lamp

How to replace the lamp, see page 86.

Your TV uses a projection lamp as its light source. As with any lamp, it has lifespan and needs to be replaced when the Lamp indicator flashes or the screen becomes darker. Note the following:

- ❑ After turning on your TV, it may take a while (1 minute or less) before the picture appears.
- ❑ When the projection lamp wears out, the screen goes dark. Replace the lamp with a new Sony XL-2400 replacement lamp (not supplied).

✍ **The light emitted from the lamp is quite bright when your TV is in use. To avoid eye discomfort or injury, do not look into the light housing when the power is on.**

Installing the TV

Carrying Your TV

Carrying the TV requires at least two people. Do not hold by the pedestal or the front panel of the TV. Doing so may cause these parts to break off.



Do not grasp the pedestal or the front panel of the TV.

When moving the TV, place one hand in the hole on the lower portion of the TV while grasping the top with the other hand, as shown in the illustration below.

KDF-E42A10



KDF-E50A10



If you have connected cables and cords, be sure to unplug them before moving the TV.

Take Precaution during Installation

To ensure the safety of children and the TV, keep children away from the TV during installation. Climbing on or pushing the TV or its stand may cause it to fall and damage the TV.

Preventing the TV from Toppling Over

As a protective measure, secure the TV as follows.

Using the TV stand with support belts

❑ Sony strongly recommends using the TV stand SU-RG11S (for KDF-E42A10)/SU-RG11M (for KDF-E50A10) with a support belt designed for your TV.



✍ **When using the SU-RG11S (for KDF-E42A10)/SU-RG11M (for KDF-E50A10) stand for your TV, you must use the support belt.**

When Installing Your TV against a Wall

Keep your TV at least 4 inches (10 cm) away from the wall to provide proper ventilation.

Recommended Viewing Area

Your viewing position may affect the picture quality.

For the best picture quality, install your TV within the areas shown below.

Model	*Viewing distance*
KDF-E42A10	min. 5.9 ft. (approx. 1.8 m)
KDF-E50A10	min. 6.6 ft. (approx. 2.0 m)

Horizontal Viewing Area



Vertical Viewing Area



TV Controls and Connectors

Front Panel



Item		Description
1	WEGA GATE	Press to display WEGA GATE and activate the ⁻╂⁻, ←, →, ↓, and ↑ buttons. Press again to exit WEGA GATE and activate the TV/VIDEO, – VOLUME + and – CHANNEL+ buttons.
2	⁻╂⁻ TV/VIDEO	Press to confirm the selection or setting. Press repeatedly to cycle through the video equipment connected to the TV's video inputs.
3	← → – VOLUME +	Press to adjust the volume.
4	↓ ↑ – CHANNEL +	Press to scan through channels. To scan quickly through channels, press and hold either – or +.
5	TIMER LED	When lit, indicates one of the timers or Sleep is set. When it is set, this LED will remain lit even if the TV is turned off. For details, see page 83.
6	LAMP LED	Lights up in red when the lamp for the light source has burned out. For details, see "Replacing the Lamp" on page 86.
7	POWER/ STANDBY LED	Lights up in green when the TV is turned on. If the LED blinks in red continuously, this may indicate the display unit needs servicing (see "Contacting Sony" on page 2). When the red LED blinks only three times, the lamp door of the lamp unit or the lamp itself is not securely attached (see page 88).
8	(IR) Infrared Receiver	Receives IR signals from the remote control. Do not put anything near the sensor, as its function may be affected.
9	POWER	Press to turn on and off the TV.
10	Speaker	Outputs audio signal.

✍ **The CHANNEL + button has a tactile dot. Use the tactile dot as a reference when operating the TV.**

Side Panel



Jack	*Description*
1 HD/DVD IN 2 (1080i/720p/ 480p/480i)	Connect to your DVD player's or digital set-top box's component video (YPBPR) and audio (L/R) jacks. Component video provides better picture quality than the S VIDEO (5 of rear panel) or the composite video (6 of rear panel) connections (see page 18).
2 VIDEO IN 2 VIDEO/ AUDIO L (MONO)/ AUDIO R	Connect to the composite video and audio output jacks on your camcorder or other video equipment. When Auto is selected for the Video 2 (Component) option in the Setup settings, the component video function will be preferentially activated (see page 79).

Rear Panel



Jack		Description
1	CABLE VHF/UHF	RF input that connects to your cable and VHF/UHF antenna signal.
2	CableCARD slot	CableCARD device provides cable subscribers with access to secure, digitally encrypted cable channels — without the need for a set-top box — that will enable you to receive not only standard definition but also high definition television. For more information, see page 30.
3	PC IN 7	Connect to the video output connector and audio output jack on your personal computer. For details, see page 40.
4	HDMI IN 6 HDMI/ L-AUDIO-R	HDMI (High-Definition Multimedia Interface) provides an uncompressed, all-digital audio/video interface between this TV and any HDMI-equipped audio/video component, such as a set-top box, DVD player, and A/V receiver. HDMI supports enhanced, or high-definition video, plus two-channel digital audio. You can also connect a DVI-equipped device to your TV by using an HDMI-to-DVI cable.

(Continued)

Jack		Description
5	VIDEO IN 1 S VIDEO	Connects to the S VIDEO output jack of your VCR or other video equipment that has S VIDEO. S VIDEO provides better picture quality than the composite video (6).
6	VIDEO IN 1/3 VIDEO/ L-AUDIO-R	Connect to the composite video and audio output jacks on your VCR or other video component. A third composite video and audio (VIDEO 2) is located on the left side panel of the TV.
7	HD/DVD IN 4/5 (1080i/720p/ 480p/480i)/ L-AUDIO-R	Connect to your DVD player's or digital set-top box's component video ($Y P_B P_R$) and audio (L/R) jacks. Component video provides better picture quality than the S VIDEO (5) or the composite video (6) connections.
8	AUDIO OUT (VAR/FIX) L/R	Connect to the left and right audio input jacks of your audio or video equipment. You can use these outputs to listen to your TV's audio through your stereo system.
9	DIGITAL AUDIO (OPTICAL) OUT (PCM/DOLBY* DIGITAL)	Connects to the optical audio input of a digital audio component that is PCM/Dolby Digital compatible.
10	AC IN	Connects the supplied AC power cord.

* Manufactured under license from Dolby Laboratories. "Dolby" and the double-D symbol are trademarks of Dolby Laboratories.

Connecting the TV

Overview

Your new LCD projection TV can receive both analog and digital broadcasting signals from antenna, satellite and cable TV.

To display clear crisp pictures, you must connect your TV correctly and choose the correct display format (see "Using the WIDE Button" on page 53). It is strongly recommended to connect the antenna using a 75-ohm coaxial cable to receive optimum picture quality signal. A 300-ohm twin lead cable can be easily affected by radio noise and the like, resulting in signal deterioration. If you use a 300-ohm twin lead cable, keep it as far away as possible from the TV.

Making Video and Audio Connections

The signals that enter your TV and connected devices will need to output in the correct format using the suitable connections. Below are different types of video connectors available these days. Your TV comes with all types of connectors with the exception of the DVI connector but your cable box or satellite receiver may be equipped with this type. When connecting your TV, use the inputs that are available on your devices that provide the best video performance, as described below.

Best Video Performance



Connector type		Separate audio connection required
	HDMI (High-Definition Multimedia Interface)	No
	DVI (Digital Video Interface) *	Yes L-AUDIO-R
	Component video (480i/480p/720p/1080i)	
	S VIDEO	
	Composite video	
	RF/Coaxial	No

* An adapter is necessary when you are connecting a DVI-equipped device to this TV (see page 20).

About Using S VIDEO

If the optional equipment you are connecting has an S VIDEO jack (shown at left), you can use an S VIDEO cable for improved picture quality (compared to an A/V cable). Because S VIDEO carries only the video signal, you also need to connect audio cables for sound, as shown below.

Example of an S VIDEO Connection



About Using HDMI to DVI Adapter

If you are connecting equipment with DVI connector with this TV, you will need to use an adapter. You can use an HDMI-to-DVI cable or an HDMI adapter (not supplied). Both are available from your local electronics store. When you use the adapter, you will also need to use separate audio cables for sound as DVI connector is for video signals only.



HDMI-to-DVI Cable



HDMI adapter



Audio cable

Basic Connections

The way in which you connect your TV will vary, depending on how your home receives a signal (antenna and satellite; cable and cable box) and whether or not you plan to connect a VCR.

If You Are Connecting	See Page
Cable System or VHF/UHF ❑ No cable box or VCR	**22**
Cable Box and Antenna ❑ Cable box unscrambles only some channels (usually premium channels) ❑ No VCR	**23**
Cable Box ❑ Cable box unscrambles all channels ❑ No VCR	**24**
Satellite Receiver	**25**
Digital Cable Box or Digital Satellite Receiver	**26**
Equipment with HDMI Connection	**27**
Equipment with DVI Connection	**28**
Equipment with Digital Audio (OPTICAL)	**29**

If you are connecting a VCR

❑ See the connections described on pages 34 and 35.

Cable System or VHF/UHF

For best results, use this connection if you:

- ❑ Have a cable and/or an antenna.

  (This is convenient if you are using a separate rooftop antenna to receive additional channels that are not provided by your cable TV company.)
- ❑ Do not have a cable box or VCR. (If you have a cable box, see pages 23 and 24. If you have a VCR, see pages 34 and 35.)

Antenna System	
Cable Type	***Connect As Shown***
Cable TV (CATV) and Antenna	

Notes on Using This Connection

To Do This...	*Do This ...*
Switch the TV's input between the cable and antenna	Press ANT to switch back and forth between the TV's VHF/UHF and CABLE inputs.

✍ **Do not use an indoor antenna, which is especially susceptible to radio noise.**

Cable Box and Antenna

Before connecting a cable box, see "Using CableCARD Device" on page 30.

For best results, use this connection if:

- ❑ Your cable company scrambles some channels, such as premium channels (which requires you to use a cable box), but does not scramble all channels.
- ❑ You do not have a VCR. (If you have a VCR, see pages 34 and 35.)

With this connection you can:

- ❑ Use the TV's remote control to change channels coming through the cable box to the TV's CABLE input. (You must first program the remote control for your specific cable box; see "Programming the Remote Control" on page 47.)
- ❑ Use the TV's remote control to change channels coming directly into the TV's VHF/UHF input jack.



Notes on Using This Connection

To Do This ...	Do This ...
Use the cable box	Tune the TV to the channel the cable box is set to (usually channel 3 or 4) and then use the cable box to switch channels.
Set up the TV remote control to operate the cable box	Program the remote control. See "Programming the Remote Control" on page 47.
Activate the remote control to operate the cable box	Press SAT/CABLE (FUNCTION) once, and the SAT/CABLE indicator lights up.
Prevent the accidental switching of TV channels	When using the cable box, ensure that the TV remains tuned to the channel that the cable box is set to (usually channel 3 or 4).
Switch the TV's input between the cable box and antenna	Press ANT to switch back and forth between the TV's VHF/UHF (scrambled channels) and CABLE (unscrambled) inputs.

Cable Box

Before connecting a cable box, see "Using CableCARD Device" on page 30.

For best results, use this connection if:

- ❑ Your cable company scrambles all channels, which requires you to use a cable box.
- ❑ You do not have a VCR. (If you have a VCR, see pages 34 and 35.)

With this connection you can:

- ❑ Use the TV's remote control to change channels coming through the cable box to the TV's VHF/UHF input jack. (You must first program the remote control for your specific cable box.)

To connect the cable box

1. Connect the CATV cable to the cable box's input jack.
2. Use a coaxial cable to connect the cable box's output jack to the TV's VHF/UHF input jack.
3. Run Auto Program, as described in "Setting Up the Channel List" on pages 32.



Notes on Using This Connection

To do this...	*Do This ...*
Use the cable box	Tune the TV to the channel the cable box is set to (usually channel 3 or 4) and then use the cable box to switch channels.
Set up the TV remote control to operate the cable box	Program the remote control. See "Programming the Remote Control" on page 47.
Activate the remote control to operate the cable box	Press SAT/CABLE (FUNCTION) once, and the SAT/CABLE indicator lights up.
Prevent the accidental switching of TV channels	When using the cable box, ensure that the TV remains tuned to the channel that the cable box is set to (usually channel 3 or 4).

Satellite Receiver

Disconnect all power sources before making any connections.

1. Connect the satellite antenna cable to the satellite receiver's SATELLITE IN jack.
2. Use A/V and S VIDEO cables to connect the satellite receiver's AUDIO and S VIDEO OUT jacks to the TV's AUDIO and S VIDEO IN jacks.
3. Use a coaxial cable to connect your cable to the TV's CABLE jack, or your antenna to the TV's VHF/UHF jack.

✍ **If your satellite receiver is not equipped with S VIDEO, use a VIDEO cable (yellow) instead of the S VIDEO cable.**



Digital Cable Box or Digital Satellite Receiver

Disconnect all power sources before making any connections.

1 Connect the RF coaxial cable from the CATV or satellite dish to the input of the digital cable box or digital satellite receiver.

2 Use a component video cable to connect the digital cable box or satellite receiver's YPBPR jacks to the TV's Y PB/CB PR/CR jacks. Use the HD/DVD IN 4 or 5 input.

✍ **Component video (Y PB/CB PR/CR) connection is necessary to view 480p, 720p, and 1080i formats. Note that this TV displays all format types of picture in a resolution of 1280 dots x 720 lines.**

3 Use an audio cable to connect the digital cable box or satellite receiver's AUDIO OUT jacks to the TV's AUDIO IN jacks.

✍ **The Y PB/CB PR/CR jacks do not provide audio, so audio cables must be connected to provide sound.**



Equipment with HDMI Connection

The HDMI jack provides both video and audio signals, so it is not necessary to connect an audio cable.

Use this hookup if:

- ❑ Your equipment has a High-Definition Multimedia Interface (HDMI).

Disconnect all power sources before making any connections.

Using an HDMI cable, connect the equipment's HDMI OUT jack to the TV's HDMI IN jack.



Equipment with DVI Connection

Disconnect all power sources before making any connections.

If you are connecting with DVI-HDTV output, you can connect to the TV's HDMI IN jack by using an HDMI-to-DVI cable or an adapter (both not supplied).



✍ **When using a HDMI-to-DVI cable or an adapter, be sure to connect the DVI output connector first; then connect to the HDMI input on your TV.**

Equipment with Digital Audio (Optical)

Disconnect all power sources before making any connections.

You can use the TV's DIGITAL AUDIO (OPTICAL) OUT jack to connect a digital audio device that is PCM/Dolby Digital compatible, such as an audio amplifier.

Using an optical audio cable, connect the device's OPTICAL IN jack to the TV's DIGITAL AUDIO (OPTICAL) OUT jack.


Rear of TV
DIGITAL AUDIO (OPTICAL) OUT
PCM/ DOLBY DIGITAL
Optical audio cable
The DIGITAL AUDIO (OPTICAL) OUT jack is available when the TV receives a digital TV channel.
Audio amplifier
LINE OUT
L AUDIO R
LINE IN
OPTICAL IN

Using CableCARD Device

The CableCARD device provides cable subscribers with access to digitally encrypted cable channels — without the need for a set-top box — that will enable you to receive not only standard definition but also high definition television. The CableCARD device, which is provided by your cable TV company, is inserted into the TV's rear panel CableCARD slot. After the service is activated with your cable TV company, the card replaces the need for a separate set-top box.

About Using CableCARD Device

If you are planning to use a separate cable box for digital cable TV services, you may be able to receive programming using this TV with the CableCARD device instead — except in the following circumstances:

- ❑ Your cable TV company does not provide CableCARD service in your viewing area.
- ❑ You want to access your cable TV company's interactive or advanced features (such as video-on-demand or, in some cases, pay-per-view). At this time, these services require a bidirectional link, which are only available through the use of a separate set-top box. CableCARD device is currently a unidirectional device only, and cannot provide these advanced services.

Check with your cable TV company for CableCARD service details, limitations, pricing, and availability, all of which are determined by your cable TV company — not Sony.

Activating CableCARD Service

Before you can use CableCARD service, you need to insert the CableCARD device (supplied by your cable TV company) and activate the service, as described below:

1 Insert the CableCARD device into the CableCARD slot.



✍ **CAUTION: When inserting the CableCARD device, the rear side of the card should face forward. Inserting the CableCARD incorrectly may result in permanent damage to the card and the TV.**

2 Gently push the card into the slot until it locks into place.

You can also access information about your CableCARD device in the Applications settings (see page 84).

3 After 1-2 minutes, the CableCARD device setup screen is automatically displayed. This screen includes information your cable TV company will request before they can activate your service.

4 Follow the displayed instructions: Phone your cable TV company. A representative will guide you through the activation process.

5 After your CableCARD device is activated, your cable TV company will download the service information, including the channel list, to the CableCARD device. After the CableCARD device has acquired channels from your cable TV company, the TV tunes to the lowest available channel.

Removing the CableCARD Device

In the event you want to cancel your service, contact your cable TV company.

✍ **Once the CableCARD device is removed, your TV will no longer decrypt digital cable TV programming services that require CableCARD.**

1 Push the eject button on the CableCARD slot to release the card.



2 Pull the CableCARD device straight out of the slot to remove it.

To install a different CableCARD device, follow the instructions in "Activating CableCARD Service" on page 30.

Setting Up the Channel List

After you finish connecting the TV, you can run the Initial Setup to create a list of available analog and digital channels. The Initial Setup screen appears when you turn on the TV for the first time after hooking it up. If you choose to set up the channels at a later time, select the Auto Program option in the Channel setting to scan available channels (see below).

✍ **The Initial Setup feature does not apply for installations that use a cable box for all channel selection.**

Using Initial Setup

If you are using a CableCARD device, Auto Program is disabled for the CABLE input.

To run Initial Setup the first time you turn on your TV

1 Press TV POWER to turn on the TV.
The Initial Setup screen appears.

2 Press ↑ or ↓ to highlight the on-screen display language. Then press ⊕. The messages "First please connect cable and/or antenna" appears. This may require 50+ minutes for completion and "Start auto program now?" appears.

3 Press ↑ or ↓ to highlight "Yes" then press ⊕.

Auto Program performed through Initial Setup will automatically create a list of receivable channels from both VHF/UHF antenna and cable TV channels if both sources are connected.

✍ **Auto Program may take a while (20 to 50 minutes) to complete. A progress bar is displayed while available channels are being scanned. If you cancel the Auto Program before all receivable channels are scanned, you may want to perform the task later (see "To run Auto Program at a later time" below).**

✍ **If you selected "No" during the Initial Setup, the Initial Setup message will appear each time you turn on the TV until you complete the Auto Program as a reminder.**

To run Auto Program at a later time

1 Select Settings in WEGA GATE, and then go to Channel settings.

2 Select Auto Program then select Start.

✍ **Auto Program will create a list of receivable channels for the current input (VHF/UHF antenna or CABLE). You will be required to run Auto Program for each RF input to create a list of available channels from both inputs.**

Connecting Optional Equipment

You can connect a variety of optional equipment to your TV. This section provides some of the individual connections you can make. For multiple connections, please refer to the Quick Setup Guide.

If You Are Connecting	See Page
VCR and Cable	**34**
VCR and Cable Box	**35**
Two VCRs for Tape Editing	**37**
DVD Player with Component Video Connectors	**38**
DVD Player with S VIDEO and Audio Connectors	**39**
Personal Computer	**40**
Camcorder or “PlayStation”	**41**
Audio Receiver	**42**

VCR and Cable

Use this hookup if:

- ❑ You have cable TV that does not require a cable box.

Disconnect all power sources before making any connections.

1 Connect the CATV cable to the single (input) jack of the splitter.

2 Use a coaxial cable to connect one of the output jack of the splitter to the TV's CABLE jack.

3 Use a coaxial cable to connect the splitter's other output jack to the VCR's input jack.

4 Use A/V and S VIDEO cables to connect the VCR's AUDIO and S VIDEO OUT jacks to the TV's AUDIO and S VIDEO IN jacks.

✍ **If your VCR is not equipped with S VIDEO, use a VIDEO cable (yellow) instead of the S VIDEO cable.**



VCR and Cable Box

Before connecting a cable box, see "Using CableCARD Device" on page 30.

Use this hookup if:

- ❑ Your cable TV company scrambles some channels, but not all of them (pay channels vs. regular cable channels) and you need to use a cable box.

With this connection you can:

- ❑ Use the TV's remote control to change channels on your cable box when the signal is scrambled. To program your Sony remote control to operate your cable box, see "Programming the Remote Control" on page 47.
- ❑ Use the TV's remote control to change channels on your TV when the signal is not scrambled. Your TV's tuner provides a better picture quality than the output of your cable box.

Disconnect all power sources before making any connections.

1. Connect the CATV cable to the single (input) jack of the splitter.
2. Use a coaxial cable to connect one of the output jack of the splitter to the TV's CABLE jack.
3. Use a coaxial cable to connect the splitter's other output jack to the cable box's input jack.
4. Use a coaxial cable to connect the cable box's output jack to the VCR's RF input jack.
5. Use an A/V cable to connect the cable box's A/V output jacks to the TV's A/V input jacks.
6. Use an A/V and S VIDEO cables to connect the VCR's AUDIO and S VIDEO OUT jacks to the TV's AUDIO and S VIDEO IN jacks.

✍ **If your VCR is not equipped with S VIDEO, use a VIDEO cable (yellow) instead of the S VIDEO cable.**

7. Run Initial Setup, as described in "Setting Up the Channel List" on page 32.

✍ **To view scrambled channels, tune the TV to the channel the cable box is set to (usually channel 3 or 4) and then use the cable box to switch channels.**

(Continued)


Rear of TV
CABLE
VHF/UHF
S VIDEO
VIDEO
AUDIO
L
R
S VIDEO cable
VIDEO
AUDIO-L
AUDIO-R
VIDEO
AUDIO-L
AUDIO-R
VCR
AUDIO R AUDIO L VIDEO S VIDEO OUT
LINE OUT
IN
Coaxial cable
2
CATV cable
1
Splitter
3
6
4
Coaxial cable
A/V cable
Cable box
AUDIO R AUDIO L VIDEO OUT
LINE OUT
IN
5
A/V cable
Coaxial cable
Cables are often color-coded to connectors. Connect red to red, white to white, etc.
If you are connecting a digital cable box, you will need a special bi-directional splitter designed to work with your cable box.

Two VCRs for Tape Editing

Using S VIDEO jacks? See page 20.

If you connect two VCRs, you can record from one VCR to the other while using your TV to monitor what is being recorded.

Disconnect all power sources before making any connections.

1 Use an A/V cable to connect the playback VCR's A/V output jacks to the recording VCR's A/V input jacks.

2 Use an A/V cable to connect the recording VCR's A/V output jacks to the TV's A/V input jacks.

Cables are often color-coded to connectors. Connect red to red, white to white, etc.



✍ **To perform tape editing, set the TV to the video input intended for playback by pressing TV/VIDEO on the remote control.**

✍ **You may need to change the video input on your VCR. See your VCR's operating manual for instructions.**

✍ **If your VCRs have S VIDEO jacks: For best picture quality, use an S VIDEO connection instead of the VIDEO cable (yellow) on your combined A/V cable.**
Using an S VIDEO cable, connect the playback VCR's S VIDEO OUT jack to the recording VCR's S VIDEO IN jack. S VIDEO does not provide audio, so audio cables must be connected to provide sound.

✍ **You cannot record signals from equipment connected to the Y P_B/C_B P_R/C_R input.**

DVD Player with Component Video Connectors

Use this hookup if:

- ❑ Your DVD player has component (YPBPR) jacks.

Disconnect all power sources before making any connections.

1 Use a component video cable to connect the DVD player's YPBPR jacks to the TV's Y PB/CB PR/CR jacks. Use the HD/DVD IN 4 or 5 input.

✍ **The YPBPR jacks on your DVD player are sometimes labeled YCBCR, or Y, B-Y and R-Y. If so, connect the cables to like colors.**

2 Use an audio cable to connect the DVD player's AUDIO OUT jacks to the TV's AUDIO IN jacks. Be sure to use the same row of inputs that you used for the video connection (HD/DVD IN 4 or 5).



✍ **To take advantage of the Wide Mode feature, set the DVD player's aspect ratio to 16:9. For details, refer to the operating instructions supplied with your DVD player.**

DVD Player with S VIDEO and Audio Connectors

Use this hookup if:

❑ Your DVD player does not have component (YPBPR) jacks.

Disconnect all power sources before making any connections.

1 Use an A/V cable to connect the DVD player's AUDIO OUT jacks to the TV's AUDIO IN jacks.

2 Use an S VIDEO cable to connect the DVD player's S VIDEO jack to the TV's S VIDEO jack.



Cables are often color-coded to connectors. Connect red to red, white to white, etc.

✍ **If your DVD player is not equipped with S VIDEO, use a VIDEO cable (yellow) instead of the S VIDEO cable.**

✍ **To watch the DVD player, press TV/VIDEO repeatedly to select the DVD input (VIDEO 1 in the illustration). If you have a non-Sony DVD player and want to set up the TV remote control to operate it, you must program the remote control. See "Programming the Remote Control" on page 47.**

✍ **To control DVD functions with the TV remote control, see "Operating a DVD Player or DVD Changer" on page 49.**

✍ **To easily identify equipment connected to the TV, see the instructions for setting up Label Video Inputs on page 79.**

Personal Computer

- When connecting to an Apple Macintosh computer, use the HD15-HD15 cable to connect PC IN of the TV to video output connector of the computer. For some Apple Macintosh computers, it may be necessary to use an adapter (not supplied). If this is the case, connect the adapter to the computer before connecting the HD15-HD15 cable.
- If the picture is noisy or flickering, adjust the Phase and Pitch in the Screen settings on page 71.

To connect a PC (personal computer)

If you connect your PC to the TV, you can watch your personal computer's display on the TV.
When your PC is connected to the TV with the HD15-HD15 cable and optional audio cable, you can view and listen to the PC's video and audio output on the TV.



Camcorder or "PlayStation"

You can connect a camcorder or "PlayStation" to your TV. For easy connection, use VIDEO IN 2 on the left side of the TV. To use the S VIDEO jack instead of the VIDEO jack (yellow), use VIDEO IN 1 on the rear panel of the TV.

To connect a camcorder or "PlayStation" to VIDEO IN 1

Use A/V and S VIDEO cables to connect the AUDIO and S VIDEO OUT jacks on the camcorder or "PlayStation" to the AUDIO and S VIDEO IN jacks on the rear panel of the TV, as shown below.

To connect a camcorder or "PlayStation" to VIDEO IN 2

Select Off in the Video 2 (Component) option in the Setup settings (see page 79). Use an A/V cable to connect the A/V output jacks on the camcorder or "PlayStation" to the A/V input jacks on the left side of the TV.

✍ **If your camcorder is not equipped with S VIDEO, use a VIDEO cable (yellow) instead of the S VIDEO cable.**

✍ **If you have a mono camcorder, connect its audio output jack to the TV's L MONO audio input jack.**



Audio Receiver

For improved sound quality, you may want to play the TV's audio through your stereo system (see page 67).

Disconnect all power sources before making any connections.

Using an audio cable, connect the TV's AUDIO OUT (VAR/FIX) jacks to the audio receiver's audio LINE IN jacks.

✍ **AUDIO OUT jacks are operable only when the TV's Speaker is set to Off.**



Watching the TV

Overview

The table on the next page describes the buttons on the remote control.

Topic	Page
Inserting Batteries into the Remote Control	**43**
Button Descriptions	**44**
Programming the Remote Control	**47**
Manufacturer's Codes	**48**
Using Other Equipment with Your Remote Control	**49**
Special Buttons on the Remote Control	**51**

Inserting Batteries into the Remote Control

Insert two size AA (R6) batteries (supplied) by matching the ⊕ and ⊖ on the batteries to the diagram inside the battery compartment.



✍ **To avoid possible damage from battery leakage, remove the batteries if you anticipate the remote control will not be used for an extended period.**

✍ **Handle the remote control with care. Avoid dropping it, getting it wet, or placing it in direct sunlight, near a heater, or in high humidity.**

✍ **Your remote control can be programmed to operate most video equipment. (See "Programming the Remote Control" on page 47.)**

Button Descriptions



The 5 button, CH + button, MTS/SAP and Play button have a tactile dot. Use the tactile dot as a reference when operating the TV.

Button	Description
1 MUTING	Press to mute the sound. Press again or press VOL + to unmute.
2 TV/VIDEO	Press to cycle through the video equipment connected to your TV's video inputs.
3 FUNCTION Buttons	The FUNCTION button indicator lights up momentarily when pressed to show which external equipment the remote control is operating. When the remote control is set to operate the external equipment, these buttons will operate the equipment you choose. You must first press one of these FUNCTION buttons to operate the corresponding equipment. See page 47 for Programming the Remote Control.
4 0-9, ENT	Press 0-9 to select a channel: the channel changes after 2 seconds. Press ENT to change channels immediately.
5 ⊙	Use ⊙ with 0-9 and ENT buttons to select digital channels (for example, 2.1).
6 JUMP	Press to jump back and forth between two channels. The TV alternates between the current channel and the last channel that was selected.
7 ANT	Press to change between the VHF/UHF input and the CABLE input.
8 SOUND	Press to cycle through different sound settings: Dynamic for enhance treble and bass, Standard for spoken dialog and Custom for flat setting.
9 PICTURE	Press repeatedly to cycle through the available video picture modes: Vivid, Standard, Custom. The video picture modes can be also accessed in the Video menu. For details, see "Selecting Video Options" on page 63.
10 GUIDE	Press to display the TV's program guide.
11 RETURN	Press to return to the previous page.
12 DVD/VCR Operating Buttons	When FUNCTION is switched on DVR or DVD/VCR, these buttons operate the video equipment you have programmed into the remote control. For details, see "Using Other Equipment with Your Remote Control" on page 49. ⏮ PREV: Press to replay the current program from the previous Chapter Mark (if any) or from the beginning of the live TV cache. ⏪• REPLAY: Press to replay the current program for a set period of time. •⏩ ADVANCE: Press to advance forward a set period of time when playing back a recorded program. ⏭ NEXT: Press to advance forward to the next Chapter Mark (if any) or to live TV when playing back a recorded program. ◀◀ (fast reverse): Press to play a program in fast rewind mode. ▷ • PLAY: Press to play a program at a normal speed. ▶▶ (fast forward): Press to play a program in fast forward mode. ❚❚ PAUSE: Press to pause playback. ■ STOP: Press to stop the playback of a recorded program.

Button	Description
13 VISUAL SEARCH	To be used only with your connected external equipment with visual search function. (Non-operable button for TV)
14 VOL +/–	Press to adjust the volume.
15 DVD/VCR Record Buttons	● REC: Press to record. By pressing this button alone will start the recording. ❚❚ REC PAUSE: Press to pause the recording. ■ REC STOP: Press to stop the recording.
16 TOP MENU	Press to display the disc menu from your connected DVD player.
17 MENU	Press to display the disc menu from your connected DVD player.
18 POWER	Press to turn on/off the eternal equipment selected from the FUNCTION buttons 3.
19 TV POWER	Press to turn on/off the TV.
20 MTS/SAP	Press repeatedly to cycle through the Multi-channel TV Sound (MTS) options: Stereo, Auto SAP (Second Audio Program), and Mono. The MTS setting can be also accessed in the Audio setting. For more details, see "Selecting Audio Options" on page 66.
21 FREEZE	Press to freeze the current picture. Press again to restore the picture. For details, see "Using the FREEZE Button" on page 54.
22 TV/SAT/SUR	TV/SAT: While in SAT/CABLE FUNCTION, press to switch between the satellite receiver and antenna. SUR: Press SUR (Surround Sound) repeatedly to step through the available audio effect models: TruSurround XT, Simulated, Off.
23 WIDE	Press repeatedly to step through the Wide Screen Mode setting: Wide Zoom, Normal, Full and Zoom. The Wide Screen Mode setting can be also accessed in the Screen setting. For details, see "Using the WIDE Button" on page 53.
24 DISPLAY	Press once to display channel number, label, current time and other information. Press again to turn Display off. See page 83 for details on setting the time.
25 ↑/↓/←/→ ⊕	Press ↑/↓/←/→ to move the on-screen cursor. To select an item, press ⊕.
26 TOOLS	To be used only with your connected external equipment that supports this TOOLS function. (Non-operable button for TV)
27 WEGA GATE	Press to access the following through the WEGA GATE: • Watch TV (see page 58) • Select channels from the Favorites Channels you stored (see page 57) • View signals from external equipment such as DVD, VCR and others (see page 59). • Adjust or customize TV settings (see Using the Settings on page 59).
28 CH +/–	Press to scan through channels. To scan quickly through channels, press and hold down either +/– button.

(Continued)

Button	Description
29 F1	Press to select the function of connected components. For details, see “Using Other Equipment with Your Remote Control” on page 49.
30 F2	Press to select the function of connected components. For details, see “Using Other Equipment with Your Remote Control” on page 49.

Programming the Remote Control



The remote control is preset to operate Sony brand video equipment.

Sony Equipment	Programmable Code Number
DVR	772
DVD/VCR	601 (Sony Dream System)
SAT/CABLE	801 (Sony Satellite Receiver)

Follow the steps below to program your TV's remote control to operate the non-Sony video equipment.

Find the three-digit code for your equipment from the "Manufacturer's Codes" listed on page 48. If more than one code number is listed, try entering from the code listed first.

1 Press and hold the DVR, DVD/VCR or SAT/CABLE FUNCTION button you want to program on the remote control and press the DISPLAY button simultaneously.

The selected FUNCTION button (DVR, DVD/VCR or SAT/CABLE) will flash.

2 Enter the three-digit manufacturer's code number using the ⓪-⑨ buttons while the button is lit. If code is not entered within 10 seconds, you must perform step 1 again.

3 Press ENT button.

When the programming is correct, the selected FUNCTION button will flash twice, and when not, flashes five times.

To check if the code works

Aim your TV's remote control at the equipment, and press the green POWER button. If the equipment turns on and off, the programming is completed. If not, try the next code listed.

If no code is input within the above specified time, or an invalid or incorrect code number is input, the remote control automatically goes back to the previous setting.

In some cases, you may not be able to program your remote control to operate other equipment. In such cases, use the equipment's own remote control.

Using dead batteries or removing the batteries may cause the programmable codes to be lost and revert back to factory settings. Reprogramming the codes may be necessary.

Manufacturer's Codes

DVD Players

Manufacturer	Code
Sony	751
General Electric	755
Hitachi	758
JVC	756
Magnavox	757
Mitsubishi	761
Panasonic	753
Philips	757
Pioneer	752, 778
RCA/PROSCAN	755
Samsung	758
Toshiba	754
Zenith	760

DVD Changers

Manufacturer	Code
Sony	765
Panasonic	766

DVD/VCR Combo Units

Manufacturer	Code
Sony	767
Broksonic	776
JVC	775
Panasonic	777
Samsung	774
Toshiba	773
Zenith	768

HDD/DVD Combo Units

Manufacturer	Code
Sony	772, 771, 770

5.1ch DVD AV System

Manufacturer	Code
Sony (DAV)	601, 602, 603, 604

AV Receivers

Manufacturer	Code
Sony	764

VCRs

Manufacturer	Code
Sony	301, 302, 303
Admiral (M. Ward)	327
Aiwa*	338, 344
Audio Dynamic	314, 337
Broksonic	319, 317
Canon	309, 308
Citizen	332
Craig	302, 332
Curtis Mathes	304, 338, 309
Daewoo	341, 312, 309
DBX	314, 336, 337
Dimensia	304
Emerson	319, 320, 316, 317, 318, 341
Fisher	330, 335
Funai	338
General Electric	329, 304, 309
Go Video	322, 339, 340
Goldstar	332
Hitachi	306, 304, 305, 338
Instant Replay	309, 308
JC Penney	309, 305, 304, 330, 314, 336, 337
JVC	314, 336, 337, 345, 346, 347
Kenwood	314, 336, 332, 337
LG	332
LXI (SEARS)	332, 305, 330, 335, 338
Magnavox	308, 309, 310
Marantz	314, 336, 337
Marta	332
Memorex	309, 335
Minolta	305, 304
Mitsubishi/MGA	323, 324, 325, 326
Multitech	325, 338, 321
NEC	314, 336, 337
Olympic	309, 308
Optimus	327
Orion	317
Panasonic	308, 309, 306, 307
Pentax	305, 304
Philco	308, 309
Philips	308, 309, 310
Pioneer	308
Quasar	308, 309, 306
RCA/PROSCAN	304, 305, 308, 309, 311, 312, 313, 310, 329
Realistic	309, 330, 328, 335, 324, 338
Sansui	314
Samsung	322, 313, 321
Sanyo	330, 335
Scott	312, 313, 321, 335, 323, 324, 325, 326
Sharp	327, 328
Signature 2000 (M. Ward)	338, 327
SV2000	338
Sylvania	308, 309, 338, 310
Symphonic	338
Tashiro	332
Tatung	314, 336, 337
Teac	314, 336, 338, 337
Technics	309, 308
Toshiba	312, 311
Wards	327, 328, 335, 331, 332
Yamaha	314, 330, 336, 337
Zenith	331

Cable Boxes

Manufacturer	Code
Sony	230
Hamlin/Regal	222, 223, 224, 225, 226
Jerrold/ General Inst./ Motorola	201, 202, 203, 204, 205, 206, 207, 208, 218, 222
Oak	227, 228, 229
Panasonic	219, 220, 221
Pioneer	211, 214, 215
Scientific Atlanta	209, 210, 211
Tocom	216, 217
Zenith	212, 213

Satellite Receivers

Manufacturer	Code
Sony	801
Dish Network	810
Echostar	810
General Electric	802
Hitachi	805
Hughes	804
Mitsubishi	809
Panasonic	803
Philips	811
RCA/PROSCAN	802, 808
Toshiba	806, 807
Samsung	812

* If an Aiwa VCR does not work even though you enter the code for Aiwa, enter the code for Sony instead.

Using Other Equipment with Your Remote Control

To operate other equipment connected to your TV, first turn to page 48 and program the necessary code. For operating video equipment, press TV/VIDEO repeatedly until you see the video input on the screen for your connected equipment. Remote control tips are provided below.

✍ **Some functions cannot be operated depending on the equipment. In that case, operate by the remote control supplied with the equipment.**

Operating a Cable Box

To Do This ...	Press ...
Activate the remote control to operate the cable box	SAT/CABLE (FUNCTION)
Turn on/off	POWER
Select a channel	0-9, ENT
Change channels	CH +/–
Back to previous channel	JUMP

Operating a Satellite Receiver

To Do This ...	Press ...
Activate the remote control to operate the satellite receiver	SAT/CABLE (FUNCTION)
Turn on/off	POWER
Select a channel	0-9, ENT
Change channels	CH +/–
Back to previous channel	JUMP
Display channel number	DISPLAY
Display SAT Guide	GUIDE
Display SAT Menu	MENU
Move highlight (cursor)	↑ ↓ ← →
Select item	⊕
Switch between the TV and satellite broadcasts	TV/SAT

Operating a VCR

To Do This ...	Press ...
Activate the remote control to operate the VCR	DVD/VCR (FUNCTION)
Turn on/off	POWER
Change channels	CH +/–
Record	●
Play	▷
Stop	■
Fast forward	▶▶
Rewind the tape	◀◀
Pause	❚❚ (press again to resume normal playback)
Search the picture forward or backward	▶▶ or ◀◀ during playback (release to resume normal playback)

Operating a DVD Player or DVD Changer

To Do This ...	Press ...
Activate the remote control to operate the DVD	DVD/VCR (FUNCTION)
Turn on/off	POWER
If you have a DVD changer, to skip disc	F1
Play	▷
Stop	■
Pause	❚❚ (press again to resume normal playback)
Step through different tracks of the disc	◀◀ to fast reverse or ▶▶ to fast forward the disc when pressed during playback
Step through different chapters of the disc	▶▶I to step forward or I◀◀ to step backward
Select a track directly	0-9, ENT
Display the disc menu	MENU
Display the top menu	TOP MENU
Operate the DVD menu	↑ ↓ ← →, ⊕

(Continued)

Operating a 5.1ch DVD AV System (Sony DAV)

To Do This ...	Press ...
Activate the remote control to operate the DVD	DVD/VCR (FUNCTION)
Turn on/off	POWER
Select other equipment connected to the DAV	F1
Disk skip	F2
Display the top menu	TOP MENU
Display the disc menu	MENU

To Do This ...	Press ...
Play	▷
Stop	■
Pause	❚❚
Search the picture forward or backward	▶▶ or ◀◀ during playback
Specify the previous chapter/track Specify the next chapter/track	⏮ ⏭
Move highlight (cursor)	↑ ↓ ← →
Select item	⊕
Master volume	VOL +/–, MUTING

Operating a DVD/VCR Combo Unit

To Do This ...	Press ...
Activate the remote control to operate the DVD/VCR	DVD/VCR (FUNCTION)
Turn on/off	POWER
Select the DVD Select the VCR	F 1 F 2
Display the top menu	TOP MENU
Display the disc menu	MENU
Play	▷
Stop	■
Pause	❚❚

To Do This ...	Press ...
Search the picture forward or backward	▶▶ or ◀◀ during playback
Replay	←•
Advance	•→
Move highlight (cursor) and select (DVD)	↑ ↓ ← → ⊕
Record (VCR)	●
Change channels (VCR)	CH +/– or 0-9, ENT (using tuner)
Adjust tracking (VCR)	CH +/– (during tape playback)

Operating a HDD/DVD Combo Unit

To Do This ...	Press ...
Activate the remote control to operate the DVD/HDD	DVR (FUNCTION)
Turn on/off	POWER
Select the HDD Select the DVD	F 1 F 2
Play	▷
Stop	■
Pause	❚❚
Search the picture forward or backward	▶▶ or ◀◀ during playback

To Do This ...	Press ...
Move highlight (cursor) and select	↑ ↓ ← → ⊕
Record	●
Specify the previous chapter/track Specify the next chapter/track	⏮ ⏭
Replay	←•
Advance	•→
Display the disc menu	MENU
Display the top menu	TOP MENU

Operating an AV Receiver

To Do This ...	Press ...
Turn on/off	POWER
Master volume	VOL +/–, MUTING
Select other input connected to AV receiver	F1

Special Buttons on the Remote Control

This TV comes with convenient features that can be accessed directly by pressing their buttons on your remote control.

Using the GUIDE Button

This TV is equipped to show program information if it is available from the station. The Program Guide lets you review program information, and select both analog and digital channels.

To display the Program Guide:

1. Tune your TV to a channel by using the 0-9, ·, and ENT buttons.
2. Press GUIDE on the TV's remote control. The Program Guide will appear with the currently selected program showing in the background.



✍ **Program information in the guide is provided by the broadcasters. As a result, it may sometimes include only the channel number, without a program title or description.**

(Continued)

Using the Program Guide

The Program Guide allows you to select the channels from a drop down list. The Guide also provides information about the current program being shown on each channel.



✍ **Subchannels are additional channels of programming broadcast simultaneously. For example, channel 4 might include three subchannels (4.1, 4.2, 4.3) that are showing programs at the same time.**

Using the Program Options Setting

The Program Options setting allows you to customize the program settings on the currently tuned channel.

Option	*Description*
Alternate Video (When available)	Each program has a main video stream (the video that you see when the channel is first tuned), and may have alternate video streams. This option allows you to switch among these alternate video streams.
Alternate Audio (When available)	Each program has a main audio stream (the audio you hear when the channel is first tuned), and may have alternate audio streams. This option allows you to switch among these alternate audio streams (e.g., for different languages).

Using the WIDE Button

Wide screen mode lets you watch 4:3 normal broadcasts in several wide screen modes (16:9 aspect ratio).



When the TV receives a 720p or 1080i signal that is 4:3 aspect ratio picture with a black bar at each side, Full returns the picture to its original size.

You can also access the Wide Mode settings in the Screen settings. For details, see page 69.

When the TV receives a 720p or 1080i signal, Normal cannot be selected.

Changing the wide screen mode



Using the JUMP Button

The JUMP button allows you to jump back and forth between the current channel and the last channel that was selected.

Using the FREEZE Button

The FREEZE button allows you to temporarily capture a program's picture. You can use this feature to write down information such as phone numbers, recipes, etc.
To cancel FREEZE and return to normal viewing, press the FREEZE button again.

Introducing WEGA GATE

Overview of WEGA GATE

WEGA GATE provides one button access for controlling your TV. It enables you to perform a variety of tasks intuitively with a control panel on the screen rather than a variety of remote control button presses. When you press the WEGA GATE button, you can select from basic TV function: selecting from Favorite Channels, watching TV, viewing external equipment signals or adjusting TV settings.



1 Press WEGA GATE on the remote.
WEGA GATE control panel appears.



2 Press ↑/↓ to highlight the item.

3 Press ⊕ to select.

4 Press WEGA GATE to exit.

The WEGA GATE screen gives you access to the following items:

Icon	*Description*
Favorites	The Favorites feature lets you select programs from a list of up to 16 favorite channels that you specify. For details, see page 57.
Cable	The Cable feature takes you to the most recently viewed channel on the cable input. When tuned to the channel, the Program Banner and Channel number will be displayed. When this feature is active, ○ is displayed to the left of the icon.
 Antenna	The Antenna feature takes you to the most recently viewed channel on the antenna input. When tuned to the channel, the Program Banner and Channel number will be displayed. When this feature is active, ○ is displayed to the left of the icon.
 External Inputs	The External Inputs feature lets you select equipment that is connected to your TV, such as a DVD player. You can assign a label to your equipment or skip unused inputs conveniently. For details, see page 59. When this feature is active, ○ is displayed to the left of the icon.
Settings	The Settings feature lets you adjust the Video, Audio, Screen, Channel, Parental Lock, Setup or Applications settings. For details, see page 59.

Navigating and Selecting Items

Use your remote control to navigate through WEGA GATE and the settings.

To Do This ...	Press ...
Display WEGA GATE control panel	Press WEGA GATE.
Display Settings	Press WEGA GATE and select Settings.
Move through Settings	Press ↑ ↓ ← →.
Select an option to change	Press ⊕.
Move back to upper layer	Press RETURN.
Select (confirm) changed setting	Press ⊕.
Exit WEGA GATE control panel or Settings	Press WEGA GATE.

Using Favorites in WEGA GATE

The Favorites feature lets you select programs from a list of up to 16 favorite channels that you specify. You can create a list using the Add to Favorites option.

1 Select Favorites from the WEGA GATE control panel and press ⊕.

The Favorite Channels list appears. Make your selection.



2 Press ↑/↓ to highlight the desired channel and press ⊕.

- To add the current channel to the list of Favorite Channels, highlight Add to Favorites and press ⊕.
- When the Favorite Channels list is full, select Edit Favorites to remove a channel from the list or go to the Channel settings and select Favorite Channels then edit the channel.

Using Cable in WEGA GATE

The Cable feature takes you to the most recently viewed channel on the cable input. When tuned to the channel, the Program Banner and Channel number will be displayed.
Select Cable from the WEGA GATE control panel and press ⊕.



✍ **If you have not completed the initial channel setup (see page 32) both Cable and Antenna will tune to the lowest channel number. To run Initial Setup see page 72.**

Using Antenna in WEGA GATE

The Antenna feature takes you to the most recently viewed channel on the antenna input. When tuned to the channel, the Program Banner and Channel number will be displayed.
Select Antenna from the WEGA GATE control panel and press ⊕.



✍ **If you have not completed the initial channel setup (see page 32) both Cable and Antenna will tune to the lowest channel number. To run Initial Setup see page 72.**

Using External Inputs in WEGA GATE

The External Inputs feature lets you view from a selected external input connected to your TV. You can assign a label or skip over unused inputs by selecting Edit Video Labels. Input label assignment can also be done by going to Setup settings and select Label Video Inputs (see page 79).

1 Select External Inputs from the WEGA GATE control panel and press ⊕.

The External Inputs list appears. Make your selection.



2 Press ↑/↓ to highlight the desired external input and press ⊕.

Using Settings in WEGA GATE

The Settings feature lets you enter to the settings screen where most of advanced settings and adjustments are performed. See “Overview ” on page 61.

Using the Settings

Overview

The Settings give you access to the following features:
(Depending on the signal tuned, you may see a different Setting options on your screen. Settings displayed here are with the 720p signal.)

Settings	*Allows you to set/change*	
Video	Picture Mode (page 63)	DRC Mode (page 64)
	Reset (page 63)	DRC Palette (page 64)
	Iris (page 63)	Advanced Video (page 65)
	Picture (page 63)	
	Brightness (page 63)	
	Color (page 63)	
	Hue (page 63)	
	Color Temp. (page 64)	
	Sharpness (page 64)	
	Noise Reduction (page 64)	
Audio	Sound Mode (page 66)	MTS (page 67)
	Reset (page 66)	Speaker (page 67)
	Treble (page 66)	Audio Out (page 67)
	Bass (page 66)	A/V Sync (page 67)
	Balance (page 66)	
	Steady Sound (page 66)	
	Volume Offset (page 66)	
	Effect (page 66)	
	BBE (page 66)	
Screen	Wide Mode (page 69)	
	Game Picture (page 69)	
	4:3 Default (page 70)	
	Display Area (page 70)	
	Vertical Center (page 70)	
	Vertical Size (page 70)	

(Continued)

Settings	*Allows you to set/change*
Channel 	Favorite Channels (page 72) Digital Channels (page 72) Auto Program (page 72) Show/Hide Channels (page 72) Label Channels (page 73)
Parental Lock 	Parental Lock (page 74) Change Password (page 75) Select Country (page 75)
Setup 	Caption Vision (page 78) Info Banner (page 78) Game Mode (page 78) Label Video Inputs (page 79) Language (page 79) Video 2 (Component) (page 79) Menu Color (page 79) Image Shift (page 79) High Altitude (page 80) CineMotion (page 80)
Applications 	Clock/Timers (page 83) Diagnostics (page 84) CableCARD (page 84)

Accessing the Video Settings

1. Press WEGA GATE.....

2. Select Settings.....

3. Highlight.....

4. Press to select.....

To highlight an option and to change settings, press ↑ ↓ ← →.
Press ⊕ to confirm the selection.
To exit the Video, press WEGA GATE.

Selecting Video Options

To quickly and easily change from one Picture Mode to another, use PICTURE on the remote control.

The Video settings include the following options:

Option	Description	
Picture Mode *Customized picture viewing*	Vivid	Select for enhanced picture contrast and sharpness.
	Standard	Select for standard picture settings. Recommended for home entertainment.
	Custom	Select to display a picture with minimum enhancements.
	✍ **You can alter the Video settings (Picture, Brightness, Color, etc.) for each Mode and each video input.**	
	✍ **You may set up a "Mode" (Vivid, Standard, Custom) independently for each Video input (Video 1-Video 6, including the Antenna input). Your "Mode" settings are automatically saved after each selection. This allows you to customize the Mode setting for each type of signal source.**	
Reset	Select OK to reset all settings and adjustments to the default setting (except for Advanced Video).	
Iris	Adjust the contrast levels.	
Picture	Adjust to increase picture contrast and deepen the color or decrease picture contrast and soften the color.	
Brightness	Adjust to brighten or darken the picture.	
Color	Adjust to increase or decrease color intensity.	
Hue	Adjust to increase or decrease the green tones.	

(Continued)

Option	*Description*	
Color Temp. *White intensity adjustment*	Choose from four color temperatures:	
	Cool	Select to give the white colors a blue tint.
	Neutral	Select to give the white colors a neutral tint.
	Warm 1, 2	When selected Custom in Picture Mode, select to give the white colors a red tint.
Sharpness	Adjust to sharpen or soften the picture.	
Noise Reduction	Select to reduce the noise level of connected equipment. This also reduces the noise level to the signal from the VHF/UHF jack. Select from Auto, High, Medium, Low and Off.	
	✍ **When ATSC or Component is in use, Auto is not available.**	
DRC Mode	High Density	Creates a high-resolution picture with 4 x density, for high quality sources (i.e., DVD player, satellite receiver).
	Progressive	Recommended for moving pictures.
	Off	
	✍ **DRC Mode is not available when Game Mode is On or using the Freeze feature; also not available when watching 480p, 720p or 1080i sources.**	
DRC Palette	Custom	Allows you to customize the level of detail (Reality) and smoothness (Clarity) for up to three input sources. For example, you can create one Custom setting to optimize your cable input's picture, and create another to optimize your DVD player's picture. You can switch among the three Custom settings. **1** Press the arrow buttons to highlight Custom then press ⊕. The DRC palette appears.  **2** Press the arrow buttons to adjust the position of the marker (●). As you move the ● higher along the Reality axis, the picture becomes more detailed. As you move the ● to the right along the Clarity axis, the picture becomes smoother. **3** To save the setting, press ⊕.
	✍ **DRC Palette is not available when Game Mode is On, Noise Reduction is set to Auto, DRC Mode is Off or using the Freeze feature; also not available when watching 480p, 720p or 1080i sources.**	

Option	Description	
Advanced Video *Available in "Custom Picture Mode"*	Program	Select Program to choose among the options: Black Corrector (High/Medium/Low/Off), Advanced Iris (High/Medium/Low/Off), Gamma (Max/High/Medium/Low/Off), Clear White (High/Low/Off), Live Color (High/Medium/Low/Off).

Selecting PC Video Options

To display the PC screen:

Press TV/VIDEO repeatedly on the remote control until VIDEO 7 (PC) appears.



✍ **You can change the settings for the PC input while the TV is displaying the PC screen.**

The PC Input Video setting includes the following options:

Option	Description	
Display Mode	Video	Select to view video images.
	Text	Select to view text, charts or tables.
Reset	Select to restore the factory default settings.	
Iris	Select to adjust the contrast levels.	
Picture	Adjust to increase or decrease picture contrast.	
Brightness	Adjust to brighten or darken the picture.	
Color Temp.	Choose from four color temperatures:	
	Cool	Select to give the white colors a blue tint.
	Neutral	Select to give the white colors a neutral tint.
	Warm 1, 2	Select to give the white colors a red tint.

Accessing the Audio Settings

1. Press WEGA GATE.....

2. Select Settings.....

3. Highlight.....

4. Press to select.....



To highlight an option and to change settings, press ↑ ↓ ← →.
Press ⊕ to confirm the selection.
To exit the Audio, press WEGA GATE.

Selecting Audio Options

- Sound Mode settings are independent of settings in the Treble/Bass options.
- TruSurround XT attempts to create the same surround effect produced by a multichannel system using the left and right speakers.

The Audio settings include the following options:

Option	*Description*	
Sound Mode	Dynamic	Select to enhance treble and bass.
	Standard	Suitable for spoken dialog.
	Custom	Flat setting.
Reset	Reset the following options to the default setting: Treble, Bass, Balance, Steady Sound, Volume Offset, Effect and BBE.	
Treble	Adjust to increase or decrease higher-pitched sounds.	
Bass	Adjust to increase or decrease lower-pitched sounds.	
Balance	Adjust to emphasize left or right speaker balance.	
Steady Sound	On	Select to stabilize the volume across all programs and commercials.
	Off	Select to turn off Steady Sound.
Volume Offset	Adjust to increase or decrease the sound level of the current input (TV or video input) relative to other inputs.	
Effect	TruSurround XT	Select for surround sound (for stereo programs only).
	Simulated	Adds a surround-like effect to mono programs.
	✍ **Simulated uses SRS 3D MONO.**	
	Off	Normal stereo or mono reception.
BBE	Select to give sound more impact by compensating for phase effects in speakers. Select from High, Low, and Off.	

Option	Description	
MTS *Enjoy stereo, bilingual and mono programs*	Stereo	Select for stereo reception when viewing a program broadcast in stereo.
	Auto SAP	Select to automatically switch to second audio programs when a signal is received. (If no SAP signal is present, the TV remains in Stereo mode.)
	Mono	Select for mono reception. (Use to reduce noise during weak stereo broadcasts.)
	✍ **MTS is available only for analog programs.**	
Speaker	On	Select to turn on the TV speakers.
	Off	Select to turn off the TV speakers and listen to the TV's sound only through your external audio system speakers.
	✍ **The MUTING button on your remote control is available when Audio Out is set to Variable, and becomes nonfunctional when set to Fixed.**	
Audio Out	This option can be set only when the Speaker option is set to Off.	
Easy control of volume adjustments	Variable	The TV's speakers are turned off and the audio output from your audio system can still be controlled by the TV's remote control.
	Fixed	The TV's speakers are turned off, and the audio output of the TV is fixed. Use your audio receiver's volume control to adjust the volume (and other settings) through your audio system.
A/V Sync	Off/1/2/3	Use this option to make adjustments to audio and video synchronization when you have external equipment connected to DIGITAL AUDIO (OPTICAL) OUT of the TV. Select Off (factory default setting) to make no adjustments. Select 1, 2 or 3 to adjust so that the video and audio from your connected external equipment are in synchronized.

Selecting PC Audio Options

To display the PC screen:

Press TV/VIDEO repeatedly on the remote control until VIDEO 7 (PC) appears.



✍ **You can change the settings for the PC input while the TV is displaying the PC screen.**

The PC Input Audio setting includes the following options:

Option	*Description*	
Sound Mode	Dynamic	Select to enhance treble and bass.
	Standard	Suitable for spoken dialog.
	Custom	Flat setting.
Reset	Select to restore the factory default settings.	
Treble	Adjust to increase or decrease higher-pitched sounds.	
Bass	Adjust to increase or decrease lower-pitched sounds.	
Balance	Adjust to emphasize left or right speaker balance.	
Effect	TruSurround XT	Select for surround sound (for stereo programs only).
	Simulated	Adds a surround-like effect to mono programs.
	Off	Normal stereo or mono reception.
Speaker	On	Select to turn on the TV speakers.
	Off	Select to turn off the TV speakers and listen to the TV's sound only through your external audio system speakers.
Audio Out	This option can be set only when the Speaker option is set to Off.	
Easy control of volume adjustments	Variable	The TV's speakers are turned off, but the audio output from your audio system can still be controlled by the TV's remote control.
	Fixed	The TV's speakers are turned off and the audio output of the TV is fixed. Use your audio receiver's volume control to adjust the volume (and other settings) through your audio system.

Accessing the Screen Settings

1. Press WEGA GATE.....

2. Select Settings.....

3. Highlight.....

4. Press to select.....



To highlight an option and to change settings, press ↑ ↓ ← →.
Press ⊕ to confirm the selection.
To exit the Screen, press WEGA GATE.

Selecting Screen Options

Wide Mode is unavailable while in Freeze (page 54).

The Screen settings include the following options:

Option	Description	
Wide Mode *Select a screen mode to use for 4:3 sources.*	Wide Zoom	Select to enlarge the 4:3 picture, to fill the 16:9 screen, keeping the original image as much as possible.
	Normal	Select to return the 4:3 picture to its original size and aspect ratio.
	✍ **Normal is not available when you are watching 720p or 1080i sources.**	
	Full	Select to enlarge the 4:3 picture horizontally only, to fill the display area.
	Zoom	Select to proportionally enlarge 1080i and 720p sources, For 480p and 480i sources, Zoom will vertically stretch the image to fill the screen.
✍ **To change from one Wide Mode setting to another, use the WIDE button on the remote control (see page 53).**		
Game Picture	Allows you to move the position of the picture left and right in the window. (This feature also allows you to adjust the picture from any connected equipment.) Select while watching the picture to be adjusted. The TV stores the position in memory for each input. Press ← or → and press ⊕ to choose a correction between +5 and –5.	
✍ **Not available in Full and Normal mode when sources are in 720p or 1080i.**		

(Continued)

If 4:3 Default is set to anything but Off, the Wide Mode setting changes only for the current channel. When you change channels (or inputs), Wide Mode is automatically replaced with the 4:3 Default setting. To retain the current Wide Mode setting as channels and inputs are changed, set 4:3 Default to Off.

Option	*Description*	
4:3 Default *Select the default screen mode to use for 4:3 sources.*	Wide Zoom	Select to enlarge the 4:3 picture, to fill the 16:9 screen, keeping the original image as much as possible.
	Normal	Select to return the 4:3 picture to normal mode.
	Full	Select to enlarge the 4:3 picture horizontally only, to fill the display area.
	Zoom	Select to enlarge the picture horizontally and vertically to an equal aspect ratio that fills the wide screen.
	Off	Select to continue using the current screen mode setting when the channel or input is changed.
Display Area	Select Normal to return to the default display area. Select -1 or -2 to keep the edge of the picture out of screen.	
Vertical Center	Allows you to move the position of the picture up and down in the window. (Available only in Zoom mode.) Press ↑ or ↓ and press ⊕ to choose a correction between +5 and –5.	
Vertical Size	Allows you to adjust the vertical size of the picture. (Available only in Zoom mode.) Press ↑ or ↓ and press ⊕ to choose a correction between +5 and –5.	

Selecting PC Screen Options

When there is no signal input, all settings are not available.

To display the PC screen:

Press TV/VIDEO repeatedly on the remote control until VIDEO 7 (PC) appears.



✍ **You can change the settings for the PC input while the TV is displaying the PC screen.**

The PC Input Screen setting includes the following options:

Select Zoom in the Wide Mode option to display movies and other content on DVD, using the entire viewable area of the screen.

Option	*Description*	
Wide Mode	Normal	Select to display the picture in its original size.
	Full 1	Select to enlarge the picture to fill the display area, keeping its original horizontal-to-vertical ratio.
	✍ **A black frame will appear on the surrounding of the picture.**	
	Full 2	Select to enlarge the picture to fill the display area.
	✍ **A black frame will appear on the surrounding of the picture.**	
	Zoom	Select to enlarge the picture horizontally and vertically to an equal aspect ratio that fills the wide screen.
Auto Adjustment	Select to automatically adjust the display position of the picture when the TV receives an input signal from the connected PC. Note that Auto Adjustment may not work well with certain input signals. In such cases, manually adjust the options below.	
Phase	Select to adjust the phase when the screen flickers.	
Pitch	Select to adjust the pitch when the picture has unwanted vertical stripes.	
Horizontal Center	Select to adjust the horizontal position of the picture. Allows you to move the picture left and right in the window. Press ← or → and press ⊕ to choose a correction between +50 and -50.	
	✍ **The variable range depends on the signal.**	
Vertical Center	Select to adjust the vertical position of the picture. Allows you to move the picture up and down in the window. Press ← or → and press ⊕ to choose a correction between +50 and -50.	
	✍ **The variable range depends on the signal.**	

Accessing the Channel Settings

1. Press WEGA GATE.....

2. Select Settings.....

3. Highlight.....

4. Press to select.....

To highlight an option and to change settings, press ↑ ↓ ← →.
Press ⊕ to confirm the selection.
To exit the Channel, press WEGA GATE.

Selecting Channel Options

The Channel settings include the following options:

Option	*Description*
Favorite Channels	Lets you set up a list of your favorite channels. For details, see "Using Favorites in WEGA GATE" on page 57.
Digital Channels	Add Select to add digital channels.
Auto Program	Automatically sets up the channel list on the TV for all receivable channels for the current input (VHF/UHF or CABLE). Select to start the Auto Program. ✍ **Auto Program may take up to 20 to 50 minutes to complete. A progress bar will display the approximate progress of the Auto Program and Digital Channels/Add sequences.**
Show/Hide Channels	Allows you to show or hide channels that appear in the Program Guide and when you use the CH+/- buttons to channel surf. Channels that are set to Hidden do not appear in the Program Guide or when you use the CH+/- buttons. **1** Press ↑ or ↓ to highlight the channel that you want to show or hide. To move between the Major and Digital subchannel lists, press ← or →. **2** To change a channel's setting to Shown or Hidden, press ⊕. **3** To show or hide more channels, repeat steps 1 and 2.

Channels that you set to Hidden can only be accessed with the 0-9 buttons.

Option	Description
✍ **If you select to hide or show a major digital channel, all the sub-channels are automatically hidden or shown. To show or hide an individual sub-channel within a digital channel, you must individually select that sub-channel to show or hide.**	
✍ **If you hide all sub-channels of a major digital channel, that digital channel is automatically set to Hidden.**	
Label Channels	Allows you to assign labels (such as station call letters) to channel numbers. **1** Press ↑ or ↓ to scroll through the channel numbers. Then press ⊕ to select the channel number that you want to assign a label. **2** Press ↑ or ↓ to scroll through the label characters (A-Z, 0-9, etc.). Then press ⊕ to select the highlighted character. Repeat to add characters to the label. **3** Press ← to return to the Channel setting, or press WEGA GATE to exit the settings.

Accessing the Parental Lock Settings

1. Press WEGA GATE.....

2. Select Settings.....

3. Highlight.....

4. Press to select.....



To highlight an option and to change settings, press ↑ ↓ ← →.
Press ⊕ to confirm the selection.
To exit the Parental Lock, press WEGA GATE.
The Parental setting allows you to set up the TV to block programs according to their content and rating levels.

✍ **You need your password for any future access to the Parental Lock settings. If you have lost your password, see "Lost password" on page 93.**

Selecting Parental Lock Options

The Parental Lock settings include the following options:

Option	*Description*	
Parental Lock *Turn ratings on/off and select a rating system*	Off	Turn Parental Lock off. No programs are blocked from viewing.
	Child	Maximum ratings permitted are: U.S.: TV-Y, TV-G, G Canada: C, G, TV-Y
	Youth	Maximum ratings permitted are: U.S.: TV-PG, PG Canada: C8+, PG, 8 ans+, TV-PG
	Y. Adult	Maximum ratings permitted are: U.S.: TV-14, PG-13 Canada: 14+, 13 ans+, TV-14
	Custom	Select to set ratings manually. U.S.: See page 76 for details. Canada: See page 77 for details.

If you are not familiar with the Parental Guideline rating system, you should select Child, Youth, or Y.Adult to help simplify the rating selection. To set more restrictive ratings, select Custom.

For descriptions of Child, Youth, and Y.Adult ratings, see page 74.

Option	Description	
Change Password	Select to change your password.	
Select Country	U.S.A.	Select to use USA ratings (see page 76).
	Canada	Select to use Canadian ratings (see page 77).

To deactivate the parental control feature

❑ Set Parental Lock to OFF when in the Parental Lock setting.

To change the password

1 In the Parental Lock setting, use the arrow buttons to highlight Change Password, and press ⊕ to select it.

2 Enter a new four-digit password using the 0-9 buttons.

3 Confirm the new password by entering it again.

4 Press WEGA GATE to exit the setting screen.

Viewing Blocked Programs

You can view a blocked program by entering the password.

1 Press ENT when tuned to a blocked program.

2 Enter your password using the 0-9 buttons.
Parental control will be canceled temporarily until you turn your TV off.

Selecting Custom Rating Options

To ensure maximum blocking capability, the age-based ratings should be blocked.

If you select Block, be aware that the following programs may be blocked: news, sports, weather, emergency broadcasts, political programs, public service announcements, and religious programs.

US custom rating options

If you selected U.S.A. as the country of residence on page 75, the Custom Rating setting includes the following options. (If you selected Canada, see page 77.)

Option	*Description*	
Movie Rating	G	All children and general audiences.
	PG	Parental guidance suggested.
	PG-13	Parental guidance for children under 13.
	R	Restricted viewing, parental guidance is suggested for children under 17.
	NC-17 and X	No one 17 and under.
TV Rating *Block programs by their rating, content or both*	Age-Based Options	
	TV-Y	All children.
	TV-Y7	Directed to children age 7 and older.
	TV-G	General audience.
	TV-PG	Parental guidance suggested.
	TV-14	Parents strongly cautioned.
	TV-MA	Mature audience only.
	Content-Based Options	
	FV	Fantasy violence.
	D	Suggestive dialog.
	L	Strong language.
	S	Sexual situations.
	V	Violence.
Unrated *Block programs or movies that are broadcast without a rating*	Allow	Allows programs and movies that are broadcast without a rating.
	Block	Blocks all programs and movies that are broadcast without a rating.

✍ **The content ratings will increase depending on the level of the age-based rating. For example, a program with a TV-PG V (Violence) rating may contain moderate violence, while a TV-14 V (Violence) rating may contain more intense violence.**

Canadian custom rating options

If you selected Canada as the country of residence on page 75, the Custom Rating setting includes the following options. (If you selected U.S.A., see page 76.)

Option	*Description*	
English Rating	C	All children.
	C8+	Children 8 years and older.
	G	General programming.
	PG	Parental guidance.
	14+	Viewers 14 and older.
	18+	Adult programming.
French Rating	G	General programming.
	8 ans+	Not recommended for ages under 8.
	13 ans+	Not recommended for ages under 13.
	16 ans+	Not recommended for ages under 16.
	18 ans+	Programming restricted to adults.
U.S.A. Rating	See "TV Rating" on page 76 for details.	

Accessing the Setup Settings

1. Press WEGA GATE.....

2. Select Settings.....

3. Highlight.....

4. Press to select.....



To highlight an option and to change settings, press ↑ ↓ ← →.
Press ⊕ to confirm the selection.
To exit the Setup, press WEGA GATE.

Selecting Setup Options

The Setup settings include the following options:

Option	*Description*	
Caption Vision	Allows you to select from four closed caption modes (for programs that are broadcast with closed captioning).	
	On	Caption Vision is turned on.
	Off	Caption Vision is turned off.
	Program	Allows you to set basic and advanced Caption Vision options. See "Programming Caption Vision" on page 80.
Info Banner	Set to On or Off. Select On to display the program name, time remaining and other information (if the broadcaster offers this service). Also displays when the channel is changed or the DISPLAY button is pressed.	
Game Mode	On	Select to optimize the lipsync when playing games.
	Off	Select to turn off the Game Mode.

Option	*Description*	
Label Video Inputs	Allows you to label the audio/video equipment you have connected to the TV so you can identify them when using TV/VIDEO. When in this setting: **1** Press ↑ or ↓ to highlight an input to label, then press ⊕ to select it. **2** Use the arrow buttons to scroll through the labels. **3** Press ⊕ to select the equipment you connected to each of the input jacks on the back of your TV. Select Skip if you do not have any equipment connected to a particular input.	
	Video 1-6	Video 1-6, VHS, DVD, Receiver, Satellite, Cable Box, 8mm, DTV, Game, LD, Beta, HD, DVR, Camcorder, Skip
	Video 7	Video 7, PC, DVD, HD, Game, Skip
	✍ **If you select Skip, your TV skips the selected connection when you press TV/VIDEO.**	
Language	Select to display all on-screen settings in your language of choice: English, Español, Français.	
Video 2 (Component)	Auto	Select to switch automatically between the component video jacks (Y P_B/C_B P_R/C_R, AUDIO L (MONO)/AUDIO R) and the composite video jacks (VIDEO, AUDIO L (MONO)/AUDIO R) on the left side of the TV (VIDEO/HD/DVD 2 IN) depending on the cable connection.
	Off	Select to activate the composite video jacks (VIDEO/AUDIO L(MONO)/ AUDIO R) on the left side of the TV.
Menu Color	Enables you to select a specific color for the on-screen settings.	
Image Shift	Corrects the image on your TV. Before adjusting  After adjusting 	
	Auto	(Factory setting) Automatically corrects double images.
	Level 1-4	Select a level from 1-4 to align the images and improve the picture.

If you use the composite connection when Video 2 (Component) is set to Auto, do not connect the component cable at the same time. Otherwise select Off.

(Continued)

Option	*Description*
High Altitude	Select On to use the TV at an altitude of 5,000 feet (1,500 m) or higher. Select Off to use the TV at normal altitude.
CineMotion	Select Auto to optimize the screen display automatically detecting film content and applying a reverse 3-2 pulldown process. Moving picture will appear clearer and more natural looking. Select Off to disable the detection.

Programming Caption Vision

If you selected the Program option under Caption Vision (see page 78), you can change the following settings:

Option	*Description*		
Basic	Allows you to select basic analog (EIA-608) closed caption options.		
	CC1, CC2, CC3, CC4	Displays a printed version of the dialog or sound effects of a program. (Should be set to CC1 for most programs.)	
	Text1, Text2, Text3, Text4	Displays network/station information presented using either half or the whole screen (if available).	
Digital CC	Allows you to set digital closed captioning to Basic (digital EIA-608) or Advanced (digital EIA-708).		
Advanced	Allows you to select advanced digital (EIA-708) closed caption options. Select from the available options.		
Advanced Settings	Allows you to make additional settings for digital (EIA-708) closed caption options. Select from As Broadcast, Small Text, Large Text and Custom.		
	Custom	Allows you to customize the following settings:	
		Character Size	Small, Standard, Large
		Character Style	Style 1-7
		Character Color	Color 1-8
		Character Opacity	Solid, Translucent
		Edge Color	Color 1-8
		Edge Type	None, Raised, Depressed, Outline, Left Shadow, Right Shadow
		Background Color	None, Color 1-8
		Background Opacity	Solid, Translucent
		Window Color	None, Color 1-8
		Window Opacity	Solid, Translucent

Selecting PC Setup Options

To display the PC screen:

Press TV/VIDEO repeatedly on the remote control until VIDEO 7 (PC) appears.

✍ **You can change the settings for the PC input while the TV is displaying the PC screen.**

The PC Input Setup setting includes the following options:

Option	*Description*	
Power Management	On	Select to automatically switch to the Power Saving mode when there is no signal input for 10 minutes.
	Off	Select to turn off Power Management.
Language	Select to display all on-screen settings in your language of choice: English, Español, Français.	
Menu Color	Enables you to select a specific color for the on-screen settings from Original, Gray, Red, Green and Purple.	
Image Shift	Auto	(Factory setting) Automatically corrects double images.
	Level 1-4	Select a level from 1-4 to align the images and improve the picture.
High Altitude	Select On to use the TV at an altitude of 5,000 feet (1,500 m) or higher. Select Off to use the TV at normal altitude.	

PC Input Signal Compatibility Chart

Resolution / Signals	Horizontal (Dot)	×	Vertical (Line)	Horizontal frequency (kHz)	Vertical frequency (Hz)	VESA standard
VGA	**640**	×	**480**	**31.5**	**60**	**–***
	640	×	480	37.5	75	✔
	640	×	480	43.3	85	✔
	720	×	400	31.5	70	–*
SVGA	800	×	600	35.2	56	✔
	800	×	**600**	**37.9**	**60**	✔
	800	×	600	46.9	75	✔
	800	×	600	48.1	72	✔
XGA**	**1024**	×	**768**	**48.4**	**60**	✔
	1024	×	768	56.5	70	✔
	1024	×	768	60	75	✔
WXGA**	**1280**	×	**768**	**47.4**	**60**	✔
	1280	×	**768**	**47.8**	**60**	✔

*: Corresponding to the VGA signal

**: These signals do not support Normal display mode.

✍ **This TV does not support Sync on Green or Composite Sync.**

✍ **If a signal other than in the above chart is input, it may not be displayed properly or may not be displayed as you set.**

✍ **Using the Vertical frequency (Hz) of the personal computer at 60 is recommended.**

✍ **Noise may be detected under certain conditions. If unsupported signals are used, you will see the message, "Unsupported Signal".**

Accessing the Applications Settings

1. Press WEGA GATE.....

2. Select Settings.....

3. Highlight.....

4. Press to select.....



To highlight an option and to change settings, press ↑ ↓ ← →.
Press ⊕ to confirm the selection.
To exit the Applications, press WEGA GATE.

Selecting Applications Options

The Applications settings include the following options:

Option	Description	
Clock/Timers	Select to set the clock and to program your TV to turn on and off at two scheduled viewing times. Once the options are set, TIMER LED lights up in red.	
	Sleep	Allows you to select the amount of time (Off, 15 minutes, 30 minutes, 45 minutes, 60 minutes or 90 minutes) that you want the TV to remain on before shutting off automatically.
	Timer 1 Timer 2	You can use the Timers to program the TV to turn on and off and tune to a specific channel at two scheduled viewing times.

Timer 1 and Timer 2 cannot be set until you set the Current Time.

1 Press ↑ or ↓ to highlight Timer 1 or Timer 2. To set the timer, press →.

✍ **To go directly to programming Timer 1 or 2, press ⊕ instead of pressing →.**

(Continued)

Option	*Description*
	2 Press ↑ or ↓ to highlight one of the following options, then press ⊕. Program — Select to set the Timer by day, time, duration, and channel. Off — Select to turn off the Timer. (Your previous settings are saved.) **3** If you selected Program in step 2, press ↑ and ↓ to set the day(s), hour, minute, AM/PM, duration, and channel number. Press ⊕ or press → to confirm each setting and move to the next setting. Press ← to go back to the previous setting. **4** Press WEGA GATE to exit the setting screen. An LED on the front panel will light, indicating the Timer has been set.
	Current Time — You can set the current time. **1** Press ⊕ to select Current Time. **2** Press ↑ and ↓ to set the current time (day, hour, minute, and AM/PM). Press ⊕ (or press →) to confirm each setting and move to the next setting. Press ← to go back the previous setting. **3** Press WEGA GATE to exit the setting screen.
Diagnostics	Display diagnostics information about the TV. This can be useful in providing information to an authorized technician or repair person.
CableCARD	This list of selectable CableCARD options will vary, depending on your cable service provider.

Other Information

Overview

This chapter includes the following topics:

Topic	Page
Contacting Sony	**85**
Replacing the Lamp	**86**
Troubleshooting	**90**
Specifications	**94**
Optional accessories	**95**
Index	**96**

Contacting Sony

If, after reading these operating instructions, you have additional questions related to the use of your Sony television, please call our Customer Information Services Center.
For US residents: 1-800-222-SONY (7669)
or visit: http://www.sonystyle.com/tv/
For Canadian residents: 1-877-899-SONY (7669)
or visit: http://www.sonystyle.ca/tv/

Before calling Sony customer support, please write down the model and serial numbers of your TV. You'll find this information on the front cover of this manual.

Replacing the Lamp

The projection lamp, which illuminates the picture, has a limited life.

If the screen becomes dark, the color looks unusual, or the LAMP indicator on the front of the TV flashes, it is time to replace the lamp with a new one (not supplied).

> ⚠ **WARNING**
>
> **Electric appliances can cause fire or high temperature, resulting in injury or death. Be sure to follow the instructions below.**

- ❑ Use a Sony XL-2400 replacement lamp (not supplied) for replacement. Use of any other lamp may damage the TV.
- ❑ Do not remove the lamp for any purpose other than replacement. Doing so may cause injury or fire.
- ❑ Do not put flammable materials and metal objects inside the lamp receptacle of the TV after removing the lamp. Doing so may cause fire or electrical shock. Do not touch the lamp receptable once the lamp has been removed.
- ❑ When the lamp eventually burns out, you may hear a noticeable pop sound. This is normal and it is inherent to this type of lamp.
- ❑ In rare instances, the bulb may pop inside the lamp unit, but the lamp unit is designed to contain all of the broken glass pieces inside the lamp unit.
- ❑ The lamps contain mercury. For proper disposal of the used lamps, follow and observe the local ordinances. See page 89.

How to Replace the Lamp

1 Turn off the power on the main unit. Wait several minutes, then unplug the power cord.
(The cooling fan will continue to operate for about two minutes after turning the power off.)

2 Wait at least 30 minutes after unplugging the power cord to allow the lamp to cool down before replacing it. To avoid being burned, do not touch the lamp receptable once the lamp has been removed.

3 Take the new lamp out of the box.
Do not touch the glass portion of the new lamp.

> ✍ **Do not shake the lamp. Vibration can damage the lamp or shorten its life.**
>
> ✍ **Avoid touching the front glass of a new lamp or the glass of the lamp receptacle. This may reduce picture quality or lamp life.**

4 Remove the outside lamp cover.



5 Remove the lamp door.

Turn the knob counterclockwise to OPEN and pull out the cover.



6 Pull out the lamp.

Hook a finger through the loop of the lamp handle and pull the handle upwards. Then pull the lamp straight out.



✍ **The lamp is very hot immediately after use. Never touch the glass portion of the lamp or the surrounding parts.**

✍ **After the used lamp has cooled, place it into the empty box of the replacement lamp. Never put the used lamp into a plastic bag.**

(Continued)

7 Put the new lamp into its place.
Mount the new lamp securely. Failure to do so may cause a fire or the screen to go dark.



✍ **If the lamp is not securely reattached, the self-diagnostic function may be triggered and the POWER/STANDBY indicator flashes three times (see page 12).**

8 Reattach the lamp door.
Turn the knob back to CLOSE and secure the cover.



9 Put the outside lamp cover back in its place.



✍ **Consult your Sony dealer for a Sony XL-2400 replacement lamp.**

✍ **Take great care when replacing the lamp or plugging in/unplugging the connecting cords. Rough handling may cause the TV to fall, damaging the TV, the TV stand and the floor.**

The used lamp

This product contains mercury. Disposal of this product may be regulated if sold in the United States. For disposal or recycling information, please contact your local authorities or the Electronics Industries Alliance (http://www.eiae.org).

- ❑ Do not leave the used lamp near flammable materials or within the reach of children.
- ❑ Do not pour water onto the used lamp or put any object inside the lamp. Doing so may cause the lamp to burst.

For replacement lamp information visit:
U. S. residents: http://www.sonystyle.com/tv/
Canadian residents: http://www.sonystyle.ca/tv/

Troubleshooting

Remote Control

Problem	*Possible Remedies*
Remote control does not operate	❑ The batteries could be weak. Replace the batteries. ❑ Check the orientation of the batteries. ❑ Press TV (FUNCTION) once, and the TV indicator lights up. You may have inadvertently pressed SAT/CABLE (FUNCTION), which changes the remote control to SAT or CABLE mode. ❑ Make sure this unit's power cord is connected securely to the wall outlet. ❑ Install the unit at least 3-4 feet away from fluorescent lights. ❑ If the "High Temperature Warning!" message appears, turn off the TV and wait until the TV's projection lamp cools down (approximately 5 minutes). If the remote control still does not work, make sure to dust the ventilation slots on the rear of the TV and the cooling fan to provide adequate ventilation around the TV.
Cannot change channels with the remote control	❑ If you are using the TV to change channels, first press TV (FUNCTION) once, and the TV indicator lights up. ❑ If you are using another device to change channels, be sure you have not inadvertently switched your TV from the channel 3 or 4 setting. ❑ If you are using another device to change channels, be sure to press FUNCTION for that device. For example, if you are using your cable box to change channels, be sure to press SAT/CABLE (FUNCTION) once, and the SAT/CABLE indicator lights up.
Remote control does not operate non-Sony video equipment	❑ If you replaced the batteries to the remote recently, the code numbers for the video equipment may need to be reset. ❑ There may be more than one code for the equipment that you are attempting to operate. ❑ There is a possibility that some non-Sony equipment cannot be operated by your Sony TV remote. You may need to use the equipment's original remote control.

CableCARD Device

Problem	*Possible Remedies*
Problems using CableCARD device or CableCARD services	❑ Check that the CableCARD is inserted properly (see pages 30-31). ❑ The CableCARD device must be activated by your local cable TV provider before you can receive digital cable TV services. See the activation instructions on pages pages 30-31. ❑ Check the Diagnostics and CableCARD setting options (see page 84). (This can be useful in providing information to an authorized technician or repair person.) ❑ Contact your cable TV provider.

Video

Problem	Possible Remedies
No picture (screen not lit), no sound	❏ If your TV does not turn on and a red light keeps flashing, your TV may need service. Call your local Sony Service Center. ❏ Make sure the power cord is plugged in. ❏ Press POWER on the front of the TV. ❏ Press TV/VIDEO to cycle through the connected video sources. ❏ Try another channel; it could be station trouble.
Dark, poor or no picture (screen lit), good sound	❏ Adjust the Picture Mode option in the Video setting (see page 63). ❏ Adjust the Brightness option in the Video setting (see page 63). ❏ Check the antenna/cable connections.
No color/dark picture/color is not correct	❏ Adjust the Color option in the Video setting (see page 63).
Only snow and noise appear on the screen	❏ Check the antenna/cable connections. ❏ Try another channel; it could be station trouble. ❏ Press ANT to change the input mode (see page 44).
Dotted lines or stripes	❏ Adjust the antenna. ❏ Move the TV away from noise sources such as cars, neon signs, or hair dryers.
Double images	❏ Using a highly directional outdoor antenna or a cable may solve the problem. ❏ Set Image Shift to an appropriate value. The default setting is Auto. If doubled images appear with Auto, select the best value from 1 to 4 (see page 79).
“Black box” on screen	❏ You have selected a text option in the Setup setting and no text is available. (See page 78 to reset Setup selections.) To turn off this feature, set the Caption Vision option to Off. If you were trying to select closed captioning, select CC1 instead of Text 1-4.
Black bands appear at the top and bottom of the screen	❏ Some wide-screen programs are filmed in aspect ratios that are greater than 16:9 (this is especially common with theatrical releases). Your TV will show these programs with black bands at the top and bottom of the screen. For more details, check the documentation that came with your DVD (or contact your program provider).
Certain programs on DVD or other digital sources display a loss of detail, especially during fast-motion or dark scenes	❏ The compression used by certain digital broadcasts and DVDs may cause your TV’s screen to display less detail than usual, or cause artifacts (small blocks or dots, pixelations) to appear on your screen. This is due to your TV’s large screen and ability to show very fine detail, and is normal for certain digitally recorded programs. Adjust the reality/clarity in the DRC Palette setting (see page 64) to optimize the picture while viewing these sources.
"Iris Unit error" appears while Advanced Iris is active	❏ The Iris Control may have a problem. Call your local Sony Service Center.

Audio

Problem	Possible Remedies
Good picture, no sound	❏ Press MUTING so that Muting disappears from the screen (see page 44). ❏ Make sure the Speaker option is set to On in the Audio setting (see page 67). ❏ Make sure the MTS option is set to Stereo or Mono (see page 67). ❏ When the HDMI IN input is in use, surround sound, such as AC-3 and DTS, cannot be input. Change the sound setting for the external input device to Linear PCM.
Audio noise	❏ Communication problems may occur if infrared communication equipment (e.g., infrared cordless headphones) is used near the TV. Use headphones other than infrared cordless headphones. Also, if you use infrared communication equipment other than infrared cordless headphones, move the infrared transceiver away from the TV until the noise is eliminated, or move the transmitter and receiver of the infrared communication equipment closer together.
Cannot gain enough volume when using a cable box	❏ Increase the volume of the cable box using the cable box's remote control. Then press TV(FUNCTION) once (the TV indicator lights up) and adjust the TV's volume.
Sound seems weak or insufficient	❏ The TV's audio might be set to Auto SAP or Mono, when it might be better set to Stereo. In the Audio setting (see page 67), set the MTS setting to Stereo. If already set to Stereo, switch to Mono (which may reduce background noise during weak stereo broadcasts).
Cannot raise the volume on external speakers	❏ If the Speaker option is set to Off and the Audio Out option is set to Fixed (in order to output the sound to your audio system), use your audio receiver to adjust the sound (see page 67). Or, to use the TV remote control, set the Audio Out option to Variable. ❏ To turn on the TV speakers, set the Speaker option to On (see page 67).

Channels

Problem	Possible Remedies
Cannot receive upper channels (UHF) when using an antenna	❏ Press ANT to select the VHF/UHF input (see page 44). ❏ Use Auto Program in the Channel setting to add receivable channels that are not presently in the TV's memory (see page 72).
Cannot receive any channels when using cable TV	❏ Use Auto Program in the Channel setting to add receivable channels that are not presently in the TV's memory (see page 72). ❏ Press ANT to select the CABLE input (see page 44).
Cannot receive or select channels	❏ Use Auto Program in the Channel setting to add receivable channels that are not presently in TV memory (see page 72).
Some digital cable channels are not being displayed	❏ Certain cable companies have limitations on the broadcast of digital cable channels. Check with your cable company for more information. ❏ The digital cable channel may be set to Hidden in the Channel setting (see page 72).

General

Problem	Possible Remedies
How to reset TV to factory settings	❑ Turn on the TV. While holding down the ↑ button on the remote control, press the POWER button on the TV. (The TV will turn itself off, then back on again.) Release the ↑ button. WARNING: The Factory Reset will clear all of your customized settings including Parental Lock setting.
How to restore Video settings to factory settings	❑ Select Reset setting option while in the Video setting (see page 66).
How to restore Audio settings to factory settings	❑ Select Reset setting option while in the Audio setting (see page 66).
Cannot cycle through the other video equipment connected to the TV	❑ Be sure the Label Video Inputs option is not set to Skip (see page 79).
Cannot operate the setting	❑ If a setting option appears in gray, this indicates that the setting option is not available.
Lost password	❑ On the password screen (see page 74), enter the following master password: 4357. The master password clears your previous password; it cannot be used to temporarily unblock channels.
TIMER LED on front panel is lit	❑ When lit, indicates that the timer is set (see page 83). When the timer is set, this LED will remain lit even when the TV is turned off.
LAMP LED blinks in red	❑ Replace the lamp (see page 86).
Digital cable box does not work	❑ If you are connecting a VCR and digital cable box using a splitter, as described on page 35, you must use a special bi-directional splitter that is designed to work with your digital cable box. Contact your cable provider for details.
Cannot record digital channels to VCR	❑ Only analog channels can be recorded to your VCR.
TV cabinet creaks	❑ When the TV is in use, there is a natural rise in temperature, causing the cabinet to expand or contract and may be accompanied by a slight creaking noise. This is not a malfunction.
A slight creaking noise occurs from the bottom part of the TV	❑ Advanced Iris applies a mechanical iris system. When Advanced Iris is set, a natural creaking noise occurs due to the basic structure of the optical unit. The creaking sound is an inherent nature of this system and is not a defect.
The cooling fan is loud	❑ If the TV is used at high altitudes and High Altitude is set to On, the cooling fan runs faster and its sound becomes louder. If the TV is not used at high altitudes, set High Altitude to Off (see page 81).
"High Temperature Warning!" appears	❑ Make sure to remove dust from the ventilation slots on the rear and both sides of the TV. In addition, make sure that there are no obstacles in front of the ventilation slots. If the message still appears after the dust or obstacles are removed, the TV may need servicing. Call your local Sony Service Center.
The TV does not turn on	❑ The TV cools down its projection lamp when the power is turned off. It takes up to two minutes for the picture to come back after the TV is turned on again. Wait for a while until the picture comes back.

Specifications

Projection System	3 LCD Panels, 1 lens projection system	
LCD Panel	0.73 inch TFT LCD panel (1,280 × 720 pixels)	
Projection Lens	High Performance, large diameter hybrid lens F2.4	
Antenna	75-ohm external terminal for VHF/UHF	
Lamp	100W, XL-2400	
Television System	NTSC	American TV Standard
	ATSC (8VSB terrestrial)	ATSC compliant 8VSB
	QAM on cable	ANSI/SCTE 07 2000
Visible Screen Size (Picture measured diagonally)	KDF-E42A10: 42 inches KDF-E50A10: 50 inches	
Channel Coverage	Terrestrial (analog)	2-69
	Cable TV (analog)	1-125
	Terrestrial (digital)	2-69
	Cable TV (digital)	1-135
Number of Inputs/Outputs		
HDMI IN	Video	1080i, 720p, 480p, 480i
	Audio	Two channel linear PCM 32, 44.1 and 48 kHz, 16, 20 and 24 bit
Video (IN)	3 total (1 on side panel)	1 Vp-p, 75 ohms unbalanced, sync negative
S Video (IN)	1	Y: 1 Vp-p, 75 ohms unbalanced, sync negative C: 0.286 Vp-p (Burst signal), 75 ohms
Audio (IN)	5 total (1 on side panel)	500 mVrms (100% modulation) Impedance: 47 kilohms
Component Video Input	2 (Y P_B/C_B P_R/C_R)	Y: 1 Vp-p, 75 ohms unbalanced, sync negative P_B/C_B: 0.7 Vp-p, 75 ohms P_R/C_R: 0.7 Vp-p, 75 ohms
AUDIO (VAR/FIX) OUT	1	500 mVrms at the maximum volume setting (Variable) 500 mVrms (Fixed) Impedance (output): 2 kilohms ✍ AUDIO OUT jacks are operable only when the TV's Speaker is set to Off.
RF Inputs	2	
PC Input	1	
Digital Audio Optical Output (PCM/Dolby Digital)	1	Optical Rectangular (1)
CableCARD Slot	PCMCIA Type I/II	
Speaker output	12 W + 12 W	
Power requirement	120 V, 60 Hz	
Power consumption	In use: 210 W In standby: Less than 17 W	

Dimensions (W/H/D)	KDF-E42A10: 999 × 722 × 357 mm (39 3/8 × 28 1/2 × 14 1/8 inches) KDF-E50A10: 1184 × 827 × 408 mm (46 5/8 × 32 5/8 × 16 1/8 inches)
Mass	KDF-E42A10: 28 kg (61 lb. 12 oz.) KDF-E50A10: 33 kg (72 lb. 13 oz.)
Supplied Accessories	
Remote Control	RM-YD003
AA (R6) Batteries	2 supplied for remote control
Operating Instructions	1
Quick Setup Guide	1
Warranty Card	1
Product Registration Card	1

Optional accessories:

- ❑ HDMI cable
- ❑ HDMI-to-DVI cable
- ❑ Component video cable
- ❑ S VIDEO cable
- ❑ A/V cable
- ❑ Audio cable
- ❑ Optical cable
- ❑ TV Stand : (SU-RG11S for KDF-E42A10, SU-RG11M for KDF-E50A10)
- ❑ Theatre Stand System: RHT-G2000
- ❑ Lamp : XL-2400

✍ **The availability of optional accessories depends on stock.**

Design and specifications are subject to change without notice.
Non-metric weights and measures are approximate.

Index

0-9 buttons 44
4:3 Default 70
5.1 Channel DVD using with remote control 50

A

A/V Sync 67
About Using CableCARD Device 30
AC IN 18
Adding channels to the channel list 72
Adjusting audio, Steady Sound 66
Advanced Iris 63
Advanced Video 65
Alternate Audio 52
Alternate Video 52
ANT button 44
Applications Settings 62, 83
Audio Out 67, 68
AUDIO OUT jack, described 18
Audio receiver, connecting 42
Audio settings 61, 66
Auto Adjustment 71
Auto Program 72

B

Balance, adjusting 66, 68
Bass, adjusting 66, 68
Batteries, inserting in remote 43
BBE 66
Brightness, adjusting 63, 65

C

Cable
  connecting with VCR 34
  using with remote control 49
Cable Box
  connecting with VCR 35
CableCARD device 30, 84
CableCARD slot 17
Camcorder connection 41
Caption Vision 78
  programming 80
Change Password 75
CHANNEL +/– button 15
Channel settings 62, 72
Channel Show/Hide 72
Channels
  Auto Program 72
  creating labels 73
CineMotion 9, 80
Clear White 65
Clock/Timers 83
Closed caption modes 78
Color Temp., adjusting 64, 65
Color, adjusting 63
Connecting
  Audio receiver 42
  Cable box 23–24
  Camcorder 41
  DVD player 38–39
  Personal Computer 40
  Satellite receiver 25
  VCR 34–37

D

Diagnostics 84
DIGITAL AUDIO (OPTICAL) OUT 18
Digital Channels 72
Digital subchannels 52
Display Area 70
DISPLAY button 45
Display Mode 65
Display, turning off 45
DRC Mode 64
DRC Palette 64
DVD player
  using with remote control 49
  with A/V connectors, connecting 39
  with component video connectors, connecting 38

E

Effect 66, 68
English Rating 77
ENT button 44
External Inputs, WEGA GATE 56, 59

F

Favorite Channels
  setting up 72
Favorites, WEGA GATE 56, 57
FREEZE button 45, 54
French Rating 77
FUNCTION button 44

G

Game Picture 69
Gamma 65
GUIDE button 51
Guide menu 52

H

HD/DVD IN jack (1080i/720p/480p/ 480i), described 16, 18
HDMI IN jack, described 17
High Altitude 80, 81
High-Definition Multimedia Interface (HDMI) 10
Horizontal Center 71
Hue, adjusting 63

I

Image Shift 79
Infrared Receiver (IR) 15
Inputs, labeling 79
Iris 63, 65

J, K

JUMP 54
JUMP button 44

L

Label
  Channels 73
Label Video Inputs 79
LAMP LED 15
Lamp, replacing 86–89
Language 79, 81
Live Color 65

M

MENU button 45, 49
Menu Color 79, 81
Movie Rating 76
MTS 67
MUTING button 44

N

Noise Reduction 64

O

Off, turning off the TV 15
On, turning on the TV 15

P, Q

Parental Control, described 9
Parental Lock settings 62, 74
Password, changing 75
PC IN jack 17
PC Input 65, 68, 71, 81
Personal Computer
  connecting 40
Phase 71
Picture 63, 65
PICTURE button 44
Picture Mode
  Custom 63
  Standard 63
  Vivid 63
Pitch 71
POWER button 15
Power Management 81
POWER/STANDBY LED 15
Problems, Troubleshooting 90–93
Program Guide 52
Program Options menu 52

R

Ratings
  setting 76
  viewing blocked programs 75
Remote control
  inserting batteries 43
  programming 47–48
Removing channels from the channel list 72
Removing the CableCARD 31
Reset 63, 65, 66, 68

S

S VIDEO jack, described 18
Satellite receiver
  connecting 25
Satellite receiver, using with remote control 49
Screen settings 61, 69
Select Country 75
Settings
  Applications 62, 83
  Audio 61, 66
  Channel 62, 72
  Parental Lock 62, 74
  Screen 61, 69
  Setup 62, 78
  Video 61, 63
Settings, WEGA GATE 56, 59
Setup settings 62, 78
Sharpness, adjusting 64
Show/Hide Channels 72
Sound Mode 66, 68
Speaker 15, 67, 68
Specifications 94–95
Steady Sound
  adjusting 66
  described 10
Support Belt 14
Surround sound 66, 68

T, U

Timer
  set current 84
TIMER indicator 12
TIMER LED 15
Timer setting 83
Treble, adjusting 66, 68
Troubleshooting 90–93
Turning on/off the TV 15
TV FUNCTION button 44
TV POWER button 45
TV Rating 76
TV/VIDEO button 15, 44
U.S.A. Rating 77
Unrated 76

V

VCR
  using with remote control 49
  with cable box, connecting 35
  with cable, connecting 34
Vertical Center 70, 71
Vertical Size 70
VHF/UHF jack, described 17
Video 2 (Component) 79
Video inputs, labeling 79
Video settings 61, 63
VIDEO/AUDIO (L/R) jacks, described 16, 18
VISUAL SEARCH 45
VOL +/– button 45
VOLUME +/– button 15
Volume Offset 66

W, X, Y

WEGA GATE 9, 55
WEGA GATE button 15
Wide Mode 69, 71
Wide Screen Mode, described 9

http://www.sony.net/

Printed in U.S.A.